

Package: polmineR (via r-universe)

September 7, 2024

Type Package

Title Verbs and Nouns for Corpus Analysis

Version 0.8.9

Date 2023-10-29

Depends R (>= 3.5.0)

Imports methods, data.table (>= 1.12.2), fs, slam, Matrix, tm, DT, xml2, stringi, utils, jsonlite, parallel, pbapply, RcppCWB (>= 0.6.2), magrittr, knitr, lifecycle, rlang, cli

Suggests markdown (>= 1.5), rmarkdown, htmltools (>= 0.4.0), highlight, sendmailR, shiny, shinythemes, shinyjs, miniUI, rhandsontable, testthat, tidytext, covr, igraph, NLP, httr, protolite, curl

VignetteBuilder knitr

Description Package for corpus analysis using the Corpus Workbench ('CWB', <<https://cwb.sourceforge.io>>) as an efficient back end for indexing and querying large corpora. The package offers functionality to flexibly create subcorpora and to carry out basic statistical operations (count, co-occurrences etc.). The original full text of documents can be reconstructed and inspected at any time. Beyond that, the package is intended to serve as an interface to packages implementing advanced statistical procedures. Respective data structures (document-term matrices, term-co-occurrence matrices etc.) can be created based on the indexed corpora.

BugReports <https://github.com/PolMine/polmineR/issues>

Biarch true

License GPL-3

URL <https://github.com/PolMine/polmineR>

Encoding UTF-8

Collate 'polmineR.R' 'S4classes.R' 'p_attributes.R' 'textstat.R'
 'bundle.R' 'corpus.R' 'count.R' 'partition.R'
 'partition_bundle.R' 'ngrams.R' 'features.R' 'context.R'
 'TermDocumentMatrix.R' 'annotations.R' 'as.VCorpus.R'
 'as.markdown.R' 'kwic.R' 'decode.R' 'cooccurrences.R'
 'as.sparseMatrix.R' 'as.speeches.R' 'blapply.R' 'coerce.R'
 'hits.R' 'cpos.R' 'dispersion.R' 'dotplot.R' 'encoding.R'
 'enrich.R' 'format.R' 'highlight.R' 'href.R' 'html.R' 'info.R'
 'means.R' 'noise.R' 'opencpu.R' 'phrases.R'
 'polmineR-defunct.R' 'ranges.R' 'regions.R' 'read.R'
 'registry.R' 'reindex.R' 'renamed.R' 'restore.R'
 's_attributes.R' 'size.R' 'split.R' 'stats.R' 'subset.R'
 'templates.R' 'terms.R' 'token_stream.R' 'tooltips.R'
 'tree_structure.R' 'trim.R' 'type.R' 'use.R' 'utils.R' 'view.R'
 'weigh.R' 'zzz.R'

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

Config/testthat/edition 3

Repository <https://polmine.r-universe.dev>

RemoteUrl <https://github.com/polmine/polminer>

RemoteRef HEAD

RemoteSha 842d4a68540dc8006d851268af6efd2ad681877a

Contents

polmineR-package	4
annotations	6
as.markdown	8
as.sparseMatrix	10
as.speeches	11
as.TermDocumentMatrix	13
as.VCorpus	16
blapply	17
bundle-class	18
capitalize	21
chisquare	22
context	24
context-class	28
context_bundle-class	31
cooccurrences	31
Cooccurrences,corpus-method	36
Cooccurrences-class	41
cooccurrences-class	44
corpus-class	45
corpus-methods	47
count	49

count_class	53
cpos	55
cqp	57
decode-method	59
dispersion	63
dotplot	66
encoding	67
encodings	68
enrich	69
features	70
features-class	72
get_template	73
get_token_stream	74
get_type	79
highlight-method	80
hits	81
hits_class	85
href-function	86
html	87
is_nested	89
kwic	90
kwic-class	95
ll	99
means	102
ngrams	103
ngrams_class	106
noise	106
ocpu_exec	107
partition	108
partition_bundle	111
partition_bundle-class	114
partition_class	116
partition_to_string	118
phrases-class	118
pmi	121
polmineR-defunct	123
polmineR-generics	123
p_attributes	124
ranges	125
ranges-class	127
read	127
regions	130
registry_move	131
renamed	133
size	133
slice	135
subcorpus	136
subcorpus_bundle-class	138

subset-method	140
s_attributes	143
terms	145
textstat-class	146
tooltips-method	151
tree_structure	152
trim	153
t_test	155
use	156
view	157
weigh	158

Index	160
--------------	------------

polmineR-package	<i>polmineR-package</i>
------------------	-------------------------

Description

A library for corpus analysis using the Corpus Workbench (CWB) as an efficient back end for indexing and querying large corpora.

Usage

```
polmineR()
```

Details

The package offers functionality to flexibly create partitions and to carry out basic statistical operations (count, co-occurrences etc.). The original full text of documents can be reconstructed and inspected at any time. Beyond that, the package is intended to serve as an interface to packages implementing advanced statistical procedures. Respective data structures (document term matrices, term co-occurrence matrices etc.) can be created based on the indexed corpora.

A session registry directory (see `registry()`) combines the registry files for corpora that may reside in anywhere on the system. Upon loading 'polmineR', the files in the registry directory defined by the environment variable `CORPUS_REGISTRY` are copied to the session registry directory. To see whether the environment variable `CORPUS_REGISTRY` is set, use the `Sys.getenv()`-function. Corpora wrapped in R data packages can be activated using the function `use()`.

The package includes a draft shiny app that can be called using `polmineR()`.

Package options

- *polmineR.p_attribute*: The default positional attribute.
- *polmineR.left*: Default value for left context.
- *polmineR.lineview*: A logical value to activate lineview output of `kwic()`.
- *polmineR.pagelength*: Maximum number of lines to show when preparing output using `DT::datatable()` (defaults to 10L).

- *polmineR.meta*: Default metadata (s-attributes) to show.
- *polmineR.mc*: Whether to use multiple cores.
- *polmineR.cores*: Number of cores to use. Passed as argument `c1` into `mclapply()`.
- *polmineR.browse*: Whether to show output in browser.
- *polmineR.buttons*: A logical value, whether to display buttons when preparing htmlwidget using `DT::datatable()`.
- *polmineR.specialChars*:
- *polmineR.cutoff*: Maximum number of characters to display when preparing html output.
- *polmineR.mdsb*: A list of pairs of character vectors defining regular expression substitutions applied as part of preprocessing documents for html display. Intended usage: Remove characters that would be misinterpreted as markdown formatting instructions.
- *polmineR.corpus_registry*: The system corpus registry directory defined by the environment variable `CORPUS_REGISTRY` before the `polmineR` package has been loaded. The `polmineR` package uses a temporary registry directory to be able to use corpora stored at multiple locations in one session. The path to the system corpus registry directory captures this setting to keep it available if necessary.
- *polmineR.shiny*: A logical value, whether `polmineR` is used in the context of a shiny app. Used to control the appearance of progress bars depending on whether shiny app is running, or not.
- *polmineR.warn.size*: When generating HTML table widgets (e.g. when preparing `kwic` output to be displayed in RStudio's View pane), the function `DT::datatable()` that is used internally will issue a warning by default if the object size of the table is greater than 1500000. The warning addresses a client-server scenario that is not applicable in the context of a local RStudio session, so you may want to turn it off. Internally, the warning can be suppressed by setting the option `"DT.warn.size"` to `FALSE`. The `polmineR` option `"polmineR.warn.size"` is processed by functions calling `DT::datatable()` to set and reset the value of `"DT.warn.size"`. Please note: The formulation of the warning does not match the scenario of a local RStudio session, but it may still be useful to get a warning when tables are large and slow to process. Therefore, the default value of the setting is `FALSE`.

Author(s)

Andreas Blaette (andreas.blaette@uni-due.de)

References

- Jockers, Matthew L. (2014): *Text Analysis with R for Students of Literature*. Cham et al: Springer.
- Baker, Paul (2006): *Using Corpora in Discourse Analysis*. London: continuum.

Examples

```
# The REUTERS corpus included in the RcppCWB package is used in examples
use(pkg = "RcppCWB", corpus = "REUTERS") # activate REUTERS corpus
r <- corpus("REUTERS")
if (interactive()) show_info(r)
```

```

# The package includes GERMAPARLMINI as sample data
use("polmineR") # activate GERMAPARLMINI
gparl <- corpus("GERMAPARLMINI")
if (interactive()) show_info(gparl)

# Core methods

count("REUTERS", query = "oil")
count("REUTERS", query = c("oil", "barrel"))
count("REUTERS", query = "'Saudi" "Arab.*'", breakdown = TRUE, cqp = TRUE)
dispersion("REUTERS", query = "oil", s_attribute = "id")
k <- kwic("REUTERS", query = "oil")
coocs <- cooccurrences("REUTERS", query = "oil")

# Core methods applied to partition

kuwait <- partition("REUTERS", places = "kuwait", regex = TRUE)
C <- count(kuwait, query = "oil")
D <- dispersion(kuwait, query = "oil", s_attribute = "id")
K <- kwic(kuwait, query = "oil", meta = "id")
CO <- cooccurrences(kuwait, query = "oil")

# Go back to full text

p <- partition("REUTERS", id = 127)
if (interactive()) read(p)
h <- html(p) %>%
  highlight(highlight = list(yellow = "oil"))
if (interactive()) h_highlighted

# Generate term document matrix (not run by default to save time)

pb <- partition_bundle("REUTERS", s_attribute = "id")
cnt <- count(pb, p_attribute = "word")
tdm <- as.TermDocumentMatrix(cnt, col = "count")

```

 annotations

Annotation functionality

Description

Objects that contain analytical results (kwic objects, objects inheriting from the `textstat` class) can be annotated by creating an annotation layer using the `annotations`-method. The augmented object can be annotated using a shiny gadget by invoking the `edit`-method on it. Note that operations are deliberately in-place, to prevent an unwanted loss of work.

Usage

```

annotations(x, ...)

## S4 method for signature 'kwic'
annotations(x, i, j, value)

## S4 method for signature 'textstat'
annotations(x, i, j, value)

annotations(x) <- value

## S4 replacement method for signature 'kwic,list'
annotations(x) <- value

## S4 replacement method for signature 'textstat,list'
annotations(x) <- value

## S4 method for signature 'textstat'
edit(name, viewer = shiny::paneViewer(minHeight = 550), ...)

```

Arguments

x	An object to be annotated, a kwic class object, or an object inheriting from the textstat class.
...	Passed into rhandsontable::rhandsontable, can be used for settings such as height etc.
i	The row number (single integer value) of the data.table where a new value shall be assigned.
j	The column number (single integer value) of the data.table where a new value shall be assigned.
value	A value to assign.
name	An S4 object to be annotated.
viewer	The viewer to use, see viewer .

Details

The edit-method is designed to be used in a RStudio session. It generates a shiny gadget (see <https://shiny.rstudio.com/articles/gadgets.html>) shown in the viewer pane of RStudio.

The edit-method returns the modified input object. Note however that changes of annotations are deliberately in-place operations: The input object is changed even if you do not close the gadget "properly" by hitting the "Done" button and catch the modified object. That may be forgotten easily and would be painful after the work that may have been invested.

Consult the examples for the intended workflow.

Value

The modified input object is returned invisibly.

Examples

```

use(pkg = "RcppCWB", corpus = "REUTERS")

a <- 2
# upon initializing a kwic object, there is a minimal labels object
# in the labels slot of the kwic object, which we can get using the
# annotations-method
o <- kwic("REUTERS", query = "oil")
annotations(o) # see the result (a data.table)

# assign new annotations as follows, using the reference semantics of the
# data.table you get by calling the labels-method on an object
annotations(o) <- list(name = "class", what = factor(x = "a", levels = c("a", "b", "c")))
annotations(o) <- list(name = "description", what = "")
annotations(o) # inspect the result

# assign values; note that is an in-place operation using the reference
# semantics of the data.table
# annotations(o, i = 77, j = 1, value = FALSE)
# annotations(o, i = 78, j = 1, value = FALSE)
annotations(o)

## Not run:
edit(o)
annotations(o) # to see changes made

# maybe we want additional metadata
enrich(o, s_attributes = "places")
edit(o)
annotations(o)

# to get some extra context
o <- enrich(o, extra = 5L, table = TRUE)
edit(o)

# lineview may be better when you use a lot of extra context
options(polmineR.lineview = TRUE)
o <- kwic("REUTERS", "oil")
o <- enrich(o, extra = 20L)
edit(o)

x <- cooccurrences("REUTERS", query = "oil")
annotations(x) <- list(name = "keep", what = TRUE)
annotations(x) <- list(name = "category", what = factor("a", levels = letters[1:10]))
edit(x)

## End(Not run)

```

Description

The method is the worker behind the `read()`-method, which will be called usually to reconstruct the full text of a partition and read it. The `as.markdown()`-method can be customized for different classes inheriting from the partition-class.

Usage

```
as.markdown(.Object, ...)  
  
## S4 method for signature 'partition'  
as.markdown(  
  .Object,  
  meta = getOption("polmineR.meta"),  
  template = get_template(.Object),  
  cpos = TRUE,  
  cutoff = NULL,  
  verbose = FALSE,  
  ...  
)  
  
## S4 method for signature 'subcorpus'  
as.markdown(  
  .Object,  
  meta = getOption("polmineR.meta"),  
  template = get_template(.Object),  
  cpos = TRUE,  
  cutoff = NULL,  
  verbose = FALSE,  
  ...  
)  
  
## S4 method for signature 'plpr_partition'  
as.markdown(  
  .Object,  
  meta = NULL,  
  template = get_template(.Object),  
  cpos = FALSE,  
  interjections = TRUE,  
  cutoff = NULL,  
  ...  
)  
  
## S4 method for signature 'plpr_subcorpus'  
as.markdown(  
  .Object,  
  meta = NULL,  
  template = get_template(.Object),  
  cpos = FALSE,
```

```

interjections = TRUE,
cutoff = NULL,
...
)

```

Arguments

.Object	The object to be converted, a partition, or a class inheriting from partition, such as plpr_partition.
...	further arguments
meta	The metainformation (s-attributes) to be displayed.
template	A template for formatting output.
cpos	A logical value, whether to add cpos as ids in span elements.
cutoff	The maximum number of tokens to reconstruct, to avoid that full text is excessively long.
verbose	A logical value, whether to output messages.
interjections	A logical value, whether to format interjections.

Examples

```

use(pkg = "RcppCWB", corpus = "REUTERS")

P <- partition("REUTERS", places = "argentina")
as.markdown(P)
as.markdown(P, meta = c("id", "places"))
if (interactive()) read(P, meta = c("id", "places"))

```

as.sparseMatrix

Type conversion - get sparseMatrix.

Description

Turn objects into the sparseMatrix as defined in the Matrix package.

Usage

```

as.sparseMatrix(x, ...)

## S4 method for signature 'simple_triplet_matrix'
as.sparseMatrix(x, ...)

## S4 method for signature 'TermDocumentMatrix'
as.sparseMatrix(x, ...)

## S4 method for signature 'DocumentTermMatrix'
as.sparseMatrix(x, ...)

```

```
## S4 method for signature 'bundle'
as.sparseMatrix(x, col, ...)
```

Arguments

x	object to convert
...	Further arguments that are passed to a call to <code>sparseMatrix</code> . Can be used, for instance to set <code>giveCsparse</code> to <code>FALSE</code> to get a <code>dgTMatrix</code> , not a <code>dgCMatrix</code> .
col	column name to get values from (if x is a bundle)

as.speeches	<i>Split corpus or partition into speeches.</i>
-------------	---

Description

Split entire corpus or a partition into speeches. The heuristic is to split the corpus/partition into partitions on day-to-day basis first, using the s-attribute provided by `s_attribute_date`. These subcorpora are then splitted into speeches by speaker name, using s-attribute `s_attribute_name`. If there is a gap larger than the number of tokens supplied by argument `gap`, contributions of a speaker are assumed to be two separate speeches.

Usage

```
as.speeches(.Object, ...)

## S4 method for signature 'partition'
as.speeches(
  .Object,
  s_attribute_date = grep("date", s_attributes(.Object), value = TRUE),
  s_attribute_name = grep("name", s_attributes(.Object), value = TRUE),
  gap = 500,
  mc = FALSE,
  verbose = TRUE,
  progress = TRUE
)

## S4 method for signature 'subcorpus'
as.speeches(
  .Object,
  s_attribute_date = grep("date", s_attributes(.Object), value = TRUE),
  s_attribute_name = grep("name", s_attributes(.Object), value = TRUE),
  gap = 500,
  mc = FALSE,
  verbose = TRUE,
  progress = TRUE
)
```

```

)

## S4 method for signature 'corpus'
as.speeches(
  .Object,
  s_attribute_date = grep("date", s_attributes(.Object), value = TRUE),
  s_attribute_name = grep("name", s_attributes(.Object), value = TRUE),
  gap = 500,
  subset,
  mc = FALSE,
  verbose = TRUE,
  progress = TRUE
)

## S4 method for signature 'character'
as.speeches(
  .Object,
  s_attribute_date = grep("date", s_attributes(.Object), value = TRUE),
  s_attribute_name = grep("name", s_attributes(.Object), value = TRUE),
  gap = 500,
  mc = FALSE,
  verbose = TRUE,
  progress = TRUE
)

```

Arguments

<code>.Object</code>	A partition, or length-one character vector indicating a CWB corpus.
<code>...</code>	Further arguments.
<code>s_attribute_date</code>	A length-one character vector, the s-attribute that provides the dates of sessions.
<code>s_attribute_name</code>	A length-one character vector, the s-attribute that provides the names of speakers.
<code>gap</code>	An integer value, the number of tokens between strucs assumed to make the difference whether a speech has been interrupted (by an interjection or question), or whether to assume separate speeches.
<code>mc</code>	Whether to use multicore, defaults to FALSE. If <code>progress</code> is TRUE, argument <code>mc</code> is passed into <code>pblapply</code> as argument <code>cl</code> . If <code>progress</code> is FALSE, <code>mc</code> is passed into <code>mclapply()</code> as argument <code>mc.cores</code> .
<code>verbose</code>	A logical value, defaults to TRUE.
<code>progress</code>	A logical value, whether to show progress bar.
<code>subset</code>	A logical expression evaluated in a temporary <code>data.table</code> with columns 'speaker' and 'date' to define a subset of the entire corpus to be turned into speeches. Usually faster than applying <code>as.speeches()</code> on a partition or subcorpus.

Value

A partition_bundle, the names of the objects in the bundle are the speaker name, the date of the speech and an index for the number of the speech on a given day, concatenated by underscores.

Examples

```
## Not run:
use("polmineR")
speeches <- as.speeches(
  "GERMAPARLMINI",
  s_attribute_date = "date", s_attribute_name = "speaker"
)
speeches_count <- count(speeches, p_attribute = "word")
tdm <- as.TermDocumentMatrix(speeches_count, col = "count")

bt <- partition("GERMAPARLMINI", date = "2009-10-27")
speeches <- as.speeches(
  bt,
  s_attribute_name = "speaker",
  s_attribute_date = "date"
)
summary(speeches)

## End(Not run)
## Not run:
#' sp <- corpus("GERMAPARLMINI") %>%
  as.speeches(s_attribute_name = "speaker", s_attribute_date = "date")

sp <- corpus("GERMAPARLMINI") %>%
  as.speeches(
    s_attribute_name = "speaker",
    s_attribute_date = "date",
    subset = {date == as.Date("2009-11-11")},
    progress = FALSE
  )

sp <- corpus("GERMAPARLMINI") %>%
  as.speeches(
    s_attribute_name = "speaker",
    s_attribute_date = "date",
    subset = {date == "2009-11-10" & grepl("Merkel", speaker)},
    progress = FALSE
  )

## End(Not run)
```

Description

Methods to generate the classes TermDocumentMatrix or DocumentTermMatrix as defined in the tm package. There are many text mining applications for document-term matrices. A DocumentTermMatrix is required as input by the topicmodels package, for instance.

Usage

```

as.TermDocumentMatrix(x, ...)

as.DocumentTermMatrix(x, ...)

## S4 method for signature 'character'
as.TermDocumentMatrix(x, p_attribute, s_attribute, verbose = TRUE, ...)

## S4 method for signature 'corpus'
as.DocumentTermMatrix(
  x,
  p_attribute,
  s_attribute,
  stoplist = NULL,
  binarize = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'character'
as.DocumentTermMatrix(x, p_attribute, s_attribute, verbose = TRUE, ...)

## S4 method for signature 'bundle'
as.TermDocumentMatrix(x, col, p_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'bundle'
as.DocumentTermMatrix(x, col = NULL, p_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'partition_bundle'
as.DocumentTermMatrix(x, p_attribute = NULL, col = NULL, verbose = TRUE, ...)

## S4 method for signature 'partition_bundle'
as.TermDocumentMatrix(x, p_attribute = NULL, col = NULL, verbose = TRUE, ...)

## S4 method for signature 'subcorpus_bundle'
as.TermDocumentMatrix(x, p_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'subcorpus_bundle'
as.DocumentTermMatrix(x, p_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'partition_bundle'
as.DocumentTermMatrix(x, p_attribute = NULL, col = NULL, verbose = TRUE, ...)

```

```
## S4 method for signature 'context'
as.DocumentTermMatrix(x, p_attribute, verbose = TRUE, ...)

## S4 method for signature 'context'
as.TermDocumentMatrix(x, p_attribute, verbose = TRUE, ...)
```

Arguments

x	A character vector indicating a corpus, or an object of class <code>bundle</code> , or inheriting from class <code>bundle</code> (e.g. <code>partition_bundle</code>).
...	Definitions of s-attribute used for subsetting the corpus, compare <code>partition-method</code> .
p_attribute	A p-attribute counting is be based on.
s_attribute	An s-attribute that defines content of columns, or rows.
verbose	A logical value, whether to output progress messages.
stoplist	A character vector of tokens to exclude from the matrix, as memory efficient way to exclude irrelevant terms early on.
binarize	A logical value. If TRUE, report occurrence of term, not absolute count.
col	The column of data.table in slot <code>stat</code> (if x is a bundle) to use of assembling the matrix.

Details

If x refers to a corpus (i.e. is a length 1 character vector), a `TermDocumentMatrix`, or `DocumentTermMatrix` will be generated for subsets of the corpus based on the `s_attribute` provided. Counts are performed for the `p_attribute`. Further parameters provided (passed in as ... are interpreted as s-attributes that define a subset of the corpus for splitting it according to `s_attribute`. If struct values for `s_attribute` are not unique, the necessary aggregation is performed, slowing things somewhat down.

If x is a bundle or a class inheriting from it, the counts or whatever measure is present in the `stat` slots (in the column indicated by `col`) will be turned into the values of the sparse matrix that is generated. A special case is the generation of the sparse matrix based on a `partition_bundle` that does not yet include counts. In this case, a `p_attribute` needs to be provided. Then counting will be performed, too.

If x is a `partition_bundle`, and argument `col` is not NULL, as `TermDocumentMatrix` is generated based on the column indicated by `col` of the `data.table` with counts in the `stat` slots of the objects in the bundle. If `col` is NULL, the p-attribute indicated by `p_attribute` is decoded, and a count is performed to obtain the values of the resulting `TermDocumentMatrix`. The same procedure applies to get a `DocumentTermMatrix`.

If x is a `subcorpus_bundle`, the p-attribute provided by argument `p_attribute` is decoded, and a count is performed to obtain the resulting `TermDocumentMatrix` or `DocumentTermMatrix`.

Value

A `TermDocumentMatrix`, or a `DocumentTermMatrix` object. These classes are defined in the `tm` package, and inherit from the `simple_triplet_matrix`-class defined in the `slam`-package.

Author(s)

Andreas Blaette

Examples

```
# examples not run by default to save time on CRAN test machines

#' use(pkg = "RcppCWB", corpus = "REUTERS")

# enriching partition_bundle explicitly
tdm <- corpus("REUTERS") %>%
  partition_bundle(s_attribute = "id") %>%
  enrich(p_attribute = "word") %>%
  as.TermDocumentMatrix(col = "count")

# leave the counting to the as.TermDocumentMatrix-method
tdm <- partition_bundle("REUTERS", s_attribute = "id") %>%
  as.TermDocumentMatrix(p_attribute = "word", verbose = FALSE)

# obtain TermDocumentMatrix directly (fastest option)
tdm <- as.TermDocumentMatrix(
  "REUTERS",
  p_attribute = "word",
  s_attribute = "id",
  verbose = FALSE
)

# workflow using split()
dtm <- corpus("REUTERS") %>%
  split(s_attribute = "id") %>%
  as.TermDocumentMatrix(p_attribute = "word")
```

as.VCorpus

*Get VCorpus.***Description**

Retrieve full text for the subcorpora or partition objects in a subcorpus_bundle or partition_bundle and generate a VCorpus-class object from the tm-package.

Usage

```
## S4 method for signature 'partition_bundle'
as.VCorpus(x)
```

Arguments

x A partition_bundle object.

Details

The VCorpus class of the tm-package offers an interface to access the functionality of the tm-package. Note however that generating a VCorpus to get a DocumentTermMatrix, or a TermDocumentMatrix is a highly inefficient detour. Applying the as.DocumentTermMatrix or as.TermDocumentMatrix methods on a partition_bundle is the recommended approach.

If the tm-package has been loaded, the as.VCorpus-method included in the polmineR-package may become inaccessible. To deal with this (probable) scenario, it is possible to use a coerce-method (as(YOUROBJECT, "VCorpus")), see examples.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

pb <- corpus("REUTERS") %>%
  partition_bundle(s_attribute = "id")

vc <- as.VCorpus(pb) # works only, if tm-package has not yet been loaded
vc <- as(pb, "VCorpus") # will work if tm-package has been loaded, too

vc <- corpus("REUTERS") %>%
  split(s_attribute = "id") %>%
  as("VCorpus")
```

blapply

apply a function over a list or bundle

Description

Very similar to lapply, but applicable to bundle-objects, in particular. The purpose of the method is to supply a uniform and convenient parallel backend for the polmineR package. In particular, progress bars are supported (the naming of the method is derived from bla bla).

Usage

```
blapply(x, ...)

## S4 method for signature 'list'
blapply(x, f, mc = TRUE, progress = TRUE, verbose = FALSE, ...)

## S4 method for signature 'vector'
blapply(x, f, mc = FALSE, progress = TRUE, verbose = FALSE, ...)

## S4 method for signature 'bundle'
blapply(x, f, mc = FALSE, progress = TRUE, verbose = FALSE, ...)
```

Arguments

x	a list or a bundle object
...	further parameters
f	a function that can be applied to each object contained in the bundle, note that it should swallow the parameters mc, verbose and progress (use ... to catch these params)
mc	logical, whether to use multicore - if TRUE, the number of cores will be taken from the polmineR-options
progress	logical, whether to display progress bar
verbose	logical, whether to print intermediate messages

Examples

```
use("polmineR")
bt <- partition("GERMAPARLMINI", date = ".*", regex=TRUE)
speeches <- as.speeches(bt, s_attribute_date = "date", s_attribute_name = "speaker")
foo <- blapply(speeches, function(x, ...) slot(x, "cpos"))
```

bundle-class

Bundle Class

Description

A bundle is used to combine several objects (partition, context, features, cooccurrences objects) into one S4 class object. Typically, a class inheriting from the bundle superclass will be used. When working with a context_bundle, a features_bundle, a cooccurrences_bundle, or a context_bundle, a similar set of standard methods is available to perform transformations.

Usage

```
## S4 replacement method for signature 'bundle'
name(x) <- value

## S4 method for signature 'bundle'
length(x)

## S4 method for signature 'bundle'
names(x)

## S4 replacement method for signature 'bundle,vector'
names(x) <- value

## S4 method for signature 'bundle'
unique(x)
```

```
## S4 method for signature 'bundle,bundle'  
e1 + e2  
  
## S4 method for signature 'bundle,textstat'  
e1 + e2  
  
## S4 method for signature 'bundle'  
x[[i]]  
  
## S4 method for signature 'bundle,ANY,ANY,ANY'  
x[i]  
  
## S4 replacement method for signature 'bundle'  
x[[i]] <- value  
  
## S4 method for signature 'bundle'  
x$name  
  
## S4 replacement method for signature 'bundle'  
x$name <- value  
  
## S4 method for signature 'bundle'  
sample(x, size)  
  
## S4 method for signature 'list'  
as.bundle(object, ...)  
  
## S4 method for signature 'textstat'  
as.bundle(object)  
  
## S3 method for class 'bundle'  
as.data.table(x, keep.rownames, col, ...)  
  
## S4 method for signature 'bundle'  
as.matrix(x, col)  
  
## S4 method for signature 'bundle'  
subset(x, ...)  
  
## S4 method for signature 'bundle'  
as.list(x)  
  
## S3 method for class 'bundle'  
as.list(x, ...)  
  
## S4 method for signature 'bundle'  
get_corpus(x)
```

Arguments

x	a bundle object
value	character string with a name to be assigned
e1	object 1
e2	object 2
i	integer or character values for indexing a bundle object.
name	The name of an object in the bundle object.
size	number of items to choose to generate a sample
object	A bundle object.
...	Further parameters
keep.rownames	Required argument to safeguard consistency with S3 method definition in the <code>data.table</code> package. Unused in this context.
col	columns of the <code>data.table</code> to use to generate an object.

Slots

corpus The CWB corpus the xobjects in the bundle are based on, a length 1 character vector.

objects An object of class `list`.

p_attribute Object of class `character`.

encoding The encoding of the corpus.

Author(s)

Andreas Blaette

Examples

```
use("RcppCWB", "REUTERS")

# generate bundle with articles in REUTERS corpus
b <- partition_bundle("REUTERS", s_attribute = "id")

# basic operations
length(b)
names(b)
get_corpus(b)
summary(b)

# enrich with count for p-attribute
b <- enrich(b, p_attribute = "word")

# Indexing and accessing bundle objects
reu <- corpus("REUTERS") %>% split(s_attribute = "id")
reu[1:3]
reu[-1]
reu[-(1:10)]
```

```
reu["127"]
reu$`127` # alternative access
reu[c("127", "273")]
reu[["127"]] <- NULL
pb <- partition_bundle("GERMAPARLMINI", s_attribute = "party")
pb$"NA" <- NULL # quotation needed if name is "NA"

# Turn bundle into data.table (not tested to save time)

dt <- partition_bundle("REUTERS", s_attribute = "id") %>%
  cooccurrences(query = "oil", cqp = FALSE) %>%
  as.data.table(col = "l1")
```

capitalize

Capitalize character vector.

Description

Make the first character of the elements of a character vector have upper case and the rest lower case.

Usage

```
capitalize(x)
```

Arguments

x A character vector.

Details

The `capitalize()` function may be useful when applying lowercased dictionaries of stoplists, a sentiment dictionary etc. on a CWB corpus that maintains capitalization (tokens are not lower-cased).

This function is inspired by a method Python offers for string objects.

Examples

```
capitalize(c("oil", "corpus", "data"))
```

chisquare *Perform chisquare-text.*

Description

Perform Chisquare-Test based on a table with counts

Usage

```
chisquare(.Object)

## S4 method for signature 'features'
chisquare(.Object)

## S4 method for signature 'context'
chisquare(.Object)

## S4 method for signature 'cooccurrences'
chisquare(.Object)
```

Arguments

.Object A features object, or an object inheriting from it (context, cooccurrences).

Details

The basis for computing for the chi square test is a contingency table of observations, which is prepared for every single token in the corpus. It reports counts for a token to inspect and all other tokens in a corpus of interest (coi) and a reference corpus (ref):

	coi	ref	TOTAL
count token	o_{11}	o_{12}	r_1
other tokens	o_{21}	o_{22}	r_2
TOTAL	c_1	c_2	N

Based on the contingency table, expected values are calculated for each cell, as the product of the column and margin sums, divided by the overall number of tokens (see example). The standard formula for calculating the chi-square test is computed as follows.

$$X^2 = \sum \frac{(O_{ij} - E_{ij})^2}{O_{ij}}$$

Results from the chisquare test are only robust for at least 5 observed counts in the corpus of interest. Usually, results need to be filtered accordingly (see examples).

Value

Same class as input object, with enriched table in the stat-slot.

Author(s)

Andreas Blaette

References

Manning, Christopher D.; Schuetze, Hinrich (1999): *Foundations of Statistical Natural Language Processing*. MIT Press: Cambridge, Mass., pp. 169-172.

Kilgarriff, A. and Rose, T. (1998): Measures for corpus similarity and homogeneity. *Proc. 3rd Conf. on Empirical Methods in Natural Language Processing*. Granada, Spain, pp 46-52.

See Also

Other statistical methods: [ll\(\)](#), [pmi\(\)](#), [t_test\(\)](#)

Examples

```
use("polmineR")
library(data.table)
m <- partition(
  "GERMAPARLMINI", speaker = "Merkel", interjection = "speech",
  regex = TRUE, p_attribute = "word"
)
f <- features(m, "GERMAPARLMINI", included = TRUE)
f_min <- subset(f, count_coi >= 5)
summary(f_min)

## Not run:

# A sample do-it-yourself calculation for chisquare:

# (a) prepare matrix with observed values
o <- matrix(data = rep(NA, 4), ncol = 2)
o[1,1] <- as.data.table(m)[word == "Weg"][["count"]]
o[1,2] <- count("GERMAPARLMINI", query = "Weg")[["count"]] - o[1,1]
o[2,1] <- size(f)[["coi"]] - o[1,1]
o[2,2] <- size(f)[["ref"]] - o[1,2]

# prepare matrix with expected values, calculate margin sums first

r <- rowSums(o)
c <- colSums(o)
N <- sum(o)

e <- matrix(data = rep(NA, 4), ncol = 2)
e[1,1] <- r[1] * (c[1] / N)
e[1,2] <- r[1] * (c[2] / N)
e[2,1] <- r[2] * (c[1] / N)
e[2,2] <- r[2] * (c[2] / N)
```

```

# compute chisquare statistic

y <- matrix(rep(NA, 4), ncol = 2)
for (i in 1:2) for (j in 1:2) y[i,j] <- (o[i,j] - e[i,j])^2 / e[i,j]
chisquare_value <- sum(y)

as(f, "data.table")[word == "Weg"][["chisquare"]]

## End(Not run)

```

context

Analyze context of a node word.

Description

Retrieve the word context of a token, optionally checking for boundaries of a XML region.

Usage

```
context(.Object, ...)
```

```

## S4 method for signature 'slice'
context(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  p_attribute = getOption("polmineR.p_attribute"),
  region = NULL,
  boundary = NULL,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  count = TRUE,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = TRUE,
  ...
)

```

```

## S4 method for signature 'partition'
context(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,

```

```
    left = getOption("polmineR.left"),
    right = getOption("polmineR.right"),
    p_attribute = getOption("polmineR.p_attribute"),
    region = NULL,
    boundary = NULL,
    stoplist = NULL,
    positivelist = NULL,
    regex = FALSE,
    count = TRUE,
    mc = getOption("polmineR.mc"),
    verbose = FALSE,
    progress = TRUE,
    ...
)

## S4 method for signature 'subcorpus'
context(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  p_attribute = getOption("polmineR.p_attribute"),
  region = NULL,
  boundary = NULL,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  count = TRUE,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = TRUE,
  ...
)

## S4 method for signature 'matrix'
context(
  .Object,
  corpus,
  registry = Sys.getenv("CORPUS_REGISTRY"),
  left,
  right,
  p_attribute,
  region = NULL,
  boundary = NULL
)
```

```
## S4 method for signature 'corpus'
context(
  .Object,
  query,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  region = NULL,
  boundary = NULL,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  count = TRUE,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = TRUE,
  ...
)

## S4 method for signature 'character'
context(
  .Object,
  query,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  region = NULL,
  boundary = NULL,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  count = TRUE,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = TRUE,
  ...
)

## S4 method for signature 'partition_bundle'
context(
  .Object,
  query,
  p_attribute,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
```

```

    verbose = TRUE,
    ...
)

## S4 method for signature 'cooccurrences'
context(.Object, query, check = TRUE, complete = FALSE)

```

Arguments

<code>.Object</code>	a partition or a partition_bundle object
<code>...</code>	Further parameters.
<code>query</code>	A query, which may be a character vector or a CQP query.
<code>cqp</code>	defaults to <code>is.cqp</code> -function, or provide TRUE/FALSE
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .
<code>left</code>	A single integer value defining the number of tokens to the left of the query match to include in the context. Advanced usage: (a) If <code>left</code> is a length-one character vector stating an s-attribute, the context will be expanded to the (left) boundary of the region where the match occurs. (b) If <code>left</code> is a named length-one integer vector, this value is the number regions of the structural attribute referred to by the vector's name to the left of the query match that are included in the context.
<code>right</code>	A single integer value, a length-one character vector or a named length-one integer value, with equivalent effects to argument <code>left</code> .
<code>p_attribute</code>	The p-attribute of the query.
<code>region</code>	An s-attribute, given by a length-one character vector. The context of query matches will be expanded to the left and right boundary of the region where the match is located. If arguments <code>left</code> and <code>right</code> are > 1, the left and right boundaries of the respective number of regions will be identified.
<code>boundary</code>	If provided, a length-one character vector specifying a s-attribute. It will be checked that corpus positions do not extend beyond the region defined by the s-attribute.
<code>stoplist</code>	Exclude match for query if stopword(s) is/are present in context. See <code>positivelist</code> for further explanation.
<code>positivelist</code>	A character vector or numeric/integer vector: include a query hit only if token in <code>positivelist</code> is present. If <code>positivelist</code> is a character vector, it may include regular expressions (see parameter <code>regex</code>).
<code>regex</code>	A logical value, defaults to FALSE - whether <code>stoplist</code> and/or <code>positivelist</code> are regular expressions.
<code>count</code>	logical
<code>mc</code>	Whether to use multicore; if NULL (default), the function will get the value from the options.
<code>verbose</code>	Report progress? A logical value, defaults to TRUE.
<code>progress</code>	A logical value, whether to show progress bar.
<code>corpus</code>	A length-one character vector stating a corpus ID.

registry	The registry directory with the registry file for corpus.
complete	enhance completely

Details

For formulating the query, CPQ syntax may be used (see examples). Statistical tests available are log-likelihood, t-test, pmi.

If `.Object` is a matrix, the `context`-method will call `RcppCWB::region_matrix_context()`, the worker behind the `context()`-method.

Value

depending on whether a `partition` or a `partition_bundle` serves as input, the return will be a context object, or a `context_bundle` object. Note that the number of objects in the `context_bundle` may differ from the number of objects in the input bundle object: NULL objects that result if no hit is obtained are dropped.

Author(s)

Andreas Blaette

Examples

```
use("polmineR")
p <- partition("GERMAPARLMINI", interjection = "speech")
y <- context(p, query = "Integration", p_attribute = "word")
y <- context(p, query = "Integration", p_attribute = "word", positivelist = "Bildung")
y <- context(
  p, query = "Integration", p_attribute = "word",
  positivelist = c("[aA]rbeit.*", "Ausbildung"), regex = TRUE
)
```

context-class

Context class.

Description

Class to organize information of context analysis.

Usage

```
## S4 method for signature 'context'
length(x)

## S4 method for signature 'context'
p_attributes(.Object)

## S4 method for signature 'context'
```

```

count(.Object)

## S4 method for signature 'context'
sample(x, size)

## S4 method for signature 'context'
enrich(
  .Object,
  s_attribute = NULL,
  p_attribute = NULL,
  decode = FALSE,
  stat = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'context'
as.regions(x, node = TRUE)

## S4 method for signature 'context'
trim(
  .Object,
  s_attribute = NULL,
  positivelist = NULL,
  p_attribute = p_attributes(.Object),
  regex = FALSE,
  stoplist = NULL,
  fn = NULL,
  verbose = TRUE,
  progress = TRUE,
  ...
)

```

Arguments

x	A context object.
.Object	A context object.
size	An integer indicating sample size.
s_attribute	The s-attribute(s) to add to data.table in slot cpos.
p_attribute	The p-attribute(s) to add to data.table in slot cpos.
decode	A logical value, whether to convert integer ids to expressive strings.
stat	A logical value, whether to generate / update slot stat from the cpos table.
verbose	A logical, whether to be talkative.
...	To maintain backwards compatibility if argument pAttribute is still used.
node	A logical value, whether to include the node (i.e. query matches) in the region matrix generated when creating a partition from a context-object.

positivelist	Tokens that are required to be present to keep a match.
regex	A logical value, whether arguments positivlist / stoplist are interpreted as regular expressions.
stoplist	Tokens that are used to exclude a match.
fn	A function that will be applied on context tables splitted by match_id.
progress	A logical value, whether to show progress bar

Details

Objects of the class context include a `data.table` in the slot `cpos`. The `data.table` will at least include the columns "match_id", "cpos" and "position".

The `length`-method will return the number of hits that were achieved.

The `enrich()`-method can be used to add additional information to the `data.table` in the `cpos`-slot of a context-object.

Slots

query	The query examined (character).
count	An integer value, the number of hits for the query.
partition	The partition the context object is based on.
size_partition	The size of the partition, a length-one integer vector.
left	A length-one integer value, the number of tokens to the left of the query match.
right	An integer value, the number of tokens to the right of the query match.
size	A length-one integer value, the number of tokens covered by the context-object, i.e. the number of tokens in the right and left context of the node as well as query matches.
size_match	A length-one integer value, the number of tokens matches by the query. Identical with the value in slot count if the query is <i>not</i> a CQP query.
size_coi	A length-one integer value, the number of tokens in the right and left context of the node (excluding query matches).
size_ref	A length-one integer value, the number of tokens in the partition, without tokens matched and the tokens in the left and right context.
boundary	An s-attribute (character).
p_attribute	The p-attribute of the query (character).
corpus	The CWB corpus used (character).
stat	A <code>data.table</code> , the statistics of the analysis.
encoding	Object of class character, encoding of the corpus.
cpos	A <code>data.table</code> , with the columns <code>match_id</code> , <code>cpos</code> , <code>position</code> , <code>word_id</code> .
method	A character-vector, statistical test used.
call	Object of class character, call that generated the object.

Examples

```
# Keep matches for 'oil' only if first position to the left is 'crude'
.fn <- function(x) if (x[position == -1L][["word"]] == "crude") x else NULL
crude_oil <- context("REUTERS", "oil") %>%
  enrich(p_attribute = "word", decode = TRUE) %>%
  trim(fn = .fn)
```

context_bundle-class *S4 context_bundle class*

Description

class to organize information of multiple context analyses

Slots

objects Object of class "list" a list of context objects

Methods

show output of core information
summary core statistical information
 [specific cooccurrences
 [[specific cooccurrences

cooccurrences *Get cooccurrence statistics.*

Description

Get cooccurrence statistics.

Usage

```
cooccurrences(.Object, ...)

## S4 method for signature 'corpus'
cooccurrences(
  .Object,
  query,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  boundary = NULL,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
```

```
    stoplist = NULL,
    positivelist = NULL,
    regex = FALSE,
    keep = NULL,
    cpos = NULL,
    method = "ll",
    mc = getOption("polmineR.mc"),
    verbose = FALSE,
    progress = FALSE,
    ...
)

## S4 method for signature 'character'
cooccurrences(
  .Object,
  query,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  boundary = NULL,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  keep = NULL,
  cpos = NULL,
  method = "ll",
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = FALSE,
  ...
)

## S4 method for signature 'slice'
cooccurrences(
  .Object,
  query,
  cqp = is.cqp,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  p_attribute = getOption("polmineR.p_attribute"),
  boundary = NULL,
  stoplist = NULL,
  positivelist = NULL,
  keep = NULL,
  method = "ll",
  mc = FALSE,
  progress = TRUE,
```

```
    verbose = FALSE,
    ...
)

## S4 method for signature 'partition'
cooccurrences(
  .Object,
  query,
  cqp = is.cqp,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  p_attribute = getOption("polmineR.p_attribute"),
  boundary = NULL,
  stoplist = NULL,
  positivelist = NULL,
  keep = NULL,
  method = "ll",
  mc = FALSE,
  progress = TRUE,
  verbose = FALSE,
  ...
)

## S4 method for signature 'subcorpus'
cooccurrences(
  .Object,
  query,
  cqp = is.cqp,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  p_attribute = getOption("polmineR.p_attribute"),
  boundary = NULL,
  stoplist = NULL,
  positivelist = NULL,
  keep = NULL,
  method = "ll",
  mc = FALSE,
  progress = TRUE,
  verbose = FALSE,
  ...
)

## S4 method for signature 'context'
cooccurrences(.Object, method = "ll", verbose = FALSE)

## S4 method for signature 'partition_bundle'
cooccurrences(
  .Object,
```

```

    query,
    verbose = FALSE,
    mc = getOption("polmineR.mc"),
    ...
)

## S4 method for signature 'Cooccurrences'
cooccurrences(.Object, query)

## S4 method for signature 'remote_corpus'
cooccurrences(.Object, ...)

## S4 method for signature 'remote_subcorpus'
cooccurrences(.Object, ...)

```

Arguments

<code>.Object</code>	A partition object, or a character vector with a CWB corpus.
<code>...</code>	Further parameters that will be passed into <code>bigmatrix</code> (applies only if <code>big = TRUE</code>).
<code>query</code>	A query, either a character vector to match a token, or a CQP query.
<code>cqp</code>	Defaults to <code>is.cqp</code> -function, or provide TRUE/FALSE; relevant only if <code>query</code> is not NULL.
<code>p_attribute</code>	The p-attribute of the tokens/the query.
<code>boundary</code>	If provided, it will be checked that the corpus positions of windows do not extend beyond the left and right boundaries of the region defined by the s-attribute where the match occurs.
<code>left</code>	A single integer value defining the number of tokens to the left of the query match to include in the context. Advanced usage: (a) If <code>left</code> is a length-one character vector stating an s-attribute, the context will be expanded to the (left) boundary of the region where the match occurs. (b) If <code>left</code> is a named length-one integer vector, this value is the number regions of the structural attribute referred to by the vector's name to the left of the query match that are included in the context.
<code>right</code>	A single integer value, a length-one character vector or a named length-one integer value, with equivalent effects to argument <code>left</code> .
<code>stoplist</code>	Exclude a query hit from analysis if stopword(s) is/are in context (relevant only if <code>query</code> is not NULL).
<code>positivelist</code>	Character vector or numeric vector: include a query hit only if token in <code>positivelist</code> is present. If <code>positivelist</code> is a character vector, it is assumed to provide regex expressions (incredibly long if the list is long) (relevant only if <code>query</code> is not NULL)
<code>regex</code>	A logical value, whether <code>stoplist/positivelist</code> are interpreted as regular expressions.
<code>keep</code>	list with tokens to keep

cpos	integer vector with corpus positions, defaults to NULL - then the corpus positions for the whole corpus will be used
method	The statistical test(s) to use (defaults to "ll").
mc	whether to use multicore
verbose	A logical value, whether to be verbose.
progress	A logical value, whether to output progress bar.

Value

a cooccurrences-class object

Author(s)

Andreas Blaette

References

Baker, Paul (2006): *Using Corpora in Discourse Analysis*. London: continuum, p. 95-120 (ch. 5).
 Manning, Christopher D.; Schuetze, Hinrich (1999): *Foundations of Statistical Natural Language Processing*. MIT Press: Cambridge, Mass., pp. 151-189 (ch. 5).

See Also

See the documentation for the [ll](#)-method for an explanation of the computation of the log-likelihood statistic.

Examples

```
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

merkel <- partition("GERMAPARLMINI", interjection = "speech", speaker = ".*Merkel", regex = TRUE)
merkel <- enrich(merkel, p_attribute = "word")
cooc <- cooccurrences(merkel, query = "Deutschland")

# use subset-method to filter results
a <- cooccurrences("REUTERS", query = "oil")
b <- subset(a, !is.na(ll))
c <- subset(b, !word %in% tm::stopwords("en"))
d <- subset(c, count_coi >= 5)
e <- subset(c, ll >= 10.83)
format(e)

# using pipe operator with subset
cooccurrences("REUTERS", query = "oil") %>%
  subset(!is.na(ll)) %>%
  subset(!word %in% tm::stopwords("en")) %>%
  subset(count_coi >= 5) %>%
  subset(ll >= 10.83) %>%
  format()
```

```

# generate datatables htmlwidget with buttons for export (Excel & more)
# (alternatively use openxlsx::write.xlsx())

interactive_table <- cooccurrences("REUTERS", query = "oil") %>%
  format() %>%
  DT::datatable(
    extensions = "Buttons",
    options = list(dom = 'Btip', buttons = c("excel", "pdf", "csv"))
  )
if (interactive()) show(interactive_table)

# compute cooccurrences for a set of partitions
# (example not run by default to save time on test machines)
## Not run:
pb <- partition_bundle("GERMAPARLMINI", s_attribute = "speaker")
ps <- count(pb, query = "Deutschland")[Deutschland >= 25][["partition"]]
pb_min <- pb[ps]
y <- cooccurrences(pb_min, query = "Deutschland")
if (interactive()) y[[1]]
if (interactive()) y[[2]]

y2 <- corpus("GERMAPARLMINI") %>%
  subset(speaker %in% c("Hubertus Heil", "Angela Dorothea Merkel")) %>%
  split(s_attribute = "speaker") %>%
  cooccurrences(query = "Deutschland")

## End(Not run)

```

Cooccurrences, corpus-method

Get all cooccurrences in corpus/partition.

Description

Obtain all cooccurrences in a corpus, or a partition. The result is a Cooccurrences-class object which includes a data.table with counts of cooccurrences. See the documentation entry for the Cooccurrences-class for methods to process Cooccurrences-class objects.

Usage

```

## S4 method for signature 'corpus'
Cooccurrences(
  .Object,
  p_attribute,
  left,
  right,
  stoplist = NULL,

```

```
    mc = getOption("polmineR.mc"),
    verbose = FALSE,
    progress = FALSE
)

## S4 method for signature 'character'
Cooccurrences(
  .Object,
  p_attribute,
  left,
  right,
  stoplist = NULL,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = FALSE
)

## S4 method for signature 'slice'
Cooccurrences(
  .Object,
  p_attribute,
  left,
  right,
  stoplist = NULL,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = FALSE
)

## S4 method for signature 'partition'
Cooccurrences(
  .Object,
  p_attribute,
  left,
  right,
  stoplist = NULL,
  mc = getOption("polmineR.mc"),
  verbose = FALSE,
  progress = FALSE
)

## S4 method for signature 'subcorpus'
Cooccurrences(
  .Object,
  p_attribute,
  left,
  right,
  stoplist = NULL,
```

```

mc = getOption("polmineR.mc"),
verbose = FALSE,
progress = FALSE
)

```

Arguments

<code>.Object</code>	A length-one character vector indicating a corpus, or a partition object.
<code>p_attribute</code>	Positional attributes to evaluate.
<code>left</code>	A scalar integer value, size of left context.
<code>right</code>	A scalar integer value, size of right context.
<code>stoplist</code>	Tokens to exclude from the analysis.
<code>mc</code>	Logical value, whether to use multiple cores.
<code>verbose</code>	Logical value, whether to output messages.
<code>progress</code>	Logical value, whether to display a progress bar.

Details

The implementation uses a `data.table` to store information and makes heavy use of the reference logic of the `data.table` package, to avoid copying potentially large objects, and to be parsimonious with limited memory. The behaviour resulting from in-place changes may be uncommon, see examples.

See Also

To learn about methods available for the object that is returned, see the documentation of the [Cooccurrences-class](#). See the [cooccurrences-method](#) (starting with a lower case c) to get the cooccurrences for the match for a query, which may also be a CQP query.

Examples

```

## Not run:
# In a first scenario, we get all cooccurrences for the REUTERS corpus,
# excluding stopwords

stopwords <- unname(unlist(
  noise(
    terms("REUTERS", p_attribute = "word"),
    stopwordsLanguage = "en"
  )
))
r <- Cooccurrences(
  .Object = "REUTERS", p_attribute = "word",
  left = 5L, right = 5L, stoplist = stopwords
)
ll(r) # note that the table in the stat slot is augmented in-place
decode(r) # in-place modification, again
r <- subset(r, ll > 11.83 & ab_count >= 5)
data.table::setorderv(r@stat, cols = "ll", order = -1L)

```

```

head(r, 25)

if (requireNamespace("igraph", quietly = TRUE)){
  r@partition <- enrich(r@partition, p_attribute = "word")
  g <- as_igraph(r, as.undirected = TRUE)
  plot(g)
}

# The next scenario is a cross-check that extracting cooccurrences from
# from a Cooccurrences-class object with all cooccurrences and the result
# for getting cooccurrences for a single object are identical

a <- cooccurrences(r, query = "oil")
a <- data.table::as.data.table(a)

b <- cooccurrences("REUTERS", query = "oil", left = 5, right = 5, p_attribute = "word")
b <- data.table::as.data.table(b)
b <- b[!word %in% stopwords]

all(b[["word"]][1:5] == a[["word"]][1:5]) # needs to be identical!

stopwords <- unlist(noise(
  terms("GERMAPARLMINI", p_attribute = "word"),
  stopwordsLanguage = "german"
))

# We now filter cooccurrences by keeping only the statistically
# significant cooccurens, identified by comparison with cooccurrences
# derived from a reference corpus

plpr_partition <- partition(
  "GERMAPARLMINI", date = "2009-11-10", interjection = "speech",
  p_attribute = "word"
)
plpr_cooc <- Cooccurrences(
  plpr_partition, p_attribute = "word",
  left = 3L, right = 3L,
  stoplist = stopwords,
  verbose = TRUE
)
decode(plpr_cooc)
ll(plpr_cooc)

merkel <- partition(
  "GERMAPARLMINI", speaker = "Merkel", date = "2009-11-10", interjection = "speech",
  regex = TRUE,
  p_attribute = "word"
)
merkel_cooc <- Cooccurrences(
  merkel, p_attribute = "word",
  left = 3L, right = 3L,

```

```

    stoplist = stopwords,
    verbose = TRUE
  )
  decode(merkel_cooc)
  ll(merkel_cooc)

  merkel_min <- subset(
    merkel_cooc,
    by = subset(features(merkel_cooc, plpr_cooc), rank_ll <= 50)
  )

  # Essentially the same procedure as in the previous example, but with
  # two positional attributes, so that part-of-speech annotation is
  # used for additional filtering.

  protocol <- partition(
    "GERMAPARLMINI",
    date = "2009-11-10",
    p_attribute = c("word", "pos"),
    interjection = "speech"
  )
  protocol_cooc <- Cooccurrences(
    protocol,
    p_attribute = c("word", "pos"),
    left = 3L, right = 3L
  )
  ll(protocol_cooc)
  decode(protocol_cooc)

  merkel <- partition(
    "GERMAPARLMINI",
    speaker = "Merkel",
    date = "2009-11-10",
    interjection = "speech",
    regex = TRUE,
    p_attribute = c("word", "pos")
  )
  merkel_cooc <- Cooccurrences(
    merkel,
    p_attribute = c("word", "pos"),
    left = 3L, right = 3L,
    verbose = TRUE
  )
  ll(merkel_cooc)
  decode(merkel_cooc)

  f <- features(merkel_cooc, protocol_cooc)
  f <- subset(f, a_pos %in% c("NN", "ADJA"))
  f <- subset(f, b_pos %in% c("NN", "ADJA"))
  f <- subset(f, c(rep(TRUE, times = 50), rep(FALSE, times = nrow(f) - 50)))

  merkel_min <- subset(merkel_cooc, by = f)

```

```

if (requireNamespace("igraph", quietly = TRUE)){
  g <- as_igraph(merkel_min, as.undirected = TRUE)
  plot(g)
}

## End(Not run)

```

Cooccurrences-class *Cooccurrences class for corpus/partition.*

Description

The Cooccurrences-class stores the information for all cooccurrences in a corpus. As this data can be bulky, in-place modifications of the data. table in the stat-slot of a Cooccurrences-object are used wherever possible, to avoid copying potentially large objects whenever possible. The class inherits from the textstat-class, so that methods for textstat-objects are inherited (see examples).

Usage

```

## S4 method for signature 'Cooccurrences'
as.simple_triplet_matrix(x)

## S4 method for signature 'Cooccurrences'
as_igraph(
  x,
  edge_attributes = c("l1", "ab_count", "rank_l1"),
  vertex_attributes = "count",
  as.undirected = TRUE,
  drop = getOption("polmineR.villainChars")
)

## S4 method for signature 'Cooccurrences'
subset(x, ..., by)

## S4 method for signature 'Cooccurrences'
decode(.Object)

## S4 method for signature 'Cooccurrences'
kwic(
  .Object,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  verbose = TRUE,
  progress = TRUE
)

```

```
## S4 method for signature 'Cooccurrences'
as.sparseMatrix(x, col = "ab_count", ...)
```

```
## S4 method for signature 'Cooccurrences'
enrich(.Object)
```

Arguments

<code>x</code>	A Cooccurrences class object.
<code>edge_attributes</code>	Attributes from <code>stat.data.table</code> in <code>x</code> to add to edges.
<code>vertex_attributes</code>	Vertex attributes to add to nodes.
<code>as.undirected</code>	Logical, whether to return directed or undirected graph.
<code>drop</code>	A character vector indicating names of nodes to drop from <code>igraph</code> object that is prepared.
<code>...</code>	Further arguments passed into a further call of <code>subset</code> .
<code>by</code>	A features-class object.
<code>.Object</code>	A Cooccurrences-class object.
<code>left</code>	Number of tokens to the left of the node.
<code>right</code>	Number of tokens to the right of the node.
<code>verbose</code>	Logical.
<code>progress</code>	Logical, whether to show progress bar.
<code>col</code>	A column to extract.

Details

The `as.simple_triplet_matrix`-method will transform a Cooccurrences object into a sparse matrix. For reasons of memory efficiency, decoding token ids is performed within the method at the as late as possible. It is NOT necessary that decoded tokens are present in the table in the Cooccurrences object.

The `as_igraph`-method can be used to turn an object of the Cooccurrences-class into an `igraph`-object.

The `subset` method, as a particular feature, allows a Cooccurrences-object to be subsetted by a `features-Object` resulting from a features extraction that compares two Cooccurrences objects.

For reasons of memory efficiency, the initial `data.table` in the slot `stat` of a Cooccurrences-object will identify tokens by an integer id, not by the string of the token. The `decode()`-method will replace these integer columns with human-readable character vectors. Due to the reference logic of the `data.table` object, this is an in-place operation, performed without copying the table. The modified object is returned invisibly; usually it will not be necessary to catch the return value.

The `kwic`-method will add a column to the `data.table` in the `stat`-slot with the concordances that are behind a statistical finding, and to the `data.table` in the `stat`-slot of the `partition` in the slot `partition`. It is an in-place operation.

Returns a `sparseMatrix` based on the counts of term cooccurrences. At this stage, it is required that decoded tokens are present.

The `enrich()`-method will add columns `'a_count'` and `'b_count'` to the `data.table` in the `'stat'` slot of the `Cooccurrences` object. If the count for the subcorpus/partition from which the cooccurrences are derived is not yet present, the count is performed first.

Slots

`left` Single integer value, number of tokens to the left of the node.

`right` Single integer value, number of tokens to the right of the node.

`p_attribute` A character vector, the p-attribute(s) the evaluation of the corpus is based on.

`corpus` Length-one character vector, the CWB corpus used.

`stat` A `data.table` with the statistical analysis of cooccurrences.

`encoding` Length-one character vector, the encoding of the corpus.

`partition` The partition that is the basis for computations.

`window_sizes` A `data.table` linking the number of tokens in the context of a token identified by `id`.

`minimized` Logical, whether the object has been minimized.

See Also

See the documentation of the [Cooccurrences](#)-method (including examples) for procedures to get and filter cooccurrence information. See the documentation for the [textstat-class](#) explaining which methods for this superclass of the `Cooccurrences-class` which are available.

Examples

```
## Not run:
# takes too much time on CRAN test machines
use(pkg = "RcppCWB", corpus = "REUTERS")
X <- Cooccurrences("REUTERS", p_attribute = "word", left = 2L, right = 2L)
m <- as.simple_triplet_matrix(X)

## End(Not run)

use(pkg = "RcppCWB", corpus = "REUTERS")

X <- Cooccurrences("REUTERS", p_attribute = "word", left = 5L, right = 5L)
decode(X)
sm <- as.sparseMatrix(X)
stm <- as.simple_triplet_matrix(X)
```

cooccurrences-class *Cooccurrences class.*

Description

S4 class to organize information of context analysis

Usage

```
## S4 method for signature 'cooccurrences'
show(object)

## S4 method for signature 'cooccurrences_bundle'
as.data.frame(x)

## S4 method for signature 'cooccurrences'
format(x, digits = 2L)

## S4 method for signature 'cooccurrences'
view(.Object)

## S4 method for signature 'cooccurrences_reshaped'
view(.Object)
```

Arguments

object	object to work with
x	object to work with
digits	Integer indicating the number of decimal places (round) or significant digits (signif) to be used.
.Object	object to work with

Slots

call Object of class character the call that generated the object
partition Object of class character the partition the analysis is based on
size_partition Object of class integer the size of the partition
left Object of class integer number of tokens to the left.
right Object of class integer number of tokens to the right.
p_attribute Object of class character p-attribute of the query
corpus Object of class character the CWB corpus used
stat Object of class data.table statistics of the analysis
encoding Object of class character encoding of the corpus
method Object of class character statistical test(s) used

corpus-class	<i>Corpus class initialization</i>
--------------	------------------------------------

Description

Corpora indexed using the 'Corpus Workbench' ('CWB') offer an efficient data structure for large, linguistically annotated corpora. The `corpus-class` keeps basic information on a CWB corpus. Corresponding to the name of the class, the `corpus-method` is the initializer for objects of the corpus class. A CWB corpus can also be hosted remotely on an [OpenCPU](#) server. The `remote_corpus` class (which inherits from the `corpus` class) will handle respective information. A (limited) set of `polmineR` functions and methods can be executed on the corpus on the remote machine from the local R session by calling them on the `remote_corpus` object. Calling the `corpus-method` without an argument will return a `data.frame` with basic information on the corpora that are available.

Usage

```
## S4 method for signature 'character'
corpus(.Object, registry_dir, server = NULL, restricted)

## S4 method for signature 'missing'
corpus()
```

Arguments

<code>.Object</code>	The upper-case ID of a CWB corpus stated by a length-one character vector.
<code>registry_dir</code>	The registry directory with the registry file describing the corpus (length-one character vector). If missing, the C representations of loaded corpora will be evaluated to get the registry directory with the registry file for the corpus.
<code>server</code>	If NULL (default), the corpus is expected to be present locally. If provided, the name of an OpenCPU server (can be an IP address) that hosts a corpus, or several corpora. The <code>corpus-method</code> will then instantiate a <code>remote_corpus</code> object.
<code>restricted</code>	A logical value, whether access to a remote corpus is restricted (TRUE) or not (FALSE).

Details

Calling `corpus()` will return a `data.frame` listing the corpora available locally and described in the active registry directory, and some basic information on the corpora.

A corpus object is instantiated by passing a corpus ID as argument `.Object`. Following the conventions of the Corpus Workbench (CWB), Corpus IDs are written in upper case. If `.Object` includes lower case letters, the corpus object is instantiated nevertheless, but a warning is issued to prevent bad practice. If `.Object` is not a known corpus, the error message will include a suggestion if there is a potential candidate that can be identified by `agrep`.

A limited set of methods of the `polmineR` package is exposed to be executed on a remote OpenCPU server. As a matter of convenience, the whereabouts of an OpenCPU server hosting a CWB corpus can be stated in an environment variable "OPENCPU_SERVER". Environment variables

for R sessions can be set easily in the `.Renv` file. A convenient way to do this is to call `usethis::edit_r_environs()`.

Slots

`corpus` A length-one character vector, the upper-case ID of a CWB corpus.

`registry_dir` Registry directory with registry file describing the corpus.

`data_dir` The directory where binary files of the indexed corpus reside.

`info_file` If available, the info file indicated in the registry file (typically a file named `.info` or `info.md` in the data directory), or NA if not.

`template` Full path to the template containing formatting instructions when showing full text output (fs_path object or NA).

`type` If available, the type of the corpus (e.g. "plpr" for a corpus of plenary protocols), or NA.

`name` Full name of the corpus that may be more expressive than the corpus ID.

`xml` Object of class character, whether the xml is "flat" or "nested".

`encoding` The encoding of the corpus, given as a length-one character vector (usually 'utf8' or 'latin1').

`size` Number of tokens (size) of the corpus, a length-one integer vector.

`server` The URL (can be IP address) of the OpenCPU server. The slot is available only with the `remote_corpus` class inheriting from the `corpus` class.

`user` If the corpus on the server requires authentication, the username.

`password` If the corpus on the server requires authentication, the password.

See Also

Methods to extract basic information from a corpus object are covered by the `corpus-methods` documentation object. Use the `s_attributes` method to get information on structural attributes. Analytical methods available for corpus objects are [size](#), [count](#), [dispersion](#), [kwic](#), [cooccurrences](#), [as.TermDocumentMatrix](#).

Other classes to manage corpora: [phrases-class](#), [ranges-class](#), [regions](#), [subcorpus](#)

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

# get corpora present locally
y <- corpus()

# initialize corpus object
r <- corpus("REUTERS")
r <- corpus("reuters") # will work, but will result in a warning

# apply core polmineR methods
a <- size(r)
b <- s_attributes(r)
```

```

c <- count(r, query = "oil")
d <- dispersion(r, query = "oil", s_attribute = "id")
e <- kwic(r, query = "oil")
f <- cooccurrences(r, query = "oil")

# used corpus initialization in a pipe
y <- corpus("REUTERS") %>% s_attributes()
y <- corpus("REUTERS") %>% count(query = "oil")

# working with a remote corpus
## Not run:
REUTERS <- corpus("REUTERS", server = Sys.getenv("OPENCPU_SERVER"))
count(REUTERS, query = "oil")
size(REUTERS)
kwic(REUTERS, query = "oil")

GERMAPARL <- corpus("GERMAPARL", server = Sys.getenv("OPENCPU_SERVER"))
s_attributes(GERMAPARL)
size(x = GERMAPARL)
count(GERMAPARL, query = "Integration")
kwic(GERMAPARL, query = "Islam")

p <- partition(GERMAPARL, year = 2000)
s_attributes(p, s_attribute = "year")
size(p)
kwic(p, query = "Islam", meta = "date")

GERMAPARL <- corpus("GERMAPARLMINI", server = Sys.getenv("OPENCPU_SERVER"))
s_attrs <- s_attributes(GERMAPARL, s_attribute = "date")
sc <- subset(GERMAPARL, date == "2009-11-10")

## End(Not run)

```

corpus-methods

Corpus class methods

Description

A set of generic methods is available to extract basic information from objects of the corpus class.

Usage

```

## S4 method for signature 'corpus'
name(x)

## S4 method for signature 'corpus'
get_corpus(x)

## S4 method for signature 'corpus'
show(object)

```

```
## S4 method for signature 'corpus'
x$name

## S4 method for signature 'corpus'
get_info(x)

## S4 method for signature 'corpus'
show_info(x)
```

Arguments

x	An object of class corpus, or inheriting from it.
object	An object of class corpus, or inheriting from it.
name	A (single) s-attribute.

Details

A corpus object can have a name, which can be retrieved using the name-method.

Use get_corpus()-method to get the corpus ID from the slot corpus of the corpus object.

The show()-method will show basic information on the corpus object.

Applying the \$-method on a corpus will return the values for the s-attribute stated with argument name.

Use get_info to get the the content of the info file for the corpus (usually in the data directory of the corpus) and return it as a character vector. Returns NULL if there is not info file.

The show_info-method will get the content of the info file for a corpus, turn it into an html document, and show the result in the viewer pane of RStudio. If the filename of the info file ends on "md", the document is rendered as markdown.

Examples

```
# get/show information on corpora
corpus("REUTERS") %>% get_info()
corpus("REUTERS") %>% show_info()
corpus("GERMAPARLMINI") %>% get_info()
corpus("GERMAPARLMINI") %>% show_info()

use(pkg = "RcppCWB", corpus = "REUTERS")

# show-method
if (interactive()) corpus("REUTERS") %>% show()
if (interactive()) corpus("REUTERS") # show is called implicitly

# get corpus ID
corpus("REUTERS") %>% get_corpus()

# use $ to access corpus properties
use("polminer")
```

```

g <- corpus("GERMAPARLMINI")
g$date
corpus("GERMAPARLMINI")$build_date #
gparl <- corpus("GERMAPARLMINI")
gparl$version %>%
  as.numeric_version()

```

count

Get counts.

Description

Count all tokens, or number of occurrences of a query (CQP syntax may be used), or matches for the query.

Usage

```
count(.Object, ...)
```

```

## S4 method for signature 'partition'
count(
  .Object,
  query = NULL,
  cqp = is.cqp,
  check = TRUE,
  breakdown = FALSE,
  decode = TRUE,
  p_attribute = getOption("polmineR.p_attribute"),
  mc = getOption("polmineR.cores"),
  verbose = TRUE,
  progress = FALSE,
  phrases = NULL,
  ...
)

```

```

## S4 method for signature 'subcorpus'
count(
  .Object,
  query = NULL,
  cqp = is.cqp,
  check = TRUE,
  breakdown = FALSE,
  decode = TRUE,
  p_attribute = getOption("polmineR.p_attribute"),
  mc = getOption("polmineR.cores"),
  verbose = TRUE,
  progress = FALSE,
)

```

```
    phrases = NULL,  
    ...  
)  
  
## S4 method for signature 'partition_bundle'  
count(  
  .Object,  
  query = NULL,  
  cqp = FALSE,  
  p_attribute = getOption("polmineR.p_attribute"),  
  phrases = NULL,  
  freq = FALSE,  
  total = TRUE,  
  mc = FALSE,  
  progress = FALSE,  
  verbose = FALSE,  
  ...  
)  
  
## S4 method for signature 'subcorpus_bundle'  
count(  
  .Object,  
  query = NULL,  
  cqp = FALSE,  
  p_attribute = NULL,  
  phrases = NULL,  
  freq = FALSE,  
  total = TRUE,  
  mc = FALSE,  
  progress = TRUE,  
  verbose = FALSE,  
  ...  
)  
  
## S4 method for signature 'corpus'  
count(  
  .Object,  
  query = NULL,  
  cqp = is.cqp,  
  check = TRUE,  
  p_attribute = getOption("polmineR.p_attribute"),  
  breakdown = FALSE,  
  sort = FALSE,  
  decode = TRUE,  
  verbose = TRUE,  
  ...  
)
```

```

## S4 method for signature 'character'
count(
  .Object,
  query = NULL,
  cqp = is.cqp,
  check = TRUE,
  p_attribute = getOption("polmineR.p_attribute"),
  breakdown = FALSE,
  sort = FALSE,
  decode = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'vector'
count(.Object, corpus, p_attribute, ...)

## S4 method for signature 'remote_corpus'
count(.Object, ...)

## S4 method for signature 'remote_subcorpus'
count(.Object, ...)

```

Arguments

<code>.Object</code>	A partition or <code>partition_bundle</code> , or a length-one character vector providing the name of a corpus.
<code>...</code>	Further arguments. If <code>.Object</code> is a <code>remote_corpus</code> object, the three dots (<code>...</code>) are used to pass arguments. Hence, it is necessary to state the names of all arguments to be passed explicitly.
<code>query</code>	A character vector (one or multiple terms), CQP syntax can be used.
<code>cqp</code>	Either logical (TRUE if query is a CQP query), or a function to check whether query is a CQP query or not (defaults to <code>is.query</code> auxiliary function).
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .
<code>breakdown</code>	Logical, whether to report number of occurrences for different matches for a query.
<code>decode</code>	Logical, whether to turn token ids into decoded strings (only if query is NULL).
<code>p_attribute</code>	The p-attribute(s) to use.
<code>mc</code>	Logical, whether to use multicore (defaults to FALSE).
<code>verbose</code>	Logical, whether to be verbose.
<code>progress</code>	Logical, whether to show progress bar.
<code>phrases</code>	A phrases object. If provided, the denoted regions will be concatenated as phrases.
<code>freq</code>	Logical, if FALSE, counts will be reported, if TRUE, (relative) frequencies are added to table.

total	Defaults to FALSE, if TRUE, the total value of counts (column named 'TOTAL') will be amended to the data.table that is returned.
sort	Logical, whether to sort table with counts (in stat slot).
corpus	The name of a CWB corpus.

Details

If .Object is a partition_bundle, the data.table returned will have the queries in the columns, and as many rows as there are in the partition_bundle.

If .Object is a length-one character vector and query is NULL, the count is performed for the whole partition.

If breakdown is TRUE and one query is supplied, the function returns a frequency breakdown of the results of the query. If several queries are supplied, frequencies for the individual queries are retrieved.

Multiple queries can be used for argument query. Some care may be necessary when summing up the counts for the individual queries. When the CQP syntax is used, different queries may yield the same match result, so that the sum of all individual query matches may overestimate the true number of unique matches. In the case of overlapping matches, a warning message is issued. Collapsing multiple CQP queries into a single query (separating the individual queries by "|" and wrapping everything in round brackets) solves this problem.

Value

A data.table if argument query is used, a count-object, if query is NULL and .Object is a character vector (referring to a corpus) or a partition, a count_bundle-object, if .Object is a partition_bundle.

References

Baker, Paul (2006): *Using Corpora in Discourse Analysis*. London: continuum, p. 47-69 (ch. 3).

See Also

For a metadata-based breakdown of counts (i.e. tabulation by s-attributes), see [dispersion](#). The [hits](#) is the worker behind the dispersion method and offers a similar, yet more low-level functionality as compared to the count method. Using the [hits](#) method may be useful to obtain the data required for flexible cross-tabulations.

Examples

```
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

debates <- partition("GERMAPARLMINI", date = ".*", regex=TRUE)
count(debates, query = "Arbeit") # get frequencies for one token
count(debates, c("Arbeit", "Freizeit", "Zukunft")) # get frequencies for multiple tokens

count("GERMAPARLMINI", query = c("Migration", "Integration"), p_attribute = "word")
```

```

debates <- partition_bundle(
  "GERMAPARLMINI", s_attribute = "date", values = NULL,
  mc = FALSE, verbose = FALSE
)
y <- count(debates, query = "Arbeit", p_attribute = "word")
y <- count(debates, query = c("Arbeit", "Migration", "Zukunft"), p_attribute = "word")

count("GERMAPARLMINI", '"Integration.*"', breakdown = TRUE)

P <- partition("GERMAPARLMINI", date = "2009-11-11")
count(P, '"Integration.*"', breakdown = TRUE)

sc <- corpus("GERMAPARLMINI") %>% subset(party == "SPD")
phr <- cpos(sc, query = '"Deutsche.*" "Bundestag.*"', cqp = TRUE) %>%
  as.phrases(corpus = "GERMAPARLMINI", enc = "latin1")
cnt <- count(sc, phrases = phr, p_attribute = "word")

# Multiple queries and overlapping query matches. The first count
# operation will issue a warning that matches overlap, see the second
# example for a solution.
corpus("REUTERS") %>%
  count(query = c('".*oil"', '"turmoil"'), cqp = TRUE)
corpus("REUTERS") %>%
  count(query = '".*oil|turmoil"', cqp = TRUE)

```

count_class

Count class.

Description

S4 class to organize counts. The classes `polmineR` and `ngrams` inherit from the class.

Usage

```

## S4 method for signature 'count'
summary(object)

## S4 method for signature 'count'
length(x)

## S4 method for signature 'count'
hist(x, ...)

```

Arguments

<code>object</code>	A count object.
<code>x</code>	A count object, or a class inheriting from <code>count</code> .
<code>...</code>	Further parameters.

Details

The `summary`-method in combination with a weighed `count`-object can be used to perform a dictionary-based sentiment analysis (see examples).

The `length`-method is synonymous with the `size`-method and will return the size of the corpus or partition a count has been derived from.

Slots

`stat` Object of class `data.table`.

`corpus` Object of class character the CWB corpus the partition is based on .

`encoding` Object of class character, the encoding of the corpus.

`name` Object of class character, a name for the object.

`size` Object of class integer, the size of the partition or corpus the count is based upon.

Author(s)

Andreas Blaette

See Also

The `count`-class inherits from the [textstat-class](#).

Examples

```
# sample for dictionary-based sentiment analysis
weights <- data.table::data.table(
  word = c("gut", "super", "herrlich", "schlecht", "grob", "mies"),
  weight = c(1,1,1,-1,-1,-1)
)
corp <- corpus("GERMAPARLMINI")
sc <- subset(corp, date == "2009-11-11")
cnt <- count(sc, p_attribute = "word")
cnt <- weigh(cnt, with = weights)
y <- summary(cnt)

# old, partition-based workflow
p <- partition("GERMAPARLMINI", date = "2009-11-11")
p <- enrich(p, p_attribute = "word")
weights <- data.table::data.table(
  word = c("gut", "super", "herrlich", "schlecht", "grob", "mies"),
  weight = c(1,1,1,-1,-1,-1)
)
p <- weigh(p, with = weights)
summary(p)
```

`cpos`*Get corpus positions for a query or queries.*

Description

Get matches for a query in a CQP corpus (subcorpus, partition etc.), optionally using the CQP syntax of the Corpus Workbench (CWB).

Usage

```
cpos(.Object, ...)
```

```
## S4 method for signature 'corpus'
```

```
cpos(  
  .Object,  
  query,  
  p_attribute = getOption("polmineR.p_attribute"),  
  cqp = is.cqp,  
  regex = FALSE,  
  check = TRUE,  
  verbose = TRUE,  
  ...  
)
```

```
## S4 method for signature 'character'
```

```
cpos(  
  .Object,  
  query,  
  p_attribute = getOption("polmineR.p_attribute"),  
  cqp = is.cqp,  
  check = TRUE,  
  verbose = TRUE,  
  ...  
)
```

```
## S4 method for signature 'slice'
```

```
cpos(  
  .Object,  
  query,  
  cqp = is.cqp,  
  check = TRUE,  
  p_attribute = getOption("polmineR.p_attribute"),  
  verbose = TRUE,  
  ...  
)
```

```
## S4 method for signature 'partition'
```

```

cpos(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  p_attribute = getOption("polmineR.p_attribute"),
  verbose = TRUE,
  ...
)

```

```
## S4 method for signature 'subcorpus'
```

```

cpos(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  p_attribute = getOption("polmineR.p_attribute"),
  verbose = TRUE,
  ...
)

```

```
## S4 method for signature 'matrix'
```

```
cpos(.Object)
```

```
## S4 method for signature 'hits'
```

```
cpos(.Object)
```

```
## S4 method for signature ``NULL``
```

```
cpos(.Object)
```

Arguments

<code>.Object</code>	A length-one character vector indicating a CWB corpus, or a corpus, or partition object.
<code>...</code>	Used for reasons of backwards compatibility to process arguments that have been renamed (e.g. <code>pAttribute</code>).
<code>query</code>	A character vector providing one or multiple queries (token to look up, regular expression or CQP query). Token ids (i.e. integer values) are also accepted. If query is neither a regular expression nor a CQP query, a sanity check removes accidental leading/trailing whitespace, issuing a respective warning.
<code>p_attribute</code>	The p-attribute to search. Needs to be stated only if query is not a CQP query. Defaults to <code>NULL</code> .
<code>cqp</code>	Either logical (<code>TRUE</code> if query is a CQP query), or a function to check whether query is a CQP query or not (defaults to <code>is.cqp</code> auxiliary function).
<code>regex</code>	Interpret query as a regular expression.
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .
<code>verbose</code>	A logical value, whether to show messages.

Details

The `cpos()`-method returns a two-column matrix with the ranges (start end end corpus positions of the matches) matched by a query. CQP syntax can be used. The encoding of the query is adjusted to conform to the encoding of the CWB corpus. If there are not matches, NULL is returned.

Previous `polmineR` versions defined the `cpos()`-method for `matrix` and `hits` objects to obtain an integer vector with unfolded individual corpus positions. This usage is deprecated starting with `polmineR v0.8.8`

Value

A matrix with two columns. The first column reports the left/starting corpus positions (`cpos`) of the hits obtained. The second column reports the right/ending corpus positions of the respective hit. The number of rows is the number of hits. If there are no hits, NULL is returned.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

# look up single tokens
cpos("REUTERS", query = "oil")
corpus("REUTERS") %>% cpos(query = "oil")

corpus("REUTERS") %>%
  subset(grepl("saudi-arabia", places)) %>%
  cpos(query = "oil")

partition("REUTERS", places = "saudi-arabia", regex = TRUE) %>%
  cpos(query = "oil")

# use CQP query syntax
cpos("REUTERS", query = '"Saudi" "Arabia"')
corpus("REUTERS") %>% cpos(query = '"Saudi" "Arabia"')
corpus("REUTERS") %>%
  subset(grepl("saudi-arabia", places)) %>%
  cpos(query = '"Saudi" "Arabia"', cqp = TRUE)
partition("REUTERS", places = "saudi-arabia", regex = TRUE) %>%
  cpos(query = '"Saudi" "Arabia"', cqp = TRUE)
```

cqp

Tools for CQP queries.

Description

Test whether a character string is a CQP query, or turn a character vector into CQP queries.

Usage

```
is.cqp(query)

check_cqp_query(query, warn = TRUE)

as.cqp(
  query,
  normalise.case = FALSE,
  collapse = FALSE,
  check = TRUE,
  warn = TRUE
)
```

Arguments

query	A character vector with at least one CQP query.
warn	A (length-one) logical value, whether to issue a warning if a query may be buggy.
normalise.case	A logical value, if TRUE, a flag will be added to the query/queries to omit matching case.
collapse	A logical value, whether to collapse the queries into one.
check	A logical value whether to run <code>check_cqp_query()</code> on queries.

Details

The `is.cqp()` function guesses whether query is a CQP query and returns the respective logical value (TRUE/FALSE).

The `as.cqp()` function takes a character vector as input and converts it to a CQP query by putting the individual strings in quotation marks.

The `check_cqp_query`-function will check that opening quotation marks are matched by closing quotation marks, to prevent crashes of CQP and the R session.

Value

`is.cqp` returns a logical value, `as.cqp` a character vector, `check_cqp_query` a logical value that is TRUE if all queries are valid, or FALSE if not.

References

CQP Query Language Tutorial (https://cwb.sourceforge.io/files/CQP_Tutorial.pdf)

Examples

```
is.cqp("migration") # will return FALSE
is.cqp('"migration"') # will return TRUE
is.cqp('[pos = "ADJA"] "migration"') # will return TRUE

as.cqp("migration")
```

```

as.cqp(c("migration", "diversity"))
as.cqp(c("migration", "diversity"), collapse = TRUE)
as.cqp("migration", normalise.case = TRUE)

check_cqp_query('"Integration.*"') # TRUE, the query is ok
check_cqp_query('"Integration.*') # FALSE, closing quotation mark is missing
check_cqp_query('"Integration.*") # FALSE, closing quotation mark is missing
check_cqp_query(c('"Integration.*', '"Integration.*')) # FALSE too

```

decode-method	<i>Decode corpus or subcorpus.</i>
---------------	------------------------------------

Description

Decode corpus or subcorpus and return class specified by argument to.

Usage

```

decode(.Object, ...)

## S4 method for signature 'corpus'
decode(
  .Object,
  to = c("data.table", "Annotation", "AnnotatedPlainTextDocument"),
  p_attributes = NULL,
  s_attributes = NULL,
  mw = NULL,
  stoplist = NULL,
  decode = TRUE,
  verbose = TRUE
)

## S4 method for signature 'character'
decode(
  .Object,
  to = c("data.table", "Annotation"),
  s_attributes = NULL,
  p_attributes = NULL,
  decode = TRUE,
  verbose = TRUE
)

## S4 method for signature 'slice'
decode(
  .Object,
  to = c("data.table", "Annotation", "AnnotatedPlainTextDocument"),
  s_attributes = NULL,
  p_attributes = NULL,

```

```

    mw = NULL,
    stoplist = NULL,
    decode = TRUE,
    verbose = TRUE
)

## S4 method for signature 'partition'
decode(
  .Object,
  to = "data.table",
  s_attributes = NULL,
  p_attributes = NULL,
  decode = TRUE,
  verbose = TRUE
)

## S4 method for signature 'subcorpus'
decode(
  .Object,
  to = c("data.table", "Annotation", "AnnotatedPlainTextDocument"),
  s_attributes = NULL,
  p_attributes = NULL,
  mw = NULL,
  stoplist = NULL,
  decode = TRUE,
  verbose = TRUE
)

## S4 method for signature 'integer'
decode(.Object, corpus, p_attributes, boost = NULL)

## S4 method for signature 'data.table'
decode(.Object, corpus, p_attributes)

```

Arguments

<code>.Object</code>	The corpus or subcorpus to decode.
<code>...</code>	Further arguments.
<code>to</code>	The class of the returned object, stated as a length-one character vector.
<code>p_attributes</code>	The positional attributes to decode. If NULL (default), all positional attributes will be decoded.
<code>s_attributes</code>	The structural attributes to decode. If NULL (default), all structural attributes will be decoded.
<code>mw</code>	A character vector with s-attributes with multiword expressions. Used only if to is 'AnnotatedPlainTextDocument'.
<code>stoplist</code>	A character vector with terms to be dropped.

decode	A logical value, whether to decode token ids and struc ids to character strings. If FALSE, the values of columns for p- and s-attributes will be integer vectors. If TRUE (default), the respective columns are character vectors.
verbose	A logical value, whether to output progress messages.
corpus	A CWB indexed corpus, either a length-one character vector, or a corpus object.
boost	A length-one logical value, whether to speed up decoding a long vector of token ids by directly by reading in the lexicon file from the data directory of a corpus. If NULL (default), the internal decision rule is that boost will be TRUE if the corpus is larger than 10 000 000 million tokens and more than 5 percent of the corpus are to be decoded.

Details

The primary purpose of the method is type conversion. By obtaining the corpus or subcorpus in the format specified by the argument `to`, the data can be processed with tools that do not rely on the Corpus Workbench (CWB). Supported output formats are `data.table` (which can be converted to a `data.frame` or `tibble` easily) or an `Annotation` object as defined in the package 'NLP'. Another purpose of decoding the corpus can be to rework it, and to re-import it into the CWB (e.g. using the 'cwbtools'-package).

An earlier version of the method included an option to decode a single s-attribute, which is not supported any more. See the `s_attribute_decode()` function of the package `RcppCWB`.

If `.Object` is an integer vector, it is assumed to be a vector of integer ids of p-attributes. The `decode-method` will translate token ids to string values as efficiently as possible. The approach taken will depend on the corpus size and the share of the corpus that is to be decoded. To decode a large number of integer ids, it is more efficient to read the lexicon file from the data directory directly and to index the lexicon with the ids rather than relying on `RcppCWB::c1_id2str`. The internal decision rule is to use the lexicon file when the corpus is larger than 10 000 000 million tokens and more than 5 percent of the corpus are to be decoded. The encoding of the character vector that is returned will be the coding of the locale (usually ISO-8859-1 on Windows, and UTF-8 on macOS and Linux machines).

The `decode-method` for `data.table` objects will decode token ids (column 'p-attribute_id'), adding the corresponding string as a new column. If a column "cpos" with corpus positions is present, ids are derived for the corpus positions given first. If the `data.table` neither has a column "cpos" nor columns with token ids (i.e. column name ending with "_id"), the input `data.table` is returned unchanged. Note that columns are added to the `data.table` in an in-place operation to handle memory parsimoniously.

Value

The return value will correspond to the class specified by argument `to`.

See Also

To decode a structural attribute, you can use the `s_attributes-method`, setting argument `unique` as FALSE and `s_attribute_decode`. See [as.VCorpus](#) to decode a `partition_bundle` object, returning a `VCorpus` object.

Examples

```

use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

# Decode corpus as data.table
dt <- decode("REUTERS", to = "data.table")

# Decode corpus selectively
dt <- decode(
  "REUTERS",
  to = "data.table",
  p_attributes = "word",
  s_attributes = "id"
)

# Decode a subcorpus
dt <- corpus("REUTERS") %>%
  subset(id %in% c("127", "144")) %>%
  decode(s_attributes = "id", to = "data.table")

# Decode partition
dt <- partition("REUTERS", places = "kuwait", regex = TRUE) %>%
  decode(to = "data.table")

# Previous versions of polmineR offered an option to decode a single
# s-attribute. This is how you could proceed to get a table with metadata.
dt <- partition("REUTERS", places = "kuwait", regex = TRUE) %>%
  decode(s_attribute = "id", decode = FALSE, to = "data.table")
dt[, "word" := NULL]
dt[, {list(cpos_left = min(.SD[["cpos"]]), cpos_right = max(.SD[["cpos"]]))}, by = "id"]

# Decode subcorpus as Annotation object
## Not run:
if (requireNamespace("NLP")){
  library(NLP)
  p <- corpus("GERMAPARLMINI") %>%
    subset(date == "2009-11-10" & speaker == "Angela Dorothea Merkel")
  s <- as(p, "String")
  a <- as(p, "Annotation")

  # The beauty of having this NLP Annotation object is that you can now use
  # the different annotators of the openNLP package. Here, just a short scenario
  # how you can have a look at the tokenized words and the sentences.

  words <- s[a$type == "word"]
  sentences <- s[a$type == "sentence"] # does not yet work perfectly for plenary protocols

  doc <- decode(p, to = "AnnotatedPlainTextDocument")
}

## End(Not run)

```

```
# decode vector of token ids
y <- decode(0:20, corpus = "GERMAPARLMINI", p_attributes = "word")
dt <- data.table::data.table(cpos = cpos("GERMAPARLMINI", query = "Liebe")[,1])
decode(dt, corpus = "GERMAPARLMINI", p_attributes = c("word", "pos"))
y <- dt[, .N, by = c("word", "pos")]
```

dispersion

Dispersion of a query or multiple queries.

Description

The method returns a `data.table` with the number of matches of a query or multiple queries (optionally frequencies) in a corpus or subcorpus as partitioned by one or two s-attributes.

Usage

```
dispersion(.Object, ...)
```

```
## S4 method for signature 'slice'
```

```
dispersion(
  .Object,
  query,
  s_attribute,
  cqp = FALSE,
  p_attribute = getOption("polmineR.p_attribute"),
  freq = FALSE,
  fill = TRUE,
  mc = FALSE,
  progress = FALSE,
  verbose = FALSE,
  ...
)
```

```
## S4 method for signature 'partition'
```

```
dispersion(
  .Object,
  query,
  s_attribute,
  cqp = FALSE,
  p_attribute = getOption("polmineR.p_attribute"),
  freq = FALSE,
  fill = TRUE,
  mc = FALSE,
  progress = TRUE,
  verbose = FALSE,
  ...
)
```

```
## S4 method for signature 'subcorpus'
dispersion(
  .Object,
  query,
  s_attribute,
  cqp = FALSE,
  p_attribute = getOption("polmineR.p_attribute"),
  freq = FALSE,
  fill = FALSE,
  mc = FALSE,
  progress = TRUE,
  verbose = FALSE,
  ...
)

## S4 method for signature 'corpus'
dispersion(
  .Object,
  query,
  s_attribute,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  freq = FALSE,
  fill = TRUE,
  mc = FALSE,
  progress = FALSE,
  verbose = FALSE,
  ...
)

## S4 method for signature 'character'
dispersion(
  .Object,
  query,
  s_attribute,
  cqp = is.cqp,
  p_attribute = getOption("polmineR.p_attribute"),
  freq = FALSE,
  fill = TRUE,
  mc = FALSE,
  progress = TRUE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'hits'
dispersion(
```

```

    .Object,
    source,
    s_attribute,
    freq = FALSE,
    fill = TRUE,
    verbose = TRUE,
    ...
)

## S4 method for signature 'remote_corpus'
dispersion(.Object, ...)

## S4 method for signature 'remote_subcorpus'
dispersion(.Object, ...)

```

Arguments

<code>.Object</code>	A corpus, subcorpus or partition object or a corpus provided by a character string.
<code>...</code>	Further parameters.
<code>query</code>	A character vector stating one or multiple queries.
<code>s_attribute</code>	A character vector (length 1 or 2) providing s-attributes.
<code>cqp</code>	If logical, whether the query is a CQP query, if it is a function that is passed in, the function will be applied to the query to guess whether query is a CQP query
<code>p_attribute</code>	Length one character vector, the p-attribute that will be looked up (typically 'word' or 'lemma').
<code>freq</code>	A logical value, whether to calculate normalized frequencies.
<code>fill</code>	A logical value, whether to report zero matches. Defaults to TRUE. But note that if there are few matches and many values of the s-attribute(s), the resulting data structure is sparse and potentially bloated.
<code>mc</code>	A logical value, whether to use multicore.
<code>progress</code>	A logical value, whether to show progress.
<code>verbose</code>	A logical value, whether to be verbose.
<code>source</code>	The source of the evaluation the hits reported in <code>.Object</code> are based on, a corpus, subcorpus or partition object.

Details

Augmenting the `data.table` with zeros for subcorpora that do not yield query matches (argument `fill = TRUE`) may require adding many new columns. A respective warning issued by the `data.table` package is supplemented an additional explanatory note of the `polmineR` package.

Value

A `data.table`.
 A `data.table`.

Author(s)

Andreas Blaette

See Also

The worker behind the dispersion-method is the hits-method.

count

Examples

```
use("polmineR")
dispersion("GERMAPARLMINI", query = "Integration", s_attribute = "date")

test <- partition("GERMAPARLMINI", date = ".*", p_attribute = NULL, regex = TRUE)
integration <- dispersion(
  test, query = "Integration",
  p_attribute = "word", s_attribute = "date"
)
integration <- dispersion(test, "Integration", s_attribute = c("date", "party"))
integration <- dispersion(test, "'Integration.*'", s_attribute = "date", cqp = TRUE)
```

dotplot

dotplot

Description

dotplot

Usage

```
dotplot(.Object, ...)

## S4 method for signature 'textstat'
dotplot(.Object, col, n = 20L, ...)

## S4 method for signature 'features'
dotplot(.Object, col = NULL, n = 20L, ...)

## S4 method for signature 'features_ngrams'
dotplot(.Object, col = NULL, n = 20L, ...)

## S4 method for signature 'partition'
dotplot(.Object, col = "count", n = 20L, ...)
```

Arguments

.Object	object
...	further arguments that will be passed into the dotchart function
col	column
n	number

encoding	<i>Get and set encoding.</i>
----------	------------------------------

Description

Method for textstat objects and classes inheriting from textstat; if object is a character vector, the encoding of the corpus is returned. If called without arguments, the session character set is returned.

Usage

```
encoding(object)

encoding(object) <- value

## S4 method for signature 'missing'
encoding(object)

## S4 method for signature 'textstat'
encoding(object)

## S4 method for signature 'bundle'
encoding(object)

## S4 method for signature 'character'
encoding(object)

## S4 method for signature 'corpus'
encoding(object)

## S4 method for signature 'subcorpus'
encoding(object)

## S4 method for signature 'call'
encoding(object)

## S4 method for signature 'quosure'
encoding(object)
```

```
## S4 replacement method for signature 'call'
encoding(object) <- value

## S4 replacement method for signature 'quosure'
encoding(object) <- value
```

Arguments

object	A textstat or bundle object (or an object inheriting from these classes), or a length-one character vector specifying a corpus. If missing, the method will return the session character set.
value	Value to be assigned.

Details

encoding() uses `l10n_info()` and `localeToCharset()` (in this order) to determine the session encoding. If `localeToCharset()` returns NA, "UTF-8" is assumed to be the session encoding.

Value

A length-one character vector with an encoding.

Examples

```
# Get session charset.
encoding()

# Get encoding of a corpus.
encoding("REUTERS")

# Get encoding of a partition.
r <- partition("REUTERS", places = "kuwait", regex = TRUE)
encoding(r)

# Get encoding of another class inheriting from textstat (count).
cnt <- count("REUTERS", p_attribute = "word")
encoding(cnt)

# Get encoding of objects in a bundle.
pb <- partition_bundle("REUTERS", s_attribute = "id")
encoding(pb)
```

encodings

Conversion between corpus and native encoding.

Description

Utility functions to convert the encoding of a character vector between the native encoding and the encoding of the corpus.

Usage

```
as.utf8(x, from)
```

```
as.nativeEnc(x, from)
```

```
as.corpusEnc(x, from = encoding(), corpusEnc)
```

Arguments

x	A character to be converted.
from	A character vector describing the encoding of the input character vector.
corpusEnc	A character vector describing the target encoding, i.e. the encoding of the corpus (usually "latin1", "UTF-8")

Details

The encoding of a corpus and the encoding of the terminal (the native encoding) may differ, provoking strange or wrong results if no conversion is carried out between the potentially differing encodings. The functions `as.nativeEnc()` and `as.corpusEnc` are auxiliary functions to assist the conversion. The functions `as.nativeEnc` and `as.utf8` deliberately remove the explicit statement of the encoding, to avoid warnings that may occur with character vector columns in a `data.table` object.

enrich	<i>Enrich an object.</i>
--------	--------------------------

Description

Methods to enrich objects with additional (statistical) information. The methods are documented with the classes to which they adhere. See the references in the `seealso`-section.

Usage

```
enrich(.Object, ...)
```

Arguments

.Object	a <code>partition</code> , <code>partition_bundle</code> or <code>comp</code> object
...	further parameters

See Also

The `enrich` method is defined for the following classes: "partition", (see [partition-class](#)), "partition_bundle" (see [partition_bundle-class](#)), "kwic" (see [kwic-class](#)), and "context" (see [context-class](#)). See the linked documentation to learn how the `enrich` method can be applied to respective objects.

features

Get features by comparison.

Description

The features of two objects, usually a partition defining a corpus of interest (coi), and a partition defining a reference corpus (ref) are compared. The most important purpose is term extraction.

Usage

```
features(x, y, ...)
```

```
## S4 method for signature 'partition'
```

```
features(x, y, included = FALSE, method = "chisquare", verbose = FALSE)
```

```
## S4 method for signature 'count'
```

```
features(  
  x,  
  y,  
  by = NULL,  
  included = FALSE,  
  method = "chisquare",  
  verbose = TRUE  
)
```

```
## S4 method for signature 'partition_bundle'
```

```
features(  
  x,  
  y,  
  included = FALSE,  
  method = "chisquare",  
  verbose = TRUE,  
  mc = getOption("polmineR.mc"),  
  progress = FALSE  
)
```

```
## S4 method for signature 'count_bundle'
```

```
features(  
  x,  
  y,  
  included = FALSE,  
  method = "chisquare",  
  verbose = !progress,  
  mc = getOption("polmineR.mc"),  
  progress = FALSE  
)
```

```
## S4 method for signature 'ngrams'
features(x, y, included = FALSE, method = "chisquare", verbose = TRUE, ...)

## S4 method for signature 'Cooccurrences'
features(x, y, included = FALSE, method = "ll", verbose = TRUE)
```

Arguments

x	A partition or partition_bundle object.
y	A partition object, it is assumed that the coi is a subcorpus of ref
...	further parameters
included	TRUE if coi is part of ref, defaults to FALSE
method	the statistical test to apply (chisquare or log likelihood)
verbose	A logical value, defaults to TRUE
by	the columns used for merging, if NULL (default), the p-attribute of x will be used
mc	logical, whether to use multicore
progress	logical

Author(s)

Andreas Blaette

References

Baker, Paul (2006): *Using Corpora in Discourse Analysis*. London: continuum, p. 121-149 (ch. 6).
Manning, Christopher D.; Schuetze, Hinrich (1999): *Foundations of Statistical Natural Language Processing*. MIT Press: Cambridge, Mass., pp. 151-189 (ch. 5).

Examples

```
## Not run:
use("polmineR")

kauder <- partition(
  "GERMAPARLMINI",
  speaker = "Volker Kauder", interjection = "speech",
  p_attribute = "word"
)
all <- partition("GERMAPARLMINI", interjection = "speech", p_attribute = "word")

terms_kauder <- features(x = kauder, y = all, included = TRUE)
top100 <- subset(terms_kauder, rank_chisquare <= 100)
head(top100)

# a different way is to compare count objects
kauder_count <- as(kauder, "count")
all_count <- as(all, "count")
```

```

terms_kauder <- features(kauder_count, all_count, included = TRUE)
top100 <- subset(terms_kauder, rank_chisquare <= 100)
head(top100)

## End(Not run)

# get matrix with features (dontrun to keep time for examples short)
## Not run:
use("RcppCWB")
docs <- partition_bundle("REUTERS", s_attribute = "id") %>%
  enrich( p_attribute = "word")
all <- corpus("REUTERS") %>%
  count(p_attribute = "word")
docs_terms <- features(docs[1:5], all, included = TRUE, progress = FALSE)
dtm <- as.DocumentTermMatrix(docs_terms, col = "chisquare", verbose = FALSE)

## End(Not run)
# Get features of objects in a count_bundle
ref <- corpus("GERMAPARLMINI") %>% count(p_attribute = "word")
cois <- corpus("GERMAPARLMINI") %>%
  subset(speaker %in% c("Angela Dorothea Merkel", "Hubertus Heil")) %>%
  split(s_attribute = "speaker") %>%
  count(p_attribute = "word")
y <- features(cois, ref, included = TRUE, method = "chisquare", progress = TRUE)

```

features-class	<i>Feature selection by comparison.</i>
----------------	---

Description

The features-method returns a features-object. Several features-objects can be combined into a features_bundle-object.

Usage

```

## S4 method for signature 'features'
summary(object)

## S4 method for signature 'features'
show(object)

## S4 method for signature 'features_bundle'
summary(object)

## S4 method for signature 'features'
format(x, digits = 2L)

## S4 method for signature 'features'
view(.Object)

```

Arguments

object	A features or features_bundle object.
x	A features object.
digits	Integer indicating the number of decimal places (round) or significant digits (signif) to be used.
.Object	a features object.

Details

A set of features objects can be combined into a features_bundle. Typically, a features_bundle will result from applying the features-method on a partition_bundle. See the documentation for bundle to learn about the methods for bundle objects that are available for a features_bundle.

Slots

corpus	The CWB corpus the features are derived from, a character vector of length 1.
p_attribute	Object of class character.
encoding	Object of class character.
corpus	Object of class character.
stat	Object of class data.frame.
size_coi	Object of class integer.
size_ref	Object of class integer.
included	Object of class logical whether corpus of interest is included in reference corpus
method	Object of class character statisticalTest used
call	Object of class character the call that generated the object

Author(s)

Andreas Blaette

get_template	<i>Get template for formatting full text output.</i>
--------------	--

Description

Templates are used to format the markdown/html of fulltext. get_template() loads and parses the content of the JSON template file, if it is found in the slot "template" of .Object.

Usage

```
get_template(.Object, ...)  
  
## S4 method for signature 'character'  
get_template(.Object, warn = FALSE)  
  
## S4 method for signature 'corpus'  
get_template(.Object, warn = FALSE)  
  
## S4 method for signature 'subcorpus'  
get_template(.Object, warn = FALSE)
```

Arguments

.Object	A corpus, subcorpus or partition object, or a length-one character vector with a corpus ID.
...	Further arguments.
warn	A logical value, whether to issue a warning if template is not available. Defaults to FALSE.

Details

To learn how to write templates, consult the sample files in the folder "templates" of the installed package - see examples.

Value

If a template is available, a list with the parsed content of the template file, otherwise NULL.

Examples

```
use("polmineR")  
corpus("GERMAPARLMINI") %>%  
  get_template()  
  
# template files included in the package  
template_dir <- system.file(package = "polmineR", "templates")  
list.files(template_dir)
```

get_token_stream *Get Token Stream.*

Description

Auxiliary method to get the fulltext of a corpus, subcorpora etc. Can be used to export corpus data to other tools.

Usage

```
get_token_stream(.Object, ...)  
  
## S4 method for signature 'numeric'  
get_token_stream(  
  .Object,  
  corpus,  
  registry = NULL,  
  p_attribute,  
  subset = NULL,  
  boost = NULL,  
  encoding = NULL,  
  collapse = NULL,  
  beautify = TRUE,  
  cpos = FALSE,  
  cutoff = NULL,  
  decode = TRUE,  
  ...  
)  
  
## S4 method for signature 'matrix'  
get_token_stream(.Object, corpus, registry = NULL, split = FALSE, ...)  
  
## S4 method for signature 'corpus'  
get_token_stream(.Object, left = NULL, right = NULL, ...)  
  
## S4 method for signature 'character'  
get_token_stream(.Object, left = NULL, right = NULL, ...)  
  
## S4 method for signature 'slice'  
get_token_stream(.Object, p_attribute, collapse = NULL, cpos = FALSE, ...)  
  
## S4 method for signature 'partition'  
get_token_stream(.Object, p_attribute, collapse = NULL, cpos = FALSE, ...)  
  
## S4 method for signature 'subcorpus'  
get_token_stream(.Object, p_attribute, collapse = NULL, cpos = FALSE, ...)  
  
## S4 method for signature 'regions'  
get_token_stream(  
  .Object,  
  p_attribute = "word",  
  collapse = NULL,  
  cpos = FALSE,  
  split = FALSE,  
  ...  
)
```

```

## S4 method for signature 'partition_bundle'
get_token_stream(
  .Object,
  p_attribute = "word",
  vocab = NULL,
  phrases = NULL,
  subset = NULL,
  min_length = NULL,
  collapse = NULL,
  cpos = FALSE,
  decode = TRUE,
  beautify = FALSE,
  verbose = TRUE,
  progress = FALSE,
  mc = FALSE,
  ...
)

```

Arguments

.Object	Input object.
...	Arguments that will be passed into the <code>get_token_stream</code> -method for a numeric vector, the real worker.
corpus	A CWB indexed corpus.
registry	Registry directory with registry file describing the corpus.
p_attribute	A character vector, the p-attribute(s) to decode.
subset	An expression applied on p-attributes, using non-standard evaluation. Note that symbols used in the expression may not be used internally (e.g. 'stopwords').
boost	A length-one logical value, whether to speed up decoding a long vector of token ids by directly by reading in the lexicon file from the data directory of a corpus. If NULL (default), the internal decision rule is that boost will be TRUE if the corpus is larger than 10 000 000 million tokens and more than 5 percent of the corpus are to be decoded.
encoding	If not NULL (default) a length-one character vector stating an encoding that will be assigned to the (decoded) token stream.
collapse	If not NULL (default), a length-one character string passed into <code>paste</code> to collapse character vector into a single string.
beautify	A (length-one) logical value, whether to adjust whitespace before and after interpunctuation.
cpos	A logical value, whether to return corpus positions as names of the tokens.
cutoff	Maximum number of tokens to be reconstructed.
decode	A (length-one) logical value, whether to decode token ids to character strings. Defaults to TRUE, if FALSE, an integer vector with token ids is returned.
split	A logical value, whether to return a character vector (when <code>split</code> is FALSE, default) or a list of character vectors; each of these vectors will then represent the tokens of a region defined by a row in a regions matrix.

left	Left corpus position.
right	Right corpus position.
vocab	A character vector with an alternative vocabulary to the one stored on disk.
phrases	A phrases object. Defined phrases will be concatenated.
min_length	If not NULL (default), an integer value with minimum length of documents required to keep them in the list object that is returned.
verbose	A length-one logical value, whether to show messages.
progress	A length-one logical value, whether to show progress bar.
mc	Number of cores to use. If FALSE (default), only one thread will be used.

Details

CWB indexed corpora have a fixed order of tokens which is called the *token stream*. Every token is assigned to a unique *corpus position*. Subsets of the (entire) token stream defined by a left and a right corpus position are called *regions*. The `get_token_stream`-method will extract the tokens (for regions) from a corpus.

The primary usage of this method is to return the token stream of a (sub-)corpus as defined by a corpus, subcorpus or partition object. The methods defined for a numeric vector or a (two-column) matrix defining regions (i.e. left and right corpus positions in the first and second column) are the actual workers for this operation.

The `get_token_stream` has been introduced so serve as a worker by higher level methods such as `read`, `html`, and `as.markdown`. It may however be useful for decoding a corpus so that it can be exported to other tools.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

# Decode first words of REUTERS corpus (first sentence)
get_token_stream(0:20, corpus = "REUTERS", p_attribute = "word")

# Decode first sentence and collapse tokens into single string
get_token_stream(0:20, corpus = "REUTERS", p_attribute = "word", collapse = " ")

# Decode regions defined by two-column integer matrix
region_matrix <- matrix(c(0L,20L,21L,38L), ncol = 2, byrow = TRUE)
get_token_stream(
  region_matrix,
  corpus = "REUTERS",
  p_attribute = "word",
  encoding = "latin1"
)

# Use argument 'beautify' to remove surplus whitespace
## Not run:
get_token_stream(
  region_matrix,
  corpus = "GERMAPARLMINI",
```

```

    p_attribute = "word",
    encoding = "latin1",
    collapse = " ", beautify = TRUE
  )

## End(Not run)

# Decode entire corpus (corpus object / specified by corpus ID)
corpus("REUTERS") %>%
  get_token_stream(p_attribute = "word") %>%
  head()

# Decode subcorpus
corpus("REUTERS") %>%
  subset(id == "127") %>%
  get_token_stream(p_attribute = "word") %>%
  head()

# Decode partition_bundle
## Not run:
pb_tokstr <- corpus("REUTERS") %>%
  split(s_attribute = "id") %>%
  get_token_stream(p_attribute = "word")

## End(Not run)
## Not run:
# Get token stream for partition_bundle
pb <- partition_bundle("REUTERS", s_attribute = "id")
ts_list <- get_token_stream(pb)

# Use two p-attributes
sp <- corpus("GERMAPARLMINI") %>%
  as.speeches(s_attribute_name = "speaker", s_attribute_date = "date", progress = FALSE)
p2 <- get_token_stream(sp, p_attribute = c("word", "pos"), verbose = FALSE)

# Apply filter
p_sub <- get_token_stream(
  sp, p_attribute = c("word", "pos"),
  subset = {!grepl("(\\$.|$|ART)", pos)}
)

# Concatenate phrases and apply filter
queries <- c("'freiheitliche" "Grundordnung"', "'Bundesrepublik" "Deutschland"' )
phr <- corpus("GERMAPARLMINI") %>%
  cpos(query = queries) %>%
  as.phrases(corpus = "GERMAPARLMINI")

kill <- tm::stopwords("de")

ts_phr <- get_token_stream(
  sp,
  p_attribute = c("word", "pos"),
  subset = {!word %in% kill & !grepl("(\\$.|$|ART)", pos)},

```

```

    phrases = phr,
    progress = FALSE,
    verbose = FALSE
)

## End(Not run)

```

get_type

Get corpus/partition type.

Description

To generate fulltext output, different templates can be used with a behavior that depends on the type of a corpus. `get_type` will return the type of corpus if it is a specialized one, or NULL.

Usage

```

get_type(.Object)

## S4 method for signature 'corpus'
get_type(.Object)

## S4 method for signature 'character'
get_type(.Object)

## S4 method for signature 'partition_bundle'
get_type(.Object)

## S4 method for signature 'subcorpus_bundle'
get_type(.Object)

```

Arguments

`.Object` A partition, partition_bundle, Corpus object, or a length-one character vector indicating a CWB corpus.

Details

When generating a partition, the corpus type will be prefixed to the class that is generated (separated by underscore). If the corpus type is not NULL, a class inheriting from the `partition`-class is instantiated. Note that at this time, only `plpr_partition` and `press_partition` is implemented.

Examples

```

use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

get_type("GERMAPARLMINI")

```

```

p <- partition("GERMAPARLMINI", date = "2009-10-28")
get_type(p)
is(p)

pb <- partition_bundle("GERMAPARLMINI", s_attribute = "date")
get_type(pb)

get_type("REUTERS") # returns NULL - no specialized corpus

```

highlight-method	<i>Highlight tokens in text output.</i>
------------------	---

Description

Highlight tokens in fulltext based on exact match, a regular expression or corpus position in kwic output or html document.

Usage

```

highlight(.Object, ...)

## S4 method for signature 'character'
highlight(.Object, highlight = list(), regex = FALSE, perl = FALSE, ...)

## S4 method for signature 'html'
highlight(.Object, highlight = list(), regex = FALSE, perl = FALSE, ...)

## S4 method for signature 'kwic'
highlight(
  .Object,
  highlight = list(),
  regex = FALSE,
  perl = TRUE,
  verbose = TRUE,
  ...
)

```

Arguments

.Object	A html, character, a kwic object.
...	Terms to be highlighted can be passed in as named character vectors of terms (or regular expressions); the name needs to be a valid color name. It is also possible to pass in a matrix with ranges (as returned by cpos()).
highlight	A character vector, or a list of character or integer vectors.
regex	Logical, whether character vectors are interpreted as regular expressions.

perl	Logical, whether to use perl-style regular expressions for highlighting when regex is TRUE.
verbose	Logical, whether to output messages.

Details

If `highlight` is a character vector, the names of the vector are interpreted as colors. If `highlight` is a list, the names of the list are considered as colors. Values can be character values or integer values with token ids. Colors are inserted into the output html and need to be digestable for the browser used.

Examples

```
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

P <- partition("REUTERS", places = "argentina")
H <- html(P)
Y <- highlight(H, list(lightgreen = "higher"))
if (interactive()) htmltools::html_print(Y)

# highlight matches for a CQP query
regions <- cpos(P, query = "'prod.*'", cqp = TRUE)
H2 <- highlight(H, highlight = list(yellow = regions))

# the method can be used in pipe
P %>% html() %>% highlight(list(lightgreen = "1986")) -> H
P %>% html() %>% highlight(list(lightgreen = c("1986", "higher"))) -> H
P %>% html() %>% highlight(list(lightgreen = 4020:4023)) -> H

# use highlight for kwic output
K <- kwic("REUTERS", query = "barrel")
K2 <- highlight(K, highlight = list(yellow = c("oil", "price")))

# use character vector for output, not list
K2 <- highlight(
  K,
  highlight = c(
    green = "pric.",
    red = "reduction",
    red = "decrease",
    orange = "dropped"
  ),
  regex = TRUE
)
```

Description

Get hits for queries, optionally with s-attribute values.

Usage

```
hits(.Object, ...)
```

```
## S4 method for signature 'corpus'
```

```
hits(  
  .Object,  
  query,  
  cqp = FALSE,  
  check = TRUE,  
  s_attribute,  
  p_attribute = "word",  
  size = FALSE,  
  freq = FALSE,  
  decode = TRUE,  
  fill = FALSE,  
  mc = 1L,  
  verbose = TRUE,  
  progress = FALSE,  
  ...  
)
```

```
## S4 method for signature 'character'
```

```
hits(  
  .Object,  
  query,  
  cqp = FALSE,  
  check = TRUE,  
  s_attribute,  
  p_attribute = "word",  
  size = FALSE,  
  freq = FALSE,  
  decode = TRUE,  
  mc = FALSE,  
  verbose = TRUE,  
  progress = FALSE,  
  ...  
)
```

```
## S4 method for signature 'subcorpus'
```

```
hits(  
  .Object,  
  query,  
  cqp = FALSE,  
  check = TRUE,
```

```
s_attribute,  
p_attribute = "word",  
size = FALSE,  
freq = FALSE,  
fill = FALSE,  
decode = TRUE,  
mc = FALSE,  
progress = FALSE,  
verbose = TRUE,  
...  
)  
  
## S4 method for signature 'partition'  
hits(  
  .Object,  
  query,  
  cqp = FALSE,  
  check = TRUE,  
  s_attribute,  
  p_attribute = "word",  
  size = FALSE,  
  freq = FALSE,  
  fill = FALSE,  
  decode = TRUE,  
  mc = FALSE,  
  progress = FALSE,  
  verbose = TRUE  
)  
  
## S4 method for signature 'partition_bundle'  
hits(  
  .Object,  
  query,  
  cqp = FALSE,  
  check = TRUE,  
  p_attribute = getOption("polmineR.p_attribute"),  
  s_attribute,  
  size = TRUE,  
  freq = FALSE,  
  mc = getOption("polmineR.mc"),  
  progress = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
## S4 method for signature 'context'  
hits(.Object, s_attribute = NULL, verbose = TRUE, ...)
```

```
## S4 method for signature 'remote_corpus'
hits(.Object, ...)
```

```
## S4 method for signature 'remote_subcorpus'
hits(.Object, ...)
```

Arguments

<code>.Object</code>	A length-one character vector with a corpus ID, a <code>partition</code> or <code>partition_bundle</code> object
<code>...</code>	Further arguments (used for backwards compatibility).
<code>query</code>	A character vector (optionally named, see details) with one or more queries.
<code>cqp</code>	Either a logical value (TRUE if query is a CQP query), or a function to check whether query is a CQP query or not.
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .
<code>s_attribute</code>	A character vector of s-attributes that will be used to breakdown counts for matches for query/queries.
<code>p_attribute</code>	A character vector stating a p-attribute.
<code>size</code>	A logical value, whether to report the size of subcorpus.
<code>freq</code>	A logical value, whether to report relative frequencies.
<code>decode</code>	A logical value, whether to decode s-attributes. If FALSE, the integer values of strucs are reported in the table with matches.
<code>fill</code>	A logical value, whether to report counts (optionally frequencies) for combinations of s-attributes where not matchers occur.
<code>mc</code>	A logical value, whether to use multicore.
<code>verbose</code>	A logical value, whether to output messages.
<code>progress</code>	A logical value, whether to show progress bar.

Details

If the character vector provided by `query` is named, these names will be reported in the `data.table` that is returned rather than the queries.

If `freq` is TRUE, the `data.table` returned in the DT-slot will deliberately include the subsets of the `partition/corpus` with no hits (`query` is NA, `count` is 0).

Value

A hits class object.

See Also

See the documentation of the hits class ([hits-class](#)) for details.

Examples

```

use(pkg = "RcppCWB", corpus = "REUTERS")

# get hits for corpus object
y <- corpus("REUTERS") %>% hits(query = "oil")
y <- corpus("REUTERS") %>% hits(query = c("oil", "barrel"))
y <- corpus("REUTERS") %>% hits(query = "oil", s_attribute = "places", freq = TRUE)

# specify corpus by corpus ID
y <- hits("REUTERS", query = "oil")
y <- hits("REUTERS", query = "oil", s_attribute = "places", freq = TRUE)

# get hits for partition
p <- partition("REUTERS", places = "saudi-arabia", regex = TRUE)
y <- hits(p, query = "oil", s_attribute = "id")

# get hits for subcorpus
y <- corpus("REUTERS") %>%
  subset(grep("saudi-arabia", places)) %>%
  hits(query = "oil")

```

hits_class

S4 class to represent hits for queries.

Description

S4 class to represent hits for queries.

Usage

```

## S4 method for signature 'hits'
sample(x, size)

```

Arguments

x	A hits object.
size	A non-negative integer giving the number of items to choose.

Slots

stat A data.table with the following columns:

query The query (optionally using CQP syntax) that evoked a hit.

count Number of matches in corpus/subcorpus.

freq Relative frequency of matches in corpus/subcorpus (optional, presence depends on usage of argument freq of the hits method).

size Total number of tokens in corpus/subcorpus (optional, presence depends on usage of argument size of the hits method).

If argument `s_attribute` has been used in the call of the `hits` method, the `data.table` will include additional columns with the `s`-attributes. The values in the columns will be the values these `s`-attributes assume. Columns `count`, `freq` and `size` will be based on subcorpora defined by (combinations of) `s`-attributes.

`corpus` A length-one "character" vector, ID of the corpus with hits for query or queries.

`query` Object of class "character", query or queries for

`p_attribute` The `p`-attribute that has been queried, a length-one character vector.

`encoding` Length-one character vector, the encoding of the corpus.

`name` Length-one character vector, name of the object.

href-function	<i>Add hypertext reference to html document.</i>
---------------	--

Description

Add hypertext reference to html document.

Usage

```
href(x, href, fmt, verbose = TRUE)
```

Arguments

<code>x</code>	Object of class 'html'.
<code>href</code>	A named list with hypertext references that will be inserted as attribute <code>href</code> of a elements. The names of the list are either colors of highlighted text that has been generated previously, or corpus positions.
<code>fmt</code>	A format string with an <code>xpath</code> expression used to look up the node where the tooltip is inserted. If missing, a heuristic evaluating the names of the <code>tooltips</code> list decides whether tooltips are inserted based on highlighting colors or corpus positions.
<code>verbose</code>	A logical value, whether to show messages.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

a <- corpus("REUTERS") %>%
  subset(places = "argentina") %>%
  html() %>%
  highlight(lightgreen = 3997) %>%
  href(href = list("3997" = "https://en.wikipedia.org/wiki/Argentina"))

if (interactive()) show(a)
```

html	<i>Generate html from object.</i>
------	-----------------------------------

Description

Prepare html document to see full text.

Usage

```
html(object, ...)  
  
## S4 method for signature 'character'  
html(object, corpus, height = NULL)  
  
## S4 method for signature 'partition'  
html(  
  object,  
  meta = NULL,  
  cpos = TRUE,  
  verbose = FALSE,  
  cutoff = NULL,  
  charoffset = FALSE,  
  beautify = TRUE,  
  height = NULL,  
  ...  
)  
  
## S4 method for signature 'subcorpus'  
html(  
  object,  
  meta = NULL,  
  cpos = TRUE,  
  verbose = FALSE,  
  cutoff = NULL,  
  charoffset = FALSE,  
  beautify = FALSE,  
  height = NULL,  
  ...  
)  
  
## S4 method for signature 'partition_bundle'  
html(  
  object,  
  charoffset = FALSE,  
  beautify = TRUE,  
  height = NULL,  
  progress = TRUE,
```

```

    ...
)

## S4 method for signature 'kwic'
html(object, i, s_attribute = NULL, type = NULL, verbose = FALSE)

## S4 method for signature 'remote_subcorpus'
html(object, ...)

```

Arguments

<code>object</code>	The object the fulltext output will be based on.
<code>...</code>	Further parameters that are passed into <code>as.markdown()</code> .
<code>corpus</code>	The ID of the corpus, a length-one character vector.
<code>height</code>	A character vector that will be inserted into the html as an optional height of a scroll box.
<code>meta</code>	Metadata to include in output, if NULL (default), the s-attributes defining a partition will be used.
<code>cpos</code>	Length-one logical value, if TRUE (default), all tokens will be wrapped by elements with id attribute indicating corpus positions.
<code>verbose</code>	Length-one logical value, whether to output progress messages.
<code>cutoff</code>	An integer value, maximum number of tokens to decode from token stream, passed into <code>as.markdown()</code> .
<code>charoffset</code>	Length-one logical value, if TRUE, character offset positions are added to elements embracing tokens.
<code>beautify</code>	A logical value, if TRUE, whitespace before interpunctuation will be removed.
<code>progress</code>	Length-one logical value, whether to output progress bar.
<code>i</code>	An integer value: If object is a kwic-object, the index of the concordance for which the fulltext is to be generated.
<code>s_attribute</code>	Structural attributes that will be used to define the partition where the match occurred.
<code>type</code>	The partition type.

Details

Substitutions configured by option `'polmineR.mdsup'` are applied to prevent presence of characters that would be misinterpreted as markdown formatting instructions.

If param `charoffset` is TRUE, character offset positions will be added to tags that embrace tokens. This may be useful, if exported html document is annotated with a tool that stores annotations with character offset positions.

Value

Returns an object of class `html` as used in the `'htmltools'` package. Methods such as `htmltools::html_print()` will be available. The encoding of the html document will be UTF-8 on all systems (including Windows).

Examples

```

use(pkg = "RcppCWB", corpus = "REUTERS")

P <- partition("REUTERS", places = "argentina")
H <- html(P)
if (interactive()) H # show full text in viewer pane

# html-method can be used in a pipe
H <- partition("REUTERS", places = "argentina") %>% html()

# use html-method to get full text where concordance occurs
K <- kwic("REUTERS", query = "barrels")
H <- html(K, i = 1, s_attribute = "id")
H <- html(K, i = 2, s_attribute = "id")
for (i in 1L:length(K)) {
  H <- html(K, i = i, s_attribute = "id")
  if (interactive()){
    show(H)
    userInput <- readline("press 'q' to quit or any other key to continue")
    if (userInput == "q") break
  }
}

```

is_nested

Check whether s-attributes of corpus are nested

Description

Simple test whether the attribute size of all s-attributes of a corpus is identical (flat import XML) or not (nested import XML).

Usage

```
is_nested(x)
```

Arguments

x A character vector with corpus ID or a corpus object.

Value

A logical value: FALSE if data structure is flat and TRUE if data structure is nested.

Examples

```

use("polmineR")
use("RcppCWB")

```

`kwic`*Perform keyword-in-context (KWIC) analysis.*

Description

Get concordances for the matches for a query / perform keyword-in-context (kwic) analysis.

Usage

```
kwic(.Object, ...)  
  
## S4 method for signature 'context'  
kwic(  
  .Object,  
  s_attributes = getOption("polmineR.meta"),  
  cpos = TRUE,  
  verbose = FALSE  
)  
  
## S4 method for signature 'slice'  
kwic(  
  .Object,  
  query,  
  cqp = is.cqp,  
  left = getOption("polmineR.left"),  
  right = getOption("polmineR.right"),  
  s_attributes = getOption("polmineR.meta"),  
  region = NULL,  
  p_attribute = "word",  
  boundary = NULL,  
  cpos = TRUE,  
  stoplist = NULL,  
  positivelist = NULL,  
  regex = FALSE,  
  verbose = TRUE,  
  ...  
)  
  
## S4 method for signature 'partition'  
kwic(  
  .Object,  
  query,  
  cqp = is.cqp,  
  left = getOption("polmineR.left"),  
  right = getOption("polmineR.right"),  
  s_attributes = getOption("polmineR.meta"),  
  p_attribute = "word",
```

```
    region = NULL,
    boundary = NULL,
    cpos = TRUE,
    stoplist = NULL,
    positivelist = NULL,
    regex = FALSE,
    verbose = TRUE,
    ...
)

## S4 method for signature 'subcorpus'
kwic(
  .Object,
  query,
  cqp = is.cqp,
  left = getOption("polmineR.left"),
  right = getOption("polmineR.right"),
  s_attributes = getOption("polmineR.meta"),
  p_attribute = "word",
  region = NULL,
  boundary = NULL,
  cpos = TRUE,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'corpus'
kwic(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  left = as.integer(getOption("polmineR.left")),
  right = as.integer(getOption("polmineR.right")),
  s_attributes = getOption("polmineR.meta"),
  p_attribute = "word",
  region = NULL,
  boundary = NULL,
  cpos = TRUE,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  verbose = TRUE,
  ...
)
```

```

## S4 method for signature 'character'
kwic(
  .Object,
  query,
  cqp = is.cqp,
  check = TRUE,
  left = as.integer(getOption("polmineR.left")),
  right = as.integer(getOption("polmineR.right")),
  s_attributes = getOption("polmineR.meta"),
  p_attribute = "word",
  region = NULL,
  boundary = NULL,
  cpos = TRUE,
  stoplist = NULL,
  positivelist = NULL,
  regex = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'remote_corpus'
kwic(.Object, ...)

## S4 method for signature 'remote_partition'
kwic(.Object, ...)

## S4 method for signature 'remote_subcorpus'
kwic(.Object, ...)

## S4 method for signature 'partition_bundle'
kwic(.Object, ..., verbose = FALSE)

## S4 method for signature 'subcorpus_bundle'
kwic(.Object, ...)

```

Arguments

<code>.Object</code>	A (length-one) character vector with the name of a CWB corpus, a partition or context object.
<code>...</code>	Further arguments, used to ensure backwards compatibility. If <code>.Object</code> is a <code>remote_corpus</code> or <code>remote_partition</code> object, the three dots (<code>...</code>) are used to pass arguments. Hence, it is necessary to state the names of all arguments to be passed explicitly.
<code>s_attributes</code>	Structural attributes (s-attributes) to include into output table as meta-information.
<code>cpos</code>	Logical, if TRUE, a <code>data.table</code> with the corpus positions (" <code>cpos</code> ") of the hits and their surrounding context will be assigned to the slot " <code>cpos</code> " of the <code>kwic</code> -object

	that is returned. Defaults to TRUE, as the availability of the <code>cpos-data.table</code> will often be a prerequisite for further operations on the <code>kwic</code> object. Omitting the table may however be useful to minimize memory consumption.
<code>verbose</code>	A logical value, whether to print messages.
<code>query</code>	A query, CQP-syntax can be used.
<code>cqp</code>	Either a logical value (TRUE if query is a CQP query), or a function to check whether query is a CQP query or not (defaults to auxiliary function <code>is.query</code>).
<code>left</code>	A single integer value defining the number of tokens to the left of the query match to include in the context. Advanced usage: (a) If <code>left</code> is a length-one character vector stating an s-attribute, the context will be expanded to the (left) boundary of the region where the match occurs. (b) If <code>left</code> is a named length-one integer vector, this value is the number regions of the structural attribute referred to by the vector's name to the left of the query match that are included in the context.
<code>right</code>	A single integer value, a length-one character vector or a named length-one integer value, with equivalent effects to argument <code>left</code> .
<code>region</code>	An s-attribute, given by a length-one character vector. The context of query matches will be expanded to the left and right boundary of the region where the match is located. If arguments <code>left</code> and <code>right</code> are > 1, the left and right boundaries of the respective number of regions will be identified.
<code>p_attribute</code>	The p-attribute, defaults to 'word'.
<code>boundary</code>	If provided, a length-one character vector stating an s-attribute that will be used to check the boundaries of the text.
<code>stoplist</code>	Terms or ids to prevent a concordance from occurring in results.
<code>positivelist</code>	Terms or ids required for a concordance to occur in results
<code>regex</code>	Logical, whether <code>stoplist/positivelist</code> is interpreted as regular expression.
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .

Details

The method works with a whole CWB corpus defined by a character vector, and can be applied on a `partition-` or a `context` object.

If `query` produces a lot of matches, the `DT::datatable()` function used to produce output in the Viewer pane of RStudio may issue a warning. Usually, this warning is harmless and can be ignored. Use `options("polmineR.warn.size" = FALSE)` for turning off this warning.

If a `positivelist` is supplied, only those concordances will be kept that have one of the terms from the `positivelist` occur in the context of the query match. Use argument `regex` if the `positivelist` should be interpreted as regular expressions. Tokens from the `positivelist` will be highlighted in the output table.

If a `negativelist` is supplied, concordances are removed if any of the tokens of the `negativelist` occurs in the context of the query match.

Applying the `kwic`-method on a `partition_bundle` or `subcorpus_bundle` will return a single `kwic` object that includes a column `'subcorpus_name'` with the name of the subcorpus (or `partition`) in the input object where the match for a concordance occurs.

Value

If there are no matches, or if all (initial) matches are dropped due to the application of a positivelist, a NULL is returned.

References

Baker, Paul (2006): *Using Corpora in Discourse Analysis*. London: continuum, pp. 71-93 (ch. 4).
 Jockers, Matthew L. (2014): *Text Analysis with R for Students of Literature*. Cham et al: Springer, pp. 73-87 (chs. 8 & 9).

See Also

The return value is a [kwic-class](#) object; the documentation for the class explains the standard generic methods applicable to [kwic-class](#) objects. It is possible to read the whole text where a query match occurs, see the [read-method](#). To highlight terms in the context of a query match, see the [highlight-method](#).

Examples

```
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

# basic usage
K <- kwic("GERMAPARLMINI", "Integration")
if (interactive()) show(K)
oil <- corpus("REUTERS") %>% kwic(query = "oil")
if (interactive()) show(oil)
oil <- corpus("REUTERS") %>%
  kwic(query = "oil") %>%
  highlight(yellow = "crude")
if (interactive()) show(oil)

# increase left and right context and display metadata
K <- kwic(
  "GERMAPARLMINI",
  "Integration", left = 20, right = 20,
  s_attributes = c("date", "speaker", "party")
)
if (interactive()) show(K)

# use CQP syntax for matching
K <- kwic(
  "GERMAPARLMINI",
  '"Integration" [] "(Menschen|Migrant.*|Personen)"', cqp = TRUE,
  left = 20, right = 20,
  s_attributes = c("date", "speaker", "party")
)
if (interactive()) show(K)

# check that boundary of region is not transgressed
K <- kwic(
```

```

    "GERMAPARLMINI",
    "'Sehr" "geehrte"', cqp = TRUE,
    left = 100, right = 100,
    boundary = "date"
  )
  if (interactive()) show(K)

# use positivelist and highlight matches in context
K <- kwic("GERMAPARLMINI", query = "Integration", positivelist = "[Ee]urop.*", regex = TRUE)
K <- highlight(K, yellow = "[Ee]urop.*", regex = TRUE)

# Apply kwic on partition_bundle/subcorpus_bundle
gparl_2009_11_10_speeches <- corpus("GERMAPARLMINI") %>%
  subset(date == "2009-11-10") %>%
  as.speeches(
    s_attribute_name = "speaker", s_attribute_date = "date",
    progress = FALSE, verbose = FALSE
  )
k <- kwic(gparl_2009_11_10_speeches, query = "Integration")

```

kwic-class

S4 kwic class

Description

S4 class for organizing information for kwic/concordance output. A set of standard generics (show, as.character, as.data.frame, length, sample, subset) as well as indexing is implemented to process kwic class objects (see 'Usage'). See section 'Details' for the enrich, view and knit_print methods.

Usage

```

## S4 method for signature 'kwic'
get_corpus(x)

## S4 method for signature 'kwic'
count(.Object, p_attribute = "word")

## S4 method for signature 'kwic'
as.DocumentTermMatrix(x, p_attribute, verbose = TRUE, ...)

## S4 method for signature 'kwic'
as.TermDocumentMatrix(x, p_attribute, verbose = TRUE, ...)

## S4 method for signature 'kwic'
show(object)

## S4 method for signature 'kwic'
knit_print(x, options = knitr::opts_chunk)

```

```

## S4 method for signature 'kwic'
as.character(x, fmt = "<i>%s</i>")

## S4 method for signature 'kwic,ANY,ANY,ANY'
x[i]

## S4 method for signature 'kwic'
subset(x, ...)

## S4 method for signature 'kwic'
as.data.frame(x)

## S4 method for signature 'kwic'
length(x)

## S4 method for signature 'kwic'
sample(x, size)

## S4 method for signature 'kwic_bundle'
merge(x)

## S4 method for signature 'kwic'
enrich(.Object, s_attributes = NULL, extra = NULL, table = FALSE, ...)

## S4 method for signature 'kwic'
format(
  x,
  node_color = "blue",
  align = TRUE,
  extra_color = "grey",
  lineview = getOption("polmineR.lineview")
)

## S4 method for signature 'kwic'
view(.Object)

```

Arguments

<code>x</code>	A kwic class object.
<code>.Object</code>	A kwic class object.
<code>p_attribute</code>	A length-one character vector supplying a p-attribute.
<code>verbose</code>	A logical value, whether to output debugging messages.
<code>...</code>	Used for backwards compatibility.
<code>object</code>	A kwic class object.
<code>options</code>	Chunk options.
<code>fmt</code>	A format string passed into <code>sprintf</code> to format the node of a KWIC display.

<code>i</code>	Single integer value, the kwic line for which the fulltext shall be inspected.
<code>size</code>	An integer, subset size for sampling.
<code>s_attributes</code>	Character vector of s-attributes with metainformation.
<code>extra</code>	An integer value, number of extra tokens to the left and to the right of the windows of tokens to the left and right of a query match that are decoded to be displayed in a kwic output to facilitate interpretation.
<code>table</code>	Logical, whether to turn <code>cpos</code> <code>data.table</code> into <code>data.table</code> in slot <code>stat</code> for output.
<code>node_color</code>	If not NULL, the html color of the node. If supplied, the node will be wrapped in respective html tags.
<code>align</code>	A logical value for preparing kwic output. If TRUE, whether the content of the columns 'left', 'node' and 'right' will be wrapped in html div elements that will align the output right, centered and left, respectively.
<code>extra_color</code>	If extra context has been generated using <code>enrich</code> , the html color of the additional output (defaults to 'grey').
<code>lineview</code>	A logical value, whether to concatenate left context, node and right context when preparing kwic output.

Details

Applying the `count`-method on a kwic object will return a count object with the evaluation of the left and right context of the match.

The `knit_print()` method will be called by knitr to render kwic objects as a `DataTable` `htmlwidget` when rendering a R Markdown document as html. It will usually be necessary to explicitly state `"render = knit_print"` in the chunk options. The option `polmineR::pageLength` controls the number of lines displayed in the resulting `htmlwidget`. Note that including `htmlwidgets` in html documents requires that `pandoc` is installed. To avoid an error, a formatted `data.table` is returned by `knit_print()` if `pandoc` is not available.

The `as.character`-method will return a list of character vectors, concatenating the columns "left", "node" and "right" of the `data.table` in the `stat`-slot of the input kwic-class object. Optionally, the node can be formatted using a format string that is passed into `sprintf`.

The `subset`-method will apply `subset` to the table in the slot `stat`, e.g. for filtering query results based on metadata (i.e. s-attributes) that need to be present.

The `enrich` method is used to generate the actual output for the kwic method. If param `table` is TRUE, corpus positions will be turned into a `data.frame` with the concordance lines. If param `s_attributes` is a character vector with s-attributes, the respective s-attributes will be added as columns to the table with concordance lines.

The `format`-method will return a `data.table` that can serve as input for rendering a `htmlwidget`, for instance using `DT::datatable` or `rhandsontable::rhandsontable`. It will include html tags, so ensure that the rendering engine does not obfuscate the html.

Slots

`metadata` A character vector with s-attributes of the metadata that are to be displayed.

`p_attribute` The p-attribute for which the context has been generated.

`left` An integer value, words to the left of the query match.

`right` An integer value, words to the right of the query match.

`corpus` Length-one character vector, the CWB corpus.

`cpos` A data.table with the columns "match_id", "cpos", "position", "word_id", "word" and "direction".

`stat` A data.table, a table with columns "left", "node", "right", and metadata, if the object has been enriched.

`encoding` A length-one character vector with the encoding of the corpus.

`name` A length-one character vector naming the object.

`annotation_cols` A character vector designating the columns of the data.table in the slot table that are annotations.

See Also

The constructor for generating kwic objects is the `kwic` method.

Examples

```
use("polmineR")
K <- kwic("GERMAPARLMINI", "Integration")
get_corpus(K)
length(K)
K_min <- K[1]
K_min <- K[1:5]

# using kwic_bundle class
queries <- c("oil", "prices", "barrel")
li <- lapply(queries, function(q) kwic("REUTERS", query = q))
kb <- as.bundle(li)

# use count-method on kwic object
coi <- kwic("REUTERS", query = "oil") %>%
  count(p_attribute = "word")

# features vs cooccurrences-method (identical results)
ref <- count("REUTERS", p_attribute = "word") %>%
  subset(word != "oil")
slot(ref, "size") <- slot(ref, "size") - count("REUTERS", "oil")[["count"]]
y_features <- features(coi, ref, method = "ll", included = TRUE)
y_cooc <- cooccurrences("REUTERS", query = "oil")

# extract node and left and right context as character vectors
oil <- kwic("REUTERS", query = "oil")
as.character(oil, fmt = NULL)
as.character(oil) # node wrapped into <i> tag by default
as.character(oil, fmt = "<b>%s</b>")

# subsetting kwic objects
oil <- corpus("REUTERS") %>%
```

```

kwic(query = "oil") %>%
  subset(grepl("prices", right))
saudi_arabia <- corpus("REUTERS") %>%
  kwic(query = "Arabia") %>%
  subset(grepl("Saudi", left))
int_spd <- corpus("GERMAPARLMINI") %>%
  kwic(query = "Integration") %>%
  enrich(s_attribute = "party") %>%
  subset(grepl("SPD", party))

# turn kwic object into data.frame with html tags
int <- corpus("GERMAPARLMINI") %>%
  kwic(query = "Integration")

as.data.frame(int) # Without further metadata

enrich(int, s_attributes = c("date", "speaker", "party")) %>%
  as.data.frame()

# merge bundle of kwic objects into one kwic
reuters <- corpus("REUTERS")
queries <- c("'Saudi" "Arabia"', "oil", "'barrel.*'")
comb <- lapply(queries, function(qu) kwic(reuters, query = qu)) %>%
  as.bundle() %>%
  merge()

# enrich kwic object
i <- corpus("GERMAPARLMINI") %>%
  kwic(query = "Integration") %>%
  enrich(s_attributes = c("date", "speaker", "party"))

```

Description

Apply the log-likelihood statistic to detect cooccurrences or keywords.

Usage

```

ll(.Object, ...)

## S4 method for signature 'features'
ll(.Object)

## S4 method for signature 'context'
ll(.Object)

## S4 method for signature 'cooccurrences'

```

```
ll(.Object)

## S4 method for signature 'Cooccurrences'
ll(.Object, verbose = TRUE)
```

Arguments

.Object An object of class cooccurrence, context, or features.
 ... Further arguments (such as verbose).
 verbose Logical, whether to output messages.

Details

The log-likelihood test to detect cooccurrences is a standard approach to find collocations (Dunning 1993, Evert 2005, 2009).

(a) The basis for computing for the log-likelihood statistic is a contingency table of observations, which is prepared for every single token in the corpus. It reports counts for a token to inspect and all other tokens in a corpus of interest (coi) and a reference corpus (ref):

	coi	ref	TOTAL
count token	o_{11}	o_{12}	r_1
other tokens	o_{21}	o_{22}	r_2
TOTAL	c_1	c_2	N

(b) Based on the contingency table(s) with observed counts, expected values are calculated for each cell, as the product of the column and margin sums, divided by the overall number of tokens (see example).

(c) The standard formula for calculating the log-likelihood test is as follows.

$$G^2 = 2 \sum O_{ij} \log\left(\frac{O_{ij}}{E_{ij}}\right)$$

Note: Before polmineR v0.7.11, a simplification of the formula was used (Rayson/Garside 2000), which omits the third and fourth term of the previous formula:

$$ll = 2(o_{11} \log\left(\frac{o_{11}}{E_{11}}\right) + o_{12} \log\left(\frac{o_{12}}{E_{12}}\right))$$

There is a (small) gain of computational efficiency using this simplified formula and the result is almost identical with the standard formula; see however the critical discussion of Ulrike Tabbert (2015: 84ff).

The implementation in the ll-method uses a vectorized approach of the computation, which is substantially faster than iterating the rows of a table, generating individual contingency tables etc. As using the standard formula is not significantly slower than relying on the simplified formula, polmineR has moved to the standard computation.

An inherent difficulty of the log likelihood statistic is that it is not possible to compute the statistical test value if the number of observed counts in the reference corpus is 0, i.e. if a term only occurs exclusively in the neighborhood of a node word. When filtering out rare words from the result table, respective NA values will usually disappear.

References

- Dunning, Ted (1993): Accurate Methods for the Statistics of Surprise and Coincidence. *Computational Linguistics*, Vol. 19, No. 1, pp. 61-74.
- Rayson, Paul; Garside, Roger (2000): Comparing Corpora using Frequency Profiling. *The Workshop on Comparing Corpora*. <https://aclanthology.org/W00-0901/>.
- Evert, Stefan (2005): *The Statistics of Word Cooccurrences. Word Pairs and Collocations*. URN urn:nbn:de:bsz:93-opus-23714. <https://elib.uni-stuttgart.de/bitstream/11682/2573/1/Evert2005phd.pdf>
- Evert, Stefan (2009). Corpora and Collocations. In: A. Ludeling and M. Kyto (eds.), *Corpus Linguistics. An International Handbook*. Mouton de Gruyter, Berlin, pp. 1212-1248 (ch. 58).
- Tabbert, Ulrike (2015): *Crime and Corpus. The Linguistic Representation of Crime in the Press*. Amsterdam: Benjamins.

See Also

Other statistical methods: [chisquare\(\)](#), [pmi\(\)](#), [t_test\(\)](#)

Examples

```
# use ll-method explicitly
oil <- cooccurrences("REUTERS", query = "oil", method = NULL)
oil <- ll(oil)
oil_min <- subset(oil, count_coi >= 3)
if (interactive()) View(format(oil_min))
summary(oil)

# use ll-method on 'Cooccurrences'-object
## Not run:
R <- Cooccurrences("REUTERS", left = 5L, right = 5L, p_attribute = "word")
ll(R)
decode(R)
summary(R)

## End(Not run)

# use log likelihood test for feature extraction
x <- partition(
  "GERMAPARLMINI", speaker = "Merkel",
  interjection = "speech", regex = TRUE,
  p_attribute = "word"
)
f <- features(x, y = "GERMAPARLMINI", included = TRUE, method = "ll")
f <- features(x, y = "GERMAPARLMINI", included = TRUE, method = NULL)
f <- ll(f)
summary(f)

## Not run:

# A sample do-it-yourself calculation for log-likelihood:
# Compute ll-value for query "oil", and "prices"
```

```

oil <- context("REUTERS", query = "oil", left = 5, right = 5)

# (a) prepare matrix with observed values
o <- matrix(data = rep(NA, 4), ncol = 2)
o[1,1] <- as(oil, "data.table")[word == "prices"][["count_coi"]]
o[1,2] <- count("REUTERS", query = "prices")[["count"]] - o[1,1]
o[2,1] <- size(oil)[["coi"]] - o[1,1]
o[2,2] <- size(oil)[["ref"]] - o[1,2]

# (b) prepare matrix with expected values, calculate margin sums first
r <- rowSums(o)
c <- colSums(o)
N <- sum(o)

e <- matrix(data = rep(NA, 4), ncol = 2) # matrix with expected values
e[1,1] <- r[1] * (c[1] / N)
e[1,2] <- r[1] * (c[2] / N)
e[2,1] <- r[2] * (c[1] / N)
e[2,2] <- r[2] * (c[2] / N)

# (c) compute log-likelihood value
ll_value <- 2 * (
  o[1,1] * log(o[1,1] / e[1,1]) +
  o[1,2] * log(o[1,2] / e[1,2]) +
  o[2,1] * log(o[2,1] / e[2,1]) +
  o[2,2] * log(o[2,2] / e[2,2])
)

df <- as.data.frame(cooccurrences("REUTERS", query = "oil"))
subset(df, word == "prices")[["ll"]]

## End(Not run)

```

means

calculate means

Description

calculate means

Usage

```
means(.Object, ...)
```

```
## S4 method for signature 'DocumentTermMatrix'
means(.Object, dim = 1)
```

Arguments

.Object	object to work on
...	further parameters @exportMethod means
dim	numeric, 1 or 2 whether to work on rows or columns

ngrams

Get N-Grams

Description

Count n-grams, either of words, or of characters.

Usage

```
ngrams(.Object, ...)
```

```
## S4 method for signature 'partition'
```

```
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)
```

```
## S4 method for signature 'character'
```

```
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)
```

```
## S4 method for signature 'partition'
```

```
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)
```

```
    ...
  )

## S4 method for signature 'subcorpus'
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)

## S4 method for signature 'character'
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)

## S4 method for signature 'data.table'
ngrams(.Object, n = 2L, p_attribute = "word")

## S4 method for signature 'corpus'
ngrams(
  .Object,
  n = 2,
  p_attribute = "word",
  char = NULL,
  progress = FALSE,
  mc = 1L,
  ...
)

## S4 method for signature 'list'
ngrams(
  .Object,
  n = 2,
  char = NULL,
  mc = FALSE,
  verbose = FALSE,
  progress = FALSE,
  ...
)
```

```

)

## S4 method for signature 'partition_bundle'
ngrams(
  .Object,
  n = 2,
  char = NULL,
  vocab = NULL,
  p_attribute = "word",
  mc = FALSE,
  verbose = FALSE,
  progress = FALSE,
  ...
)

```

Arguments

<code>.Object</code>	object of class <code>partition</code>
<code>...</code>	Further arguments.
<code>n</code>	Number of tokens (if <code>char</code> is <code>NULL</code>) or characters otherwise.
<code>p_attribute</code>	the p-attribute to use (can be > 1)
<code>char</code>	If <code>NULL</code> , tokens will be counted, else characters, keeping only those provided by a character vector
<code>progress</code>	A logical value.
<code>mc</code>	A logical value, whether to use multicore, passed into call to <code>blapply()</code> .
<code>verbose</code>	A length-one logical value, whether to show messages.
<code>vocab</code>	A character vector with an alternative vocabulary to the one stored on disk.

Examples

```

use("polminer")
P <- partition("GERMAPARLMINI", date = "2009-10-27")
ngrm <- ngrams(P, n = 2, p_attribute = "word", char = NULL)

# a more complex scenario: get most frequent ADJA/NN-combinations
ngrm <- ngrams(P, n = 2, p_attribute = c("word", "pos"), char = NULL)
ngrm2 <- subset(
  ngrm,
  ngrm[["1_pos"]] == "ADJA" & ngrm[["2_pos"]] == "NN"
)
ngrm2@stat[, "1_pos" := NULL][, "2_pos" := NULL]
ngrm3 <- sort(ngrm2, by = "count")
head(ngrm3)
use(pkg = "RcppCWB", corpus = "REUTERS")
dt <- decode("REUTERS", p_attribute = "word", s_attribute = character(), to = "data.table")
y <- ngrams(dt, n = 3L, p_attribute = "word")

```

ngrams_class	<i>Ngrams class.</i>
--------------	----------------------

Description

Ngrams class.

noise	<i>detect noise</i>
-------	---------------------

Description

detect noise

Usage

```
noise(.Object, ...)

## S4 method for signature 'DocumentTermMatrix'
noise(
  .Object,
  minTotal = 2,
  minTfIdfMean = 0.005,
  sparse = 0.995,
  stopwordsLanguage = "german",
  minNchar = 2L,
  specialChars = getOption("polmineR.specialChars"),
  numbers = "[0-9\\.\\.,]+",
  verbose = TRUE
)

## S4 method for signature 'TermDocumentMatrix'
noise(.Object, ...)

## S4 method for signature 'character'
noise(
  .Object,
  stopwordsLanguage = "german",
  minNchar = 2,
  specialChars = getOption("polmineR.specialChars"),
  numbers = "[0-9\\.\\.,]+",
  verbose = TRUE
)

## S4 method for signature 'textstat'
noise(.Object, p_attribute, ...)
```

Arguments

.Object	An object of class DocumentTermMatrix.
...	further parameters
minTotal	minimum colsum (for DocumentTermMatrix) to qualify a term as non-noise
minTfIdfMean	minimum mean value for tf-idf to qualify a term as non-noise
sparse	Will be passed into tm::removeSparseTerms().
stopwordsLanguage	e.g. "german", to get stopwords defined in the tm package.
minNchar	Minimum number of characters to qualify a term as non-noise.
specialChars	special characters to drop
numbers	regex, to drop numbers
verbose	logical
p_attribute	relevant if applied to a textstat object

Value

a list

ocpu_exec

Execute code on OpenCPU server

Description

ocpu_exec will execute a function/method fn on an OpenCPU server (specified by argument server), using three dots (...) to pass arguments. It is the worker of methods defined for remote_corpus, remote_subcorpus and remote_partition objects.

Usage

```
ocpu_exec(fn, corpus, server, restricted = FALSE, do.call = FALSE, ...)
```

Arguments

fn	Name of the function/method to execute on remote server (length-one character vector).
corpus	A length-one character vector, the id of the corpus to be queried.
server	The IP/URL of the remote OpenCPU server.
restricted	A logical value, whether credentials are required to access the data.
do.call	Logical, if TRUE, the function fn is passed into a call of do.call, which offers some flexibility.
...	Arguments passed into the method/function call.

Examples

```
## Not run:
# Get polmineR version installed on remote server
ocpu_exec(
  fn = "packageVersion",
  server = Sys.getenv("OPENCPU_SERVER"),
  do.call = TRUE,
  pkg = "polmineR"
)

## End(Not run)
```

partition

Initialize a partition.

Description

Create a subcorpus and keep it in an object of the partition class. If defined, counts are performed for the p-attribute defined by the parameter p_attribute.

Usage

```
partition(.Object, ...)

## S4 method for signature 'corpus'
partition(
  .Object,
  def = NULL,
  name = "",
  encoding = NULL,
  p_attribute = NULL,
  regex = FALSE,
  xml = slot(.Object, "xml"),
  decode = TRUE,
  type = get_type(.Object),
  mc = FALSE,
  verbose = TRUE,
  ...
)

## S4 method for signature 'character'
partition(
  .Object,
  def = NULL,
  name = "",
  encoding = NULL,
  p_attribute = NULL,
```

```

    regex = FALSE,
    decode = TRUE,
    type = get_type(.Object),
    mc = FALSE,
    verbose = TRUE,
    ...
)

## S4 method for signature 'environment'
partition(.Object, slots = c("name", "corpus", "size", "p_attribute"))

## S4 method for signature 'partition'
partition(
  .Object,
  def = NULL,
  name = "",
  regex = FALSE,
  p_attribute = NULL,
  decode = TRUE,
  xml = NULL,
  verbose = TRUE,
  mc = FALSE,
  ...
)

## S4 method for signature 'context'
partition(.Object, node = TRUE)

## S4 method for signature 'remote_corpus'
partition(.Object, ...)

## S4 method for signature 'remote_partition'
partition(.Object, ...)

```

Arguments

<code>.Object</code>	A length-one character-vector, the CWB corpus to be used.
<code>...</code>	Arguments to define partition (see examples). If <code>.Object</code> is a <code>remote_corpus</code> or <code>remote_partition</code> object, the three dots (<code>...</code>) are used to pass arguments. Hence, it is necessary to state the names of all arguments to be passed explicitly.
<code>def</code>	A named list of character vectors of s-attribute values, the names are the s-attributes (see details and examples)
<code>name</code>	A name for the new partition object, defaults to "".
<code>encoding</code>	The encoding of the corpus (typically "LATIN1 or "(UTF-8)), if NULL, the encoding provided in the registry file of the corpus (charset="...") will be used.
<code>p_attribute</code>	The p-attribute(s) for which a count is performed.
<code>regex</code>	A logical value (defaults to FALSE).

<code>xml</code>	Either 'flat' (default) or 'nested'.
<code>decode</code>	Logical, whether to turn token ids to strings (set <code>FALSE</code> to minimize object size / memory consumption) in <code>data.table</code> with counts.
<code>type</code>	A length-one character vector specifying the type of corpus / partition (e.g. "plpr")
<code>mc</code>	Whether to use multicore (for counting terms).
<code>verbose</code>	Logical, whether to be verbose.
<code>slots</code>	Object slots that will be reported columns of <code>data.frame</code> summarizing partition objects in environment.
<code>node</code>	A logical value, whether to include the node (i.e. query matches) in the region matrix generated when creating a partition from a context-object.

Details

The function sets up a partition object based on s-attribute values. The s-attributes defining the partition can be passed in as a list, e.g. `list(interjection="speech", year = "2013")`, or directly (see examples).

The s-attribute values defining the partition may use regular expressions. To use regular expressions, set the parameter `regex` to `TRUE`. Regular expressions are passed into `grep`, i.e. the regex syntax used in R needs to be used (double backslashes etc.). If `regex` is `FALSE`, the length of the character vectors can be > 1 , matching s-attributes are identified with the operator `'%in%'`.

The XML imported into the CWB may be "flat" or "nested". This needs to be indicated with the parameter `xml` (default is "flat"). If you generate a partition based on a flat XML structure, some performance gain may be achieved when ordering the s-attributes with decreasingly restrictive conditions. If you have a nested XML, it is mandatory that the order of the s-attributes provided reflects the hierarchy of the XML: The top-level elements need to be positioned at the beginning of the list with the s-attributes, the the most restrictive elements at the end.

If `p_attribute` is not `NULL`, a count of tokens in the corpus will be performed and kept in the `stat`-slot of the partition-object. The length of the `p_attribute` character vector may be 1 or more. If two or more p-attributes are provided, The occurrence of combinations will be counted. A typical scenario is to combine the p-attributes "word" or "lemma" and "pos".

If `.Object` is a length-one character vector, a subcorpus/partition for the corpus defined by `.Object` is generated.

If `.Object` is an environment (typically `.GlobalEnv`), the partition objects present in the environment are listed.

If `.Object` is a partition object, a subcorpus of the subcorpus is generated.

Value

An object of the S4 class `partition`.

Author(s)

Andreas Blaette

See Also

To learn about the methods available for objects of the class `partition`, see [partition_class](#),

Examples

```
use("polmineR")
spd <- partition("GERMAPARLMINI", party = "SPD", interjection = "speech")
kauder <- partition("GERMAPARLMINI", speaker = "Volker Kauder", p_attribute = "word")
merkel <- partition("GERMAPARLMINI", speaker = ".*Merkel", p_attribute = "word", regex = TRUE)
s_attributes(merkel, "date")
s_attributes(merkel, "speaker")
merkel <- partition(
  "GERMAPARLMINI", speaker = "Angela Dorothea Merkel",
  date = "2009-11-10", interjection = "speech", p_attribute = "word"
)
merkel <- subset(merkel, !word %in% punctuation)
merkel <- subset(merkel, !word %in% tm::stopwords("de"))

# a certain defined time segment
days <- seq(
  from = as.Date("2009-10-28"),
  to = as.Date("2009-11-11"),
  by = "1 day"
)
period <- partition("GERMAPARLMINI", date = days)
```

partition_bundle	<i>Generate bundle of partitions.</i>
------------------	---------------------------------------

Description

Use `partition_bundle` to create a `partition_bundle` object, which combines a set of `partition` objects.

Usage

```
partition_bundle(.Object, ...)

## S4 method for signature 'partition'
partition_bundle(
  .Object,
  s_attribute,
  values = NULL,
  prefix = "",
  mc = getOption("polmineR.mc"),
  verbose = TRUE,
  progress = FALSE,
  type = get_type(.Object),
```

```
    ...
)

## S4 method for signature 'corpus'
partition_bundle(
  .Object,
  s_attribute,
  values = NULL,
  prefix = "",
  mc = getOption("polmineR.mc"),
  verbose = TRUE,
  progress = FALSE,
  xml = "flat",
  type = get_type(.Object),
  ...
)

## S4 method for signature 'character'
partition_bundle(
  .Object,
  s_attribute,
  values = NULL,
  prefix = "",
  mc = getOption("polmineR.mc"),
  verbose = TRUE,
  progress = FALSE,
  xml = "flat",
  type = get_type(.Object),
  ...
)

## S4 method for signature 'context'
partition_bundle(
  .Object,
  node = TRUE,
  verbose = TRUE,
  progress = TRUE,
  mc = 1L
)

## S4 method for signature 'partition_bundle'
partition_bundle(
  .Object,
  s_attribute,
  prefix = character(),
  progress = TRUE,
  mc = getOption("polmineR.mc")
)
```

Arguments

.Object	A partition, a length-one character vector supplying a CWB corpus, or a partition_bundle
...	parameters to be passed into partition-method (see respective documentation)
s_attribute	The s-attribute to vary.
values	Values the s-attribute provided shall assume.
prefix	A character vector that will be attached as a prefix to partition names.
mc	Logical, whether to use multicore parallelization.
verbose	Logical, whether to provide progress information.
progress	Logical, whether to show progress bar.
type	The type of partition to generate.
xml	A logical value.
node	A logical value, whether to include the node (i.e. query matches) in the region matrix generated when creating a partition from a context-object.

Details

Applying the partition_bundle-method to a partition_bundle-object will iterate through the partition objects in the object-slot in the partition_bundle, and apply partition_bundle on each partition, splitting it up by the s-attribute provided by the argument s_attribute. The return value is a partition_bundle, the names of which will be the names of the incoming partition_bundle concatenated with the s-attribute values used for splitting. The argument prefix can be used to achieve a more descriptive name.

Value

S4 class partition_bundle, with list of partition objects in slot 'objects'

Author(s)

Andreas Blaette

See Also

[partition](#) and [bundle](#)

Examples

```
## Not run:
use("polmineR")
bt2009 <- partition("GERMAPARLMINI", date = "2009-.*", regex = TRUE)
pb <- partition_bundle(bt2009, s_attribute = "date", progress = TRUE)
pb <- enrich(pb, p_attribute = "word")
dtm <- as.DocumentTermMatrix(pb, col = "count")
summary(pb)
pb <- partition_bundle("GERMAPARLMINI", s_attribute = "date")
```

```
## End(Not run)
## Not run:
use("RcppCWB", corpus = "REUTERS")
pb <- corpus("REUTERS") %>%
  context(query = "oil", p_attribute = "word") %>%
  partition_bundle(node = FALSE, verbose = TRUE)

## End(Not run)
# split up objects in partition_bundle by using partition_bundle-method
use("polmineR")
pb <- partition_bundle("GERMAPARLMINI", s_attribute = "date")
pb2 <- partition_bundle(pb, s_attribute = "speaker", progress = FALSE)

summary(pb2)
```

partition_bundle-class

Bundle of partitions (partition_bundle class).

Description

Class and methods to manage bundles of partitions.

Usage

```
## S4 method for signature 'partition_bundle'
show(object)

## S4 method for signature 'partition_bundle'
summary(object, progress = FALSE)

## S4 method for signature 'partition_bundle'
merge(x, name = "", verbose = FALSE)

## S4 method for signature 'partition_bundle'
barplot(height, ...)

## S4 method for signature 'list'
as.partition_bundle(.Object, ...)

## S4 method for signature 'environment'
partition_bundle(.Object)

## S4 method for signature 'partition_bundle'
enrich(.Object, p_attribute, decode = TRUE, verbose = FALSE)

## S4 method for signature 'subcorpus_bundle'
enrich(.Object, p_attribute, decode = TRUE, verbose = FALSE)
```

```
flatten(object)
```

Arguments

object	A partition_bundle object.
progress	A logical value, whether to show progress bar.
x	A partition_bundle object.
name	the name for the new partition
verbose	A logical value, whether to show progress messages.
height	height
...	further parameters
.Object	A partition_bundle object.
p_attribute	A character vector with p-attribute(s) for counting.
decode	A logical value, whether to turn token ids into decoded strings.

Details

The merge-method aggregates several partitions into one partition. The prerequisite for this function to work properly is that there are no overlaps of the different partitions that are to be summarized. Encodings and the root node need to be identical, too.

The enrich() method will fill the slot stat of the partition objects within the bundle with a count for the designated p-attributes. If .Object is a subcorpus_bundle, the output class will be a partition_bundle.

Value

An object of the class 'partition'. See partition for the details on the class.
a partition_bundle object

Slots

objects Object of class list the partitions making up the bundle
 corpus Object of class character the CWB corpus the partition is based on
 s_attributes_fixed Object of class list fixed s-attributes
 encoding Object of class character encoding of the corpus
 explanation Object of class character an explanation of the partition
 xml Object of class character whether the xml is flat or nested
 call Object of class character the call that generated the partition_bundle

Author(s)

Andreas Blaette

Examples

```
# merge partition_bundle into one partition
gpar1 <- corpus("GERMAPARLMINI") %>%
  split(s_attribute = "date") %>%
  merge()
use(pkg = "RcppCWB", corpus = "REUTERS")

pb <- partition_bundle("REUTERS", s_attribute = "id")
barplot(pb, las = 2)

sc <- corpus("GERMAPARLMINI") %>%
  subset(date == "2009-11-10") %>%
  split(s_attribute = "speaker") %>%
  barplot(las = 2)
```

partition_class *Partition class and methods.*

Description

The partition class is used to manage subcorpora. It is an S4 class, and a set of methods is defined for the class. The class inherits from the classes count and textstat.

Usage

```
## S4 method for signature 'partition'
p_attributes(.Object, p_attribute = NULL, decode = TRUE)

## S4 method for signature 'subcorpus'
p_attributes(.Object, p_attribute = NULL, decode = TRUE)

is.partition(x)

## S4 method for signature 'partition'
enrich(
  .Object,
  p_attribute = NULL,
  decode = TRUE,
  verbose = TRUE,
  mc = FALSE,
  ...
)

## S4 method for signature 'partition'
as.regions(x)

## S4 method for signature 'partition'
split(x, gap, ...)
```

Arguments

.Object	A partition object.
p_attribute	a p-attribute (for enriching) / performing count.
decode	logical value, whether to decode token ids into strings when performing count
x	A partition object.
verbose	logical value, whether to output messages
mc	logical or, if numeric, providing the number of cores
...	further parameters passed into count when calling enrich, and ...
gap	An integer value specifying the minimum gap between regions for performing the split.

Details

As partition objects inherit from count and textstat class, methods available are view to inspect the table in the stat slot, name and name<- to retrieve/set the name of an object, and more.

The is.partition function returns a logical value whether x is a partition, or not.

The enrich-method will add a count of tokens defined by argument p_attribute to slot stat of the partition object.

The split()-method will split a partition object into a partition_bundle if gap between strucs exceeds a minimum number of tokens specified by gap. Relevant to split up a plenary protocol into speeches. Note: To speed things up, the returned partitions will not include frequency lists. The lists can be prepared by applying enrich on the partition_bundle object that is returned.

Slots

name	A name to identify the object (character vector with length 1); useful when multiple partition objects are combined to a partition_bundle.
corpus	The CWB indexed corpus the partition is derived from (character vector with length 1).
encoding	Encoding of the corpus (character vector with length 1).
s_attributes	A named list with the s-attributes specifying the partition.
explanation	Object of class character, an explanation of the partition.
cpos	A matrix with left and right corpus positions defining regions (two columns).
annotations	Object of class list.
size	Total size of the partition (integer vector, length 1).
stat	An (optional) data.table with counts. If present, speeds up computation of cooccurrences, as count is already present.
metadata	Object of class data.frame, metadata information.
strucs	Object of class integer, the strucs defining the partition.
p_attribute	Object of class character indicating the p_attribute of the count in slot stat.
xml	Object of class character, whether the xml is flat or nested.
s_attribute_strucs	Object of class character the base node
key	Experimental, an s-attribute that is used as a key.
call	Object of class character the call that generated the partition

Author(s)

Andreas Blaette

See Also

The partition-class inherits from the [textstat-class](#), see respective documentation to learn more.

Examples

```
p <- partition(
  "GERMAPARLMINI",
  date = "2009-11-11",
  speaker = "Norbert Lammert"
)
name(p) <- "Norbert Lammert"
pb <- split(p, gap = 500L)
summary(pb)
```

partition_to_string *Decode as String.*

Description

Decode as String.

Examples

```
corpus("REUTERS") %>%
  subset(id == "127") %>%
  as("String")
```

phrases-class *Manage and use phrases*

Description

Class, methods and functionality for processing phrases (lexical units, lexical items, multi-word expressions) beyond the token level. The envisaged workflow at this stage is to detect phrases using the ngrams-method and to generate a phrases class object from the ngrams object using the as.phrases method. This object can be passed into a call of count, see examples. Further methods and functions documented here are used internally, but may be useful.

Usage

```

## S4 method for signature 'ngrams'
as.phrases(.Object)

## S4 method for signature 'matrix'
as.phrases(.Object, corpus, enc = encoding(corpus))

## S4 method for signature 'phrases'
as.character(x, p_attribute)

concatenate_phrases(dt, phrases, col)

```

Arguments

<code>.Object</code>	Input object, either a <code>ngrams</code> or a <code>matrix</code> object.
<code>corpus</code>	A length-one character vector, the corpus ID of the corpus from which regions / the <code>data.table</code> representing a decoded corpus is derived.
<code>enc</code>	Encoding of the corpus.
<code>x</code>	A <code>phrases</code> class object.
<code>p_attribute</code>	The positional attribute (p-attribute) to decode.
<code>dt</code>	A <code>data.table</code> .
<code>phrases</code>	A <code>phrases</code> class object.
<code>col</code>	If <code>.Object</code> is a <code>data.table</code> , the column to concatenate.

Details

The `phrases` considers a phrase as sequence as tokens that can be defined by region, i.e. a left and a right corpus position. This information is kept in a region matrix in the slot "cpos" of the `phrases` class. The `phrases` class inherits from the `regions` class (which inherits from the `and` and the `corpus` class), without adding further slots.

If `.Object` is an object of class `ngrams`, the `as.phrases()`-method will interpret the `ngrams` as CQP queries, look up the matching corpus positions and return an `phrases` object.

If `.Object` is a `matrix`, the `as.phrases()`-method will initialize a `phrases` object. The corpus and the encoding of the corpus will be assigned to the object.

Applying the `as.character`-method on a `phrases` object will return the decoded regions, concatenated using an underscore as separator.

The `concatenate_phrases` function takes a `data.table` (argument `dt`) as input and concatenates phrases in successive rows into a phrase.

See Also

Other classes to manage corpora: [corpus-class](#), [ranges-class](#), [regions](#), [subcorpus](#)

Examples

```

## Not run:
# Workflow to create document-term-matrix with phrases

obs <- corpus("GERMAPARLMINI") %>%
  count(p_attribute = "word")

phrases <- corpus("GERMAPARLMINI") %>%
  ngrams(n = 2L, p_attribute = "word") %>%
  pmi(observed = obs) %>%
  subset(ngram_count > 5L) %>%
  subset(1:100) %>%
  as.phrases()

dtm <- corpus("GERMAPARLMINI") %>%
  as.speeches(s_attribute_name = "speaker", s_attribute_date = "date", progress = TRUE) %>%
  count(phrases = phrases, p_attribute = "word", progress = TRUE, verbose = TRUE) %>%
  as.DocumentTermMatrix(col = "count", verbose = FALSE)

grep("erneuerbaren_Energien", colnames(dtm))
grep("verpasste_Chancen", colnames(dtm))

## End(Not run)
## Not run:
use(pkg = "RcppCWB", corpus = "REUTERS")

# Derive phrases object from an ngrams object

reuters_phrases <- ngrams("REUTERS", p_attribute = "word", n = 2L) %>%
  pmi(observed = count("REUTERS", p_attribute = "word")) %>%
  subset(ngram_count >= 5L) %>%
  subset(1:25) %>%
  as.phrases()

phr <- as.character(reuters_phrases, p_attribute = "word")

## End(Not run)
# Derive phrases from explicitly stated CQP queries

## Not run:
cqp_phrase_queries <- c(
  "'oil" "revenue";',
  "'Sheikh" "Aziz";',
  "'Abdul" "Aziz";',
  "'Saudi" "Arabia";',
  "'oil" "markets";'
)
reuters_phrases <- cpos("REUTERS", cqp_phrase_queries, p_attribute = "word") %>%
  as.phrases(corpus = "REUTERS", enc = "latin1")

## End(Not run)

```

```

# Use the concatenate_phrases() function on a data.table

## Not run:
#' lexical_units_cqp <- c(
  "'Deutsche.*" "Bundestag.*";',
  "'sozial.*" "Gerechtigkeit";',
  "'Ausschuss" "f.r" "Arbeit" "und" "Soziales";',
  "'soziale.*" "Marktwirtschaft";',
  "'freiheitliche.*" "Grundordnung";'
)

phr <- cpos("GERMAPARLMINI", query = lexical_units_cqp, cqp = TRUE) %>%
  as.phrases(corpus = "GERMAPARLMINI", enc = "word")

dt <- corpus("GERMAPARLMINI") %>%
  decode(p_attribute = "word", s_attribute = character(), to = "data.table") %>%
  concatenate_phrases(phrases = phr, col = "word")

dt[word == "Deutschen_Bundestag"]
dt[word == "soziale_Marktwirtschaft"]

## End(Not run)

```

pmi

*Calculate Pointwise Mutual Information (PMI).***Description**

Calculate Pointwise Mutual Information as an information-theoretic approach to find collocations.

Usage

```

pmi(.Object, ...)

## S4 method for signature 'context'
pmi(.Object)

## S4 method for signature 'Cooccurrences'
pmi(.Object)

## S4 method for signature 'ngrams'
pmi(.Object, observed, p_attribute = p_attributes(.Object)[1])

```

Arguments

.Object	An object.
...	Arguments methods may require.

observed	A count-object with the numbers of the observed occurrences of the tokens in the input ngrams object.
p_attribute	The positional attribute which shall be considered. Relevant only if ngrams have been calculated for more than one p-attribute.

Details

Pointwise mutual information (PMI) is calculated as follows (see Manning/Schuetze 1999):

$$I(x, y) = \log \frac{p(x, y)}{p(x)p(y)}$$

The formula is based on maximum likelihood estimates: When we know the number of observations for token x , o_x , the number of observations for token y , o_y and the size of the corpus N , the probabilities for the tokens x and y , and for the co-occurrence of x and y are as follows:

$$p(x) = \frac{o_x}{N}$$

$$p(y) = \frac{o_y}{N}$$

The term $p(x,y)$ is the number of observed co-occurrences of x and y .

Note that the computation uses log base 2, not the natural logarithm you find in examples (e.g. https://en.wikipedia.org/wiki/Pointwise_mutual_information).

References

Manning, Christopher D.; Schuetze, Hinrich (1999): *Foundations of Statistical Natural Language Processing*. MIT Press: Cambridge, Mass., pp. 178-183.

See Also

Other statistical methods: `chisquare()`, `ll()`, `t_test()`

Examples

```
y <- cooccurrences("REUTERS", query = "oil", method = "pmi")
N <- size(y)[["partition"]]
I <- log2((y[["count_coi"]]/N) / ((count(y) / N) * (y[["count_partition"]]/N)))
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

dt <- decode(
  "REUTERS",
  p_attribute = "word",
  s_attribute = character(),
  to = "data.table",
  verbose = FALSE
)
n <- ngrams(dt, n = 2L, p_attribute = "word")
obs <- count("REUTERS", p_attribute = "word")
phrases <- pmi(n, observed = obs)
```

polmineR-defunct *Defunct functionality*

Description

Methods and functions not in use any more or that have been superseded by renamed functions.

Usage

`mail(...)`

`browse(...)`

Arguments

... Any arguments that may be passed into the defunct function/method.

polmineR-generics *Generic methods defined in the polmineR package*

Description

This documentation object gives an overview over the generic methods defined in the polmineR package that have no individual man page but are documented directly with the classes they are defined for.

Usage

`get_info(x)`

`show_info(x)`

Arguments

x An S4 class object.

p_attributes *Get p-attributes.*

Description

In a CWB corpus, every token has positional attributes. While s-attributes cover a range of tokens, every single token in the token stream of a corpus will have a set of positional attributes (such as part-of-speech, or lemma). The available p-attributes are returned by the p_attributes-method.

Usage

```
p_attributes(.Object, ...)

## S4 method for signature 'character'
p_attributes(.Object, p_attribute = NULL)

## S4 method for signature 'corpus'
p_attributes(.Object, p_attribute = NULL)

## S4 method for signature 'slice'
p_attributes(.Object, p_attribute = NULL, decode = TRUE)

## S4 method for signature 'partition_bundle'
p_attributes(.Object, p_attribute = NULL, decode = TRUE)

## S4 method for signature 'remote_corpus'
p_attributes(.Object, ...)

## S4 method for signature 'remote_partition'
p_attributes(.Object, ...)
```

Arguments

.Object	A length-one character vector, or a partition object.
...	Arguments passed to get_token_stream.
p_attribute	A p-attribute to decode, provided by a length-one character vector.
decode	A length-one logical value. Whether to return decoded p-attributes or unique token ids.

Details

The p_attributes-method returns the p-attributes defined for the corpus the partition is derived from, if argument p_attribute is NULL (the default). If p_attribute is defined, the unique values for the p-attribute are returned.

References

Stefan Evert & The OCWB Development Team, CQP Query Language Tutorial, https://cwb.sourceforge.io/files/CQP_Tutorial

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

p_attributes("REUTERS")
p_attributes("REUTERS", p_attribute = "word")
merkel <- partition("GERMAPARLMINI", speaker = "Merkel", regex = TRUE)
merkel_words <- p_attributes(merkel, "word")
```

ranges	<i>Get ranges for query.</i>
--------	------------------------------

Description

Get ranges (pairs of left and right corpus positions) for queries.

Usage

```
ranges(.Object, ...)

## S4 method for signature 'corpus'
ranges(
  .Object,
  query,
  cqp = FALSE,
  check = TRUE,
  p_attribute = "word",
  verbose = TRUE,
  mc = 1L,
  progress = FALSE
)

## S4 method for signature 'character'
ranges(
  .Object,
  query,
  cqp = FALSE,
  check = TRUE,
  p_attribute = "word",
  verbose = TRUE,
  mc = 1L,
  progress = FALSE
)
```

```

## S4 method for signature 'subcorpus'
ranges(
  .Object,
  query,
  cqp = FALSE,
  check = TRUE,
  p_attribute = "word",
  verbose = TRUE,
  mc = 1L,
  progress = FALSE
)

## S4 method for signature 'partition'
ranges(
  .Object,
  query,
  cqp = FALSE,
  check = TRUE,
  p_attribute = "word",
  verbose = TRUE,
  mc = 1L,
  progress = FALSE
)

```

Arguments

<code>.Object</code>	A length-one character vector indicating a CWB corpus, or a corpus, or partition object.
<code>...</code>	Used for reasons of backwards compatibility to process arguments that have been renamed (e.g. <code>pAttribute</code>).
<code>query</code>	A character vector providing one or multiple queries (token to look up, regular expression or CQP query). Token ids (i.e. integer values) are also accepted. If query is neither a regular expression nor a CQP query, a sanity check removes accidental leading/trailing whitespace, issuing a respective warning.
<code>cqp</code>	Either logical (TRUE if query is a CQP query), or a function to check whether query is a CQP query or not (defaults to <code>is.cqp</code> auxiliary function).
<code>check</code>	A logical value, whether to check validity of CQP query using <code>check_cqp_query</code> .
<code>p_attribute</code>	The p-attribute to search. Needs to be stated only if query is not a CQP query. Defaults to NULL.
<code>verbose</code>	A logical value, whether to show messages.
<code>mc</code>	If logical value TRUE, the value of <code>getOption("polmineR.cores")</code> is passed into <code>mclapply</code> or <code>pblapply</code> as the specification of the number of cores to use. It is also possible to supply an integer value with the number of cores directly. Defaults to 1 (no multicore). Relevant only if several queries are to be processed.
<code>progress</code>	A logical value, whether to show a progress bar when processing multiple queries.

ranges-class	<i>Ranges of query matches.</i>
--------------	---------------------------------

Description

S4 class to manage ranges of corpus positions for query matches. The class inherits from the classes `regions` and `corpus`.

Usage

```
## S3 method for class 'ranges'
as.data.table(x, ...)
```

Arguments

<code>x</code>	A ranges class object.
<code>...</code>	Additional arguments (unused).

Slots

<code>query</code>	A length-one character string, query used for query matches.
--------------------	--

See Also

Other classes to manage corpora: [corpus-class](#), [phrases-class](#), [regions](#), [subcorpus](#)

read	<i>Display full text.</i>
------	---------------------------

Description

Generate text (i.e. html) and display it in the viewer pane of RStudio for reading it. If called on a `partition_bundle-object`, skip through the partitions contained in the bundle.

Usage

```
read(.Object, ...)

## S4 method for signature 'partition'
read(
  .Object,
  meta = NULL,
  highlight = list(),
  tooltips = list(),
  href = list(),
```

```

    verbose = TRUE,
    cpos = TRUE,
    cutoff = getOption("polmineR.cutoff"),
    template = get_template(.Object),
    ...
)

## S4 method for signature 'subcorpus'
read(
  .Object,
  meta = NULL,
  highlight = list(),
  tooltips = list(),
  href = list(),
  annotation,
  verbose = TRUE,
  cpos = TRUE,
  cutoff = getOption("polmineR.cutoff"),
  template = get_template(.Object),
  ...
)

## S4 method for signature 'partition_bundle'
read(.Object, highlight = list(), cpos = TRUE, ...)

## S4 method for signature 'data.table'
read(.Object, col, partition_bundle, highlight = list(), cpos = FALSE, ...)

## S4 method for signature 'hits'
read(.Object, def, i = NULL, ...)

## S4 method for signature 'kwic'
read(.Object, i = NULL, type)

## S4 method for signature 'regions'
read(.Object, meta = NULL)

```

Arguments

<code>.Object</code>	aAn object to be read (partition or partition_bundle).
<code>...</code>	Further parameters passed into read().
<code>meta</code>	a character vector supplying s-attributes for the metainformation to be printed; if not stated explicitly, session settings will be used
<code>highlight</code>	a named list of character vectors (see details)
<code>tooltips</code>	a named list (names are colors, vectors are tooltips)
<code>href</code>	A named list with hypertext references that will be inserted as attribute href of a elements. The names of the list are either colors of highlighted text that has been generated previously, or corpus positions.

verbose	logical
cpos	logical, if TRUE, corpus positions will be assigned (invisibly) to a cpos tag of a html element surrounding the tokens
cutoff	maximum number of tokens to display
template	template to format output
annotation	Object inheriting from subcorpus class. If provided, highlight, tooltips and href will be taken from the slot 'annotations' of this object.
col	column of data.table with terms to be highlighted
partition_bundle	A partition_bundle object.
def	a named list used to define a partition (names are s-attributes, vectors are values of s-attributes)
i	If .Object is an object of the classes kwic or hits, the ith kwic line or hit to derive a partition to be inspected from
type	the partition type, see documentation for partition()-method

Details

To prepare the html output, the method `read()` will call `html()` and `as.markdown()` subsequently, the latter method being the actual worker. Consult these methods to understand how preparing the output works.

The param `highlight()` can be used to highlight terms. It is expected to be a named list of character vectors, the names providing the colors, and the vectors the terms to be highlighted. To add tooltips, use the param `tooltips`.

The method `read()` is a high-level function that calls the methods mentioned before. Results obtained through `read()` can also be obtained through combining these methods in a pipe using the package 'magrittr'. That may offer more flexibility, e.g. to highlight matches for CQP queries. See examples and the documentation for the different methods to learn more.

See Also

For concordances / a keyword-in-context display, see [kwic](#).

Examples

```
use("polmineR")
merkel <- partition("GERMAPARLMINI", date = "2009-11-10", speaker = "Merkel", regex = TRUE)
if (interactive()) read(merkel, meta = c("speaker", "date"))
if (interactive()) read(
  merkel,
  highlight = list(yellow = c("Deutschland", "Bundesrepublik"), lightgreen = "Regierung"),
  meta = c("speaker", "date")
)

## Not run:
pb <- as.speeches("GERMAPARLMINI", s_attribute_date = "date", s_attribute_name = "speaker")
pb <- pb[[ data.table::as.data.table(summary(pb))[size >= 500][["name"]] ]]
```

```
pb <- pb[[ 1:10 ]]
read(pb)

## End(Not run)
```

regions	<i>Regions of a CWB corpus.</i>
---------	---------------------------------

Description

Class to store and process the regions of a corpus. Regions are defined by start and end corpus positions and correspond to a set of tokens surrounded by start and end XML tags.

Usage

```
regions(x, s_attribute)

## S4 method for signature 'corpus'
regions(x, s_attribute)

## S4 method for signature 'subcorpus'
regions(x, s_attribute)

as.regions(x, ...)

## S3 method for class 'regions'
as.data.table(x, keep.rownames, values = NULL, ...)
```

Arguments

x	object of class regions
s_attribute	An s-attribute denoted by a length-one character vector for which regions shall be derived.
...	Further arguments.
keep.rownames	Required argument to safeguard consistency with S3 method definition in the data.table package. Unused in this context.
values	values to assign to a column that will be added

Details

The regions class is a minimal representation of regions and does not include information on the "strucs" (region IDs) that are used internally to obtain values of s-attributes or information, which combination of conditions on s-attributes has been used to obtain regions. This is left to the subcorpus corpus class. Whereas the subcorpus class is associated with the assumption, that a set of regions is a meaningful sub-unit of a corpus, the regions class has a focus on the individual sequences of tokens defined by a structural attribute (such as paragraphs, sentences, named entities).

Information on regions is maintained in the `cpos` slot of the `regions S4` class: A two-column matrix with begin and end corpus positions (first and second column, respectively). All other slots are inherited from the `corpus` class.

The understanding of "regions" is modelled on the usage of terms by CWB developers. As it is put in the [CQP Interface and Query Language Manual](#): "Matching pairs of XML start and end tags are encoded as token regions, identified by the corpus positions of the first token (immediately following the start tag) and the last token (immediately preceding the end tag) of the region." (p. 6)

The `as.regions`-method coerces objects to a `regions`-object.

The `as.data.table` method returns the matrix with corpus positions in the slot `cpos` as a `data.table`.

Slots

`cpos` A two-column matrix with start and end corpus positions (first and second column, respectively).

See Also

Other classes to manage corpora: [corpus-class](#), [phrases-class](#), [ranges-class](#), [subcorpus](#)

Examples

```
use("polmineR")
P <- partition("GERMAPARLMINI", date = "2009-11-12", speaker = "Jens Spahn")
R <- as.regions(P)
use(pkg = "RcppCWB", corpus = "REUTERS")

# Get regions matrix as data.table, without / with values
sc <- corpus("REUTERS") %>% subset(grep("saudi-arabia", places))
regions_dt <- as.data.table(sc)
regions_dt <- as.data.table(
  sc,
  values = s_attributes(sc, "id", unique = FALSE)
)
```

registry_move

Get registry and data directories.

Description

The Corpus Workbench (CWB) uses a registry directory with plain text files describing corpora in a standardized format. The binary files of a corpus are stored in a data directory defined in the registry directory. The `registry` and `data_dir` functions return the respective directories within a package, if the argument `pkg` is used, or the temporary registry and data directory in the per-session temporary directory, if `pkg` is `NULL` (default value).

Usage

```
registry_move(corpus, registry, registry_new, home_dir_new)

registry(pkg = NULL)

data_dir(pkg = NULL)
```

Arguments

corpus	The ID of the corpus for which the registry file shall be moved.
registry	The old registry directory.
registry_new	The new registry directory.
home_dir_new	The new home directory.
pkg	A character string with the name of a single package; if NULL (default), the temporary registry and data directory is returned.

Details

The `registry_move` is an auxiliary function to create a copy of a registry file in the directory specified by the argument `registry_new`.

Upon loading the `polmineR` package, there is a check whether the environment variable `CORPUS_REGISTRY` is defined. In case it is, the registry files in the directory defined by the `CORPUS_REGISTRY` environment variable are copied to the temporary registry directory, which serves as the central place to store all registry files for all corpora, be it system corpora, corpora included in R packages, or temporary corpora.

The Corpus Workbench may have problems to cope with a registry path that includes registry non-ASCII characters. On Windows, a call to `utils::shortPathName` will generate the short MS-DOS path name that circumvents resulting problems.

Usage of the temporary registry directory can be suppress by setting the environment variable `POLMINER_USE_TMP_REGISTRY` as 'false'. In this case, the `registry` function will return the environment variable `CORPUS_REGISTRY` unchanged. The `data_dir` function will return the "indexed_corpus" directory that is assumed to live in the same parent directory as the registry directory.

Value

A path to a (registry or data) directory, or NULL, if package does not exist or is not a package including a corpus.

Examples

```
registry() # returns temporary registry directory
registry(pkg = "polmineR") # returns registry directory in polmineR-package

data_dir()
data_dir(pkg = "polmineR")
```

renamed	<i>Renamed Functions</i>
---------	--------------------------

Description

These functions have been renamed in order to have a consistent coding style that follows the snake_case convention. The "old" function still work to maintain backwards compatibility.

Usage

```
sAttributes(...)
pAttributes(...)
getTokenStream(...)
getTerms(...)
getEncoding(...)
partitionBundle(...)
as.partitionBundle(...)

## S4 method for signature 'textstat'
corpus(.Object)

## S4 method for signature 'bundle'
corpus(.Object)

## S4 method for signature 'kwic'
corpus(.Object)
```

Arguments

...	argument that are passed to the renamed function
.Object	A kwic object.

size	<i>Get Number of Tokens.</i>
------	------------------------------

Description

The method will get the number of tokens in a corpus, partition or subcorpus, split up by an s-attribute if provided.

Usage

```

size(x, ...)

## S4 method for signature 'corpus'
size(x, s_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'character'
size(x, s_attribute = NULL, verbose = TRUE, ...)

## S4 method for signature 'partition'
size(x, s_attribute = NULL, ...)

## S4 method for signature 'partition_bundle'
size(x)

## S4 method for signature 'DocumentTermMatrix'
size(x)

## S4 method for signature 'TermDocumentMatrix'
size(x)

## S4 method for signature 'features'
size(x)

## S4 method for signature 'remote_corpus'
size(x)

## S4 method for signature 'remote_partition'
size(x)

```

Arguments

x	An object to get size(s) for.
...	Further arguments (used only for backwards compatibility).
s_attribute	A character vector with s-attributes (one or more).
verbose	A logical value, whether to output messages.

Details

One or more s-attributes can be provided to get the dispersion of tokens across one or more dimensions. If more than one s_attribute is provided and the structure of s-attributes is nested, ordering attributes according to the ascending tree structure is advised for performance reasons.

The size()-method for features objects will return a named list with the size of the corpus of interest ("coi"), i.e. the number of tokens in the window, and the reference corpus ("ref"), i.e. the number of tokens that are not matched by the query and that are outside the window.

Value

If `.Object` is a corpus (a corpus object or specified by corpus id), an integer vector if argument `s_attribute` is `NULL`, a two-column `data.table` otherwise (first column is the s-attribute, second column: "size"). If `.Object` is a `subcorpus_bundle` or a `partition_bundle`, a `data.table` (with columns "name" and "size").

See Also

See [dispersion](#)-method for counts of hits. The [hits](#) method calls the `size`-method to get sizes of subcorpora.

Examples

```
use("polmineR")
use(pkg = "RcppCWB", corpus = "REUTERS")

# for corpus object
corpus("REUTERS") %>% size()
corpus("REUTERS") %>% size(s_attribute = "id")
corpus("GERMAPARLMINI") %>% size(s_attribute = c("date", "party"))

# for corpus specified by ID
size("GERMAPARLMINI")
size("GERMAPARLMINI", s_attribute = "date")
size("GERMAPARLMINI", s_attribute = c("date", "party"))

# for partition object
P <- partition("GERMAPARLMINI", date = "2009-11-11")
size(P, s_attribute = "speaker")
size(P, s_attribute = "party")
size(P, s_attribute = c("speaker", "party"))

# for subcorpus
sc <- corpus("GERMAPARLMINI") %>% subset(date == "2009-11-11")
size(sc, s_attribute = "speaker")
size(sc, s_attribute = "party")
size(sc, s_attribute = c("speaker", "party"))

# for subcorpus_bundle
subcorpora <- corpus("GERMAPARLMINI") %>% split(s_attribute = "date")
size(subcorpora)
```

 slice

Virtual class slice.

Description

The classes `subcorpus` and `partition` can be used to define subcorpora. Unlike the `subcorpus` class, the `partition` class may include statistical evaluations. The virtual class `slice` is a mechanism to define methods for these classes without making `subcorpus` the superclass of `partition`.

Usage

```
## S4 method for signature 'slice'
aggregate(x)
```

Arguments

x An object of a class belonging to the virtual class `slice`, i.e. a partition or regions object.

Details

The method `aggregate` will deflate the matrix in the slot `cpos`, i.e. it checks for each new row in the matrix whether it increments the end of the previous region (by 1), and ensure that the `cpos` matrix defines disjointed regions.

Examples

```
P <- new(
  "partition",
  cpos = matrix(data = c(1:10, 20:29), ncol = 2, byrow = TRUE),
  stat = data.table::data.table()
)
P2 <- aggregate(P)
P2@cpos
```

subcorpus

The S4 subcorpus class.

Description

Class to manage subcorpora derived from a CWB corpus.

Usage

```
## S4 method for signature 'subcorpus'
summary(object)

## S4 replacement method for signature 'subcorpus'
name(x) <- value

## S4 method for signature 'subcorpus'
get_corpus(x)

## S4 method for signature 'subcorpus'
size(x, s_attribute = NULL, ...)
```

Arguments

object	A subcorpus object.
x	A subcorpus object.
value	A character vector to assign as name to slot name of a subcorpus class object.
s_attribute	A character vector with s-attributes (one or more).
...	Arguments passed into size-method. Used only to maintain backwards compatibility.

Methods (by generic)

- `summary(subcorpus)`: Get named list with basic information for subcorpus object.
- `name(subcorpus) <- value`: Assign name to a subcorpus object.
- `get_corpus(subcorpus)`: Get the corpus ID from the subcorpus object.
- `size(subcorpus)`: Get the size of a subcorpus object from the respective slot of the object.

Slots

s_attributes	A named list with the structural attributes defining the subcorpus.
cpos	A matrix with left and right corpus positions defining regions (two column matrix with integer values).
annotations	Object of class <code>list</code> .
size	Total size (number of tokens) of the subcorpus object (a length-one integer vector). The value is accessible by calling the <code>size</code> -method on the subcorpus-object (see examples).
metadata	Object of class <code>data.frame</code> , metadata information.
strucs	Object of class <code>integer</code> , the strucs defining the subcorpus.
xml	Object of class <code>character</code> , whether the xml is "flat" or "nested".
s_attribute_strucs	Object of class <code>character</code> , the base node.
user	If the corpus on the server requires authentication, the username.
password	If the corpus on the server requires authentication, the password.

See Also

Most commonly, a subcorpus is derived from a corpus or a subcorpus using the [subset](#) method. See [size](#) for detailed documentation on how to use the `size`-method. The subcorpus class shares many features with the `partition` class, but it is more parsimonious and does not include information on statistical properties of the subcorpus (i.e. a count table). In line with this logic, the subcorpus class inherits from the `corpus` class, whereas the `partition` class inherits from the `textstat` class.

Other classes to manage corpora: [corpus-class](#), [phrases-class](#), [ranges-class](#), [regions](#)

Examples

```

use("polmineR")

# basic example
r <- corpus("REUTERS")
k <- subset(r, grepl("kuwait", places))
name(k) <- "kuwait"
y <- summary(k)
s <- size(k)

# the same with a magrittr pipe
corpus("REUTERS") %>%
  subset(grepl("kuwait", places)) %>%
  summary()

# subsetting a subcorpus in a pipe
stone <- corpus("GERMAPARLMINI") %>%
  subset(date == "2009-11-10") %>%
  subset(speaker == "Frank-Walter Steinmeier")

# perform count for subcorpus
n <- corpus("REUTERS") %>% subset(grep("kuwait", places)) %>% count(p_attribute = "word")
n <- corpus("REUTERS") %>% subset(grep("saudi-arabia", places)) %>% count('Saudi Arabia')

# keyword-in-context analysis (kwic)
k <- corpus("REUTERS") %>% subset(grep("kuwait", places)) %>% kwic("oil")

```

subcorpus_bundle-class

Bundled subcorpora

Description

A subcorpus_bundle object combines a set of subcorpus objects in a list in the the slot objects. The class inherits from the partition_bundle and the bundle class. Typically, a subcorpus_bundle is generated by applying the split-method on a corpus or subcorpus.

Usage

```

## S4 method for signature 'subcorpus_bundle'
show(object)

## S4 method for signature 'subcorpus_bundle'
merge(x, name = "", verbose = FALSE)

## S4 method for signature 'subcorpus'
merge(x, y, ...)

```

```

## S4 method for signature 'subcorpus'
split(
  x,
  s_attribute,
  values,
  prefix = "",
  mc = getOption("polmineR.mc"),
  verbose = TRUE,
  progress = FALSE,
  type = get_type(x)
)

## S4 method for signature 'corpus'
split(
  x,
  s_attribute,
  values,
  prefix = "",
  mc = getOption("polmineR.mc"),
  verbose = TRUE,
  progress = FALSE,
  type = get_type(x),
  xml = "flat"
)

## S4 method for signature 'subcorpus_bundle'
split(
  x,
  s_attribute,
  prefix = "",
  progress = TRUE,
  mc = getOption("polmineR.mc")
)

```

Arguments

object	An object of class subcorpus_bundle.
x	A corpus, subcorpus, or subcorpus_bundle object.
name	The name of the new subcorpus object.
verbose	Logical, whether to provide progress information.
y	A subcorpus to be merged with x.
...	Further subcorpus objects to be merged with x and y.
s_attribute	The s-attribute to vary.
values	Either a character vector with values used for splitting, or a logical value: If TRUE, changes of s-attribute values will be the basis for generating subcorpora. If FALSE, a new subcorpus is generated for every struc of the s-attribute. If

	missing (default), TRUE/FALSE is assigned depending on whether s-attribute has values, or not.
prefix	A character vector that will be attached as a prefix to partition names.
mc	Logical, whether to use multicore parallelization.
progress	Logical, whether to show progress bar.
type	The type of partition to generate.
xml	A logical value.

Details

Applying the `split`-method to a `subcorpus_bundle`-object will iterate through the subcorpus, and apply `split` on each subcorpus object in the bundle, splitting it up by the s-attribute provided by the argument `s_attribute`. The return value is a `subcorpus_bundle`, the names of which will be the names of the incoming `partition_bundle` concatenated with the s-attribute values used for splitting. The argument `prefix` can be used to achieve a more descriptive name.

Examples

```
corpus("REUTERS") %>% split(s_attribute = "id") %>% summary()

# Merge multiple subcorpus objects
a <- corpus("GERMAPARLMINI") %>% subset(date == "2009-10-27")
b <- corpus("GERMAPARLMINI") %>% subset(date == "2009-10-28")
c <- corpus("GERMAPARLMINI") %>% subset(date == "2009-11-10")
y <- merge(a, b, c)
s_attributes(y, "date")
sc <- subset("GERMAPARLMINI", date == "2009-11-11")
b <- split(sc, s_attribute = "speaker")

p <- partition("GERMAPARLMINI", date = "2009-11-11")
y <- partition_bundle(p, s_attribute = "speaker")
gparl <- corpus("GERMAPARLMINI")
b <- split(gparl, s_attribute = "date")
# split up objects in partition_bundle by using partition_bundle-method
use("polmineR")
y <- corpus("GERMAPARLMINI") %>%
  split(s_attribute = "date") %>%
  split(s_attribute = "speaker")

summary(y)
```

Description

The structural attributes of a corpus (s-attributes) can be used to generate subcorpora (i.e. a subcorpus class object) by applying the subset-method. To obtain a subcorpus, the subset-method can be applied on a corpus represented by a corpus object, a length-one character vector (as a shortcut), and on a subcorpus object.

Usage

```
## S4 method for signature 'corpus'
subset(x, subset, regex = FALSE, verbose = FALSE, ...)

## S4 method for signature 'character'
subset(x, ...)

## S4 method for signature 'subcorpus'
subset(x, subset, verbose = FALSE, ...)

## S4 method for signature 'remote_corpus'
subset(x, subset)

## S4 method for signature 'subcorpus_bundle'
subset(x, ..., iterate = FALSE, verbose = TRUE, progress = FALSE, mc = NULL)
```

Arguments

x	A corpus or subcorpus object. A corpus may also specified by a length-one character vector.
subset	A logical expression indicating elements or rows to keep. The expression may be unevaluated (using quote() or bquote()).
regex	A logical value. If TRUE, values for s-attributes defined using the three dots (...) are interpreted as regular expressions and passed into a grep call for subsetting a table with the regions and values of structural attributes. If FALSE (the default), values for s-attributes must match exactly.
verbose	A logical value, whether to show progress messages.
...	An expression that will be used to create a subcorpus from s-attributes.
iterate	A logical value, if TRUE, process very single object of x individually.
progress	A logical value, whether to display progress bar.
mc	An integer value, number of cores to use. If NULL (default), no multithreading.

Details

The default approach for subsetting a subcorpus_bundle is to temporarily merge objects into a single subcorpus, perform subset(), and restore subcorpus_bundle by splitting on the s-attribute of the input subcorpus_bundle. This approach may have unintended results, if x has been generated using complex criteria. This may be the case for instance, if x resulted from as.speeches(). In this scenario, set argument iterate to TRUE to iterate over objects in bundle one-by-one.

Value

A subcorpus object. If the expression provided by argument `subset` includes undefined `s`-attributes, a warning is issued and the return value is `NULL`.

See Also

The methods applicable for the subcorpus object resulting from subsetting a corpus or subcorpus are described in the documentation of the `\link{subcorpus-class}`. Note that the `subset-method` can also be applied to `textstat-class` objects (and objects inheriting from this class).

Examples

```
use("polmineR")

# examples for standard and non-standard evaluation
a <- corpus("GERMAPARLMINI")

# subsetting a corpus object using non-standard evaluation
sc <- subset(a, speaker == "Angela Dorothea Merkel")
sc <- subset(a, speaker == "Angela Dorothea Merkel" & date == "2009-10-28")
sc <- subset(a, grepl("Merkel", speaker))
sc <- subset(a, grepl("Merkel", speaker) & date == "2009-10-28")

# subsetting corpus specified by character vector
sc <- subset("GERMAPARLMINI", grepl("Merkel", speaker))
sc <- subset("GERMAPARLMINI", speaker == "Angela Dorothea Merkel")
sc <- subset("GERMAPARLMINI", speaker == "Angela Dorothea Merkel" & date == "2009-10-28")
sc <- subset("GERMAPARLMINI", grepl("Merkel", speaker) & date == "2009-10-28")

# subsetting a corpus using the (old) logic of the partition-method
sc <- subset(a, speaker = "Angela Dorothea Merkel")
sc <- subset(a, speaker = "Angela Dorothea Merkel", date = "2009-10-28")
sc <- subset(a, speaker = "Merkel", regex = TRUE)
sc <- subset(a, speaker = c("Merkel", "Kauder"), regex = TRUE)
sc <- subset(a, speaker = "Merkel", date = "2009-10-28", regex = TRUE)

# providing the value for s-attribute as a variable
who <- "Volker Kauder"
sc <- subset(a, quote(speaker == !!who))

# quoting and quosures necessary when programming against subset
# note how variable who needs to be handled
gparl <- corpus("GERMAPARLMINI")
subcorpora <- lapply(
  c("Angela Dorothea Merkel", "Volker Kauder", "Ronald Pofalla"),
  function(who) subset(gparl, speaker == !!who)
)

# subset a subcorpus_bundle
merkel <- corpus("GERMAPARLMINI") %>%
  split(s_attribute = "protocol_date") %>%
  subset(speaker == "Angela Dorothea Merkel")
```

```
# iterate over objects in bundle one by one
sp <- corpus("GERMAPARLMINI") %>%
  as.speeches(
    s_attribute_name = "speaker",
    s_attribute_date = "protocol_date",
    progress = FALSE
  ) %>%
  subset(interjection == "speech", iterate = TRUE, progress = FALSE)
```

s_attributes

Get s-attributes.

Description

Structural annotations (s-attributes) of a corpus capture metainformation for regions of tokens. The `s_attributes()`-method offers high-level access to the s-attributes present in a corpus or subcorpus, or the values of s-attributes in a corpus/partition.

Usage

```
s_attributes(.Object, ...)

## S4 method for signature 'character'
s_attributes(.Object, s_attribute = NULL, unique = TRUE, regex = NULL, ...)

## S4 method for signature 'corpus'
s_attributes(.Object, s_attribute = NULL, unique = TRUE, regex = NULL, ...)

## S4 method for signature 'slice'
s_attributes(.Object, s_attribute = NULL, unique = TRUE, ...)

## S4 method for signature 'partition'
s_attributes(.Object, s_attribute = NULL, unique = TRUE, ...)

## S4 method for signature 'subcorpus'
s_attributes(.Object, s_attribute = NULL, unique = TRUE, ...)

## S4 method for signature 'context'
s_attributes(.Object, s_attribute = NULL)

## S4 method for signature 'partition_bundle'
s_attributes(.Object, s_attribute, unique = TRUE, ...)

## S4 method for signature 'call'
s_attributes(.Object, corpus)

## S4 method for signature 'quosure'
```

```

s_attributes(.Object, corpus)

## S4 method for signature 'name'
s_attributes(.Object, corpus)

## S4 method for signature 'remote_corpus'
s_attributes(.Object, ...)

## S4 method for signature 'remote_partition'
s_attributes(.Object, ...)

## S4 method for signature 'data.table'
s_attributes(.Object, corpus, s_attribute, registry)

```

Arguments

.Object	A corpus, subcorpus, partition object, or a call. A corpus can also be specified by a length-one character vector.
...	To maintain backward compatibility, if argument sAttribute (deprecated) is used. If .Object is a remote_corpus or remote_subcorpus object, the three dots (...) are used to pass arguments. Hence, it is necessary to state the names of all arguments to be passed explicitly.
s_attribute	The name of a specific s-attribute.
unique	A logical value, whether to return unique values.
regex	A regular expression passed into grep to filter return value by applying a regex.
corpus	A corpus-object or a length one character vector denoting a corpus.
registry	The registry directory with the registry file defining corpus. If missing, the registry directory that can be derived using RcppCWB::corpus_registry_dir() is used.

Details

Importing XML into the Corpus Workbench (CWB) turns elements and element attributes into so-called "s-attributes". There are two basic uses of the s_attributes()-method: If the argument s_attribute is NULL (default), the return value is a character vector with all s-attributes present in a corpus.

If s_attribute denotes a specific s-attribute (a length-one character vector), the values of the s-attributes available in the corpus/partition are returned. If the s-attribute does not have values, NA is returned and a warning message is issued.

If argument unique is FALSE, the full sequence of the s_attributes is returned, which is a useful building block for decoding a corpus.

If argument s_attributes is a character providing several s-attributes, the method will return a data.table. If unique is TRUE, all unique combinations of the s-attributes will be reported by the data.table.

If the corpus is based on a nested XML structure, the order of items on the s_attribute vector matters. The method for corpus objects will take the first s-attribute as the benchmark and assume that further s-attributes are XML ancestors of the node.

If `.Object` is a context object, the `s`-attribute value for the first corpus position of every match is returned in a character vector. If the match is outside a region of the `s`-attribute, `NA` is returned.

If `.Object` is a call or a quosure (defined in the `rlang` package), the `s_attributes`-method will return a character vector with the `s`-attributes occurring in the call. This usage is relevant internally to implement the subset method to generate a subcorpus using non-standard evaluation. Usually it will not be relevant in an interactive session.

Value

A character vector (`s`-attributes, or values of `s`-attributes).

Examples

```
use("polmineR")

s_attributes("GERMAPARLMINI")
s_attributes("GERMAPARLMINI", "date") # dates of plenary meetings
s_attributes("GERMAPARLMINI", s_attribute = c("date", "party"))
s_attributes(corpus("GERMAPARLMINI"))
p <- partition("GERMAPARLMINI", date = "2009-11-10")
s_attributes(p)
s_attributes(p, "speaker") # get names of speakers

# Get s-attributes occurring in a call
s_attributes(quote(grep("Merkel", speaker)), corpus = "GERMAPARLMINI")
s_attributes(quote(speaker == "Angela Merkel"), corpus = "GERMAPARLMINI")
s_attributes(quote(speaker != "Angela Merkel"), corpus = "GERMAPARLMINI")
s_attributes(
  quote(speaker == "Angela Merkel" & date == "2009-10-28"),
  corpus = "GERMAPARLMINI"
)

# Get s-attributes from quosure
s_attributes(
  rlang::new_quosure(quote(grep("Merkel", speaker))),
  corpus = "GERMAPARLMINI"
)
```

terms

Get terms in partition or corpus.

Description

Get terms in partition or corpus.

Usage

```
## S4 method for signature 'partition'
terms(x, p_attribute, regex = NULL)

## S4 method for signature 'subcorpus'
terms(x, p_attribute, regex = NULL)

## S4 method for signature 'corpus'
terms(x, p_attribute, regex = NULL, robust = FALSE)

## S4 method for signature 'character'
terms(x, p_attribute, regex = NULL, robust = FALSE)
```

Arguments

x	A corpus, partition or subcorpus object, or a length-one character with a corpus id.
p_attribute	The p-attribute to for which to retrieve results (length-one character vector).
regex	Regular expression(s) to filter results (character vector).
robust	A logical value, whether to check for potential failures.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

r <- partition("REUTERS", id = "144")
words <- terms(r, "word")
terms(r, p_attribute = "word", regex = ".*il.*")
```

textstat-class	<i>S4 textstat superclass.</i>
----------------	--------------------------------

Description

The textstat S4 class is the superclass for the classes features, context, and partition. Usually, these subclasses, which are designed to serve a specified analytical purpose, will be used. Common standard generic methods such as head, tail, dim, nrow, colnames are defined for the textstat class and are available for subclasses by inheritance. The core of textstat and its childs is a data.table in the slot stat for keeping data on text statistics of a corpus, or a partition. The textstat class inherits from the corpus class, keeping information on the corpus available.

Usage

```
## S4 method for signature 'textstat'
name(x)
```

```
## S4 method for signature 'character'
name(x)

## S4 replacement method for signature 'textstat'
name(x) <- value

## S4 method for signature 'textstat'
round(x, digits = 2L)

## S4 method for signature 'textstat'
sort(x, by, decreasing = TRUE)

as.bundle(object, ...)

## S4 method for signature 'textstat,textstat'
e1 + e2

## S4 method for signature 'textstat'
subset(x, subset)

## S3 method for class 'textstat'
as.data.table(x, ...)

## S4 method for signature 'textstat'
show(object)

## S4 method for signature 'textstat'
p_attributes(.Object)

## S4 method for signature 'textstat'
knit_print(x, options = knitr::opts_chunk, ...)

## S4 method for signature 'textstat'
get_corpus(x)

## S4 method for signature 'textstat'
format(x, digits = 2L)

restore(file)

cp(x)

## S4 method for signature 'textstat'
view(.Object)
```

Arguments

x An object (textstat or class inheriting from textstat).

value	A character vector to assign as name to slot name of a textstat class object.
digits	Number of digits.
by	Column that will serve as the key for sorting.
decreasing	Logical, whether to return decreasing order.
object	a textstat object
...	Argument that will be passed into a call of the format method on the object x.
e1	A textstat object.
e2	Another textstat object.
subset	A logical expression indicating elements or rows to keep.
.Object	A textstat object.
options	Chunk options.
file	An rds file to restore (filename).

Details

A `head`-method will return the first rows of the `data.table` in the `stat`-slot. Use argument `n` to specify the number of rows.

A `tail`-method will return the last rows of the `data.table` in the `stat`-slot. Use argument `n` to specify the number of rows.

The methods `dim`, `nrow` and `ncol` will return information on the dimensions, the number of rows, or the number of columns of the `data.table` in the `stat`-slot, respectively.

Objects derived from the `textstat` class can be indexed with simple square brackets (`"[`") to get rows specified by an numeric/integer vector, and with double square brackets (`"[[`") to get specific columns from the `data.table` in the slot `stat`.

The `colnames`-method will return the column names of the `data-table` in the slot `stat`.

The methods `as.data.table`, and `as.data.frame` will extract the `data.table` in the slot `stat` as a `data.table`, or `data.frame`, respectively.

`textstat` objects can have a name, which can be retrieved, and set using the `name`-method and `name<-`, respectively.

The `round()`-method looks up all numeric columns in the `data.table` in the `stat`-slot of the `textstat` object and rounds values of these columns to the number of decimal places specified by argument `digits`.

The `knit_print` method will be called by `knitr` to render `textstat` objects or objects inheriting from the `textstat` class as a `DataTable` `htmlwidget` when rendering a R Markdown document as `html`. It will usually be necessary to explicitly state `"render = knit_print"` in the chunk options. The option `polmineR.pagelength` controls the number of lines displayed in the resulting `htmlwidget`. Note that including `htmlwidgets` in `html` documents requires that `pandoc` is installed. To avoid an error, a formatted `data.table` is returned by `knit_print` if `pandoc` is not available.

The `format()`-method returns a pretty-printed and minimized version of the `data.table` in the `stat`-slot of the `textstat`-object: It will round all numeric columns to the number of decimal numbers specified by `digits`, and drop all columns with token ids. The return value is a `data.table`.

Using the reference semantics of `data.table` objects (i.e. inplace modification) has great advantages for memory efficiency. But there may be unexpected behavior when reloading an S4

textstat object (including classes inheriting from textstat) with a data.table in the stat slot. Use restore to copy the data.table once to have a restored object that works for inplace operations after saving / reloading it.

It is not possible to add columns to the data.table in the stat slot of a textclass object, when the object has been saved and loaded using save()/load(). This scenario applies for instance, when the objects of an interactive R session are saved, and loaded when starting the next interactive R session. The cp() function will create a copy of the object, including an explicit copy of the data.table in the stat slot. Inplace modifications of the new object are possible. The function can also be used to avoid unwanted side effects of modifying an object.

Slots

p_attribute Object of class character, p-attribute of the query.

corpus A corpus specified by a length-one character vector.

stat A data.table with statistical information.

name The name of the object.

annotation_cols A character vector, column names of data.table in slot stat that are annotations.

encoding A length-one character vector, the encoding of the corpus.

Examples

```
use(pkg = "polmineR", corpus = "GERMAPARLMINI")
use(pkg = "RcppCWB", corpus = "REUTERS")

P <- partition("GERMAPARLMINI", date = ".*", p_attribute = "word", regex = TRUE)
y <- cooccurrences(P, query = "Arbeit")

# generics defined in the polmineR package
x <- count("REUTERS", p_attribute = "word")
name(x) <- "count_reuters"
name(x)
get_corpus(x)

# Standard generic methods known from data.frames work for objects inheriting
# from the textstat class

head(y)
tail(y)
nrow(y)
ncol(y)
dim(y)
colnames(y)

# Use brackets for indexing

## Not run:
y[1:25]
y[,c("word", "11")]
```

```

y[1:25, "word"]
y[1:25][["word"]]
y[which(y[["word"]] %in% c("Arbeit", "Sozial"))]
y[ y[["word"]] %in% c("Arbeit", "Sozial") ]

## End(Not run)
sc <- partition("GERMAPARLMINI", speaker = "Angela Dorothea Merkel")
cnt <- count(sc, p_attribute = c("word", "pos"))
cnt_min <- subset(cnt, pos %in% c("NN", "ADJA"))
cnt_min <- subset(cnt, pos == "NE")
use(pkg = "RcppCWB", corpus = "REUTERS")

# Get statistics in textstat object as data.table
count_dt <- corpus("REUTERS") %>%
  subset(grep("saudi-arabia", places)) %>%
  count(p_attribute = "word") %>%
  as.data.table()

# textstat objects stored as *.rds files should be loaded using restore().
# Before moving to examples, this is a brief technical dip why this is
# recommended: If we load the *.rds file with readRDS(), the data.table in
# the slot 'stat' will have the pointer '0x0', and the data.table cannot be
# augmented without having been copied previously.

k <- kwic("REUTERS", query = "oil")
kwicfile <- tempfile(fileext = ".rds")
saveRDS(k, file = kwicfile)
problemprone <- readRDS(file = kwicfile)
problemprone@stat[, "newcol" := TRUE]
"newcol" %in% colnames(problemprone@stat) # is FALSE!

attr(problemprone@stat, ".internal.selfref")
identical(attr(problemprone@stat, ".internal.selfref"), new("externalptr"))

# Restore stored S4 object with copy of data.table in 'stat' slot
k <- kwic("REUTERS", query = "oil")
kwicfile <- tempfile(fileext = ".rds")
saveRDS(k, file = kwicfile)

k2 <- restore(kwicfile)
enrich(k2, s_attribute = "id")
"id" %in% colnames(k2) # is TRUE
k <- kwic("REUTERS", query = "oil")
rdata_file <- tempfile(fileext = ".RData")
save(k, file = rdata_file)
rm(k)

load(rdata_file)
k <- cp(k) # now it is possible to columns by reference
enrich(k, s_attribute = "id")
"id" %in% colnames(k)

```

tooltips-method	<i>Add tooltips to text output.</i>
-----------------	-------------------------------------

Description

Highlight tokens based on exact match, a regular expression or corpus position in kwic output or html document.

Usage

```
tooltips(.Object, tooltips, ...)

## S4 method for signature 'character'
tooltips(
  .Object,
  tooltips = list(),
  fmt = "//span[@style=\"background-color:%s\"]",
  verbose
)

## S4 method for signature 'html'
tooltips(.Object, tooltips = list(), fmt, verbose = TRUE)

## S4 method for signature 'kwic'
tooltips(.Object, tooltips, regex = FALSE, ...)
```

Arguments

.Object	A html or character object with html.
tooltips	A named list of character vectors, the names need to match colors in the list provided to param highlight. The value of the character vector is the tooltip to be displayed.
...	Further arguments are interpreted as assignments of tooltips to tokens.
fmt	A format string with an xpath expression used to look up the node where the tooltip is inserted. If missing, a heuristic evaluating the names of the tooltips list decides whether tooltips are inserted based on highlighting colors or corpus positions.
verbose	A logical value, whether to show messages.
regex	A logical value, whether character vector values of argument tooltips are interpreted as regular expressions.

Examples

```
use(pkg = "RcppCWB", corpus = "REUTERS")

a <- partition("REUTERS", places = "argentina")
```

```

b <- html(a)
c <- highlight(b, lightgreen = "higher")
d <- tooltips(c, list(lightgreen = "Further information"))
if (interactive()) d

# Using the tooltips-method in a pipe ...
h <- a %>%
  html() %>%
  highlight(yellow = c("barrels", "oil", "gas")) %>%
  tooltips(list(yellow = "energy"))

```

tree_structure	<i>Show the structure of s-attributes</i>
----------------	---

Description

Show the structure of s-attributes. If x is a subcorpus, the s-attribute used for corpus subsetting is highlighted.

Usage

```

tree_structure(x, ...)

## S4 method for signature 'xml_node'
tree_structure(x, s_attribute = NULL, prefix = 0, indent = 3, root = TRUE)

## S4 method for signature 'xml_document'
tree_structure(x, s_attribute = NULL, prefix = 0, indent = 3, root = TRUE)

## S4 method for signature 'subcorpus'
tree_structure(x)

## S4 method for signature 'corpus'
tree_structure(x, s_attribute = NULL)

```

Arguments

x	Object for which to visualise structure.
...	Further arguments.
s_attribute	Name of the s-attribute used for subsetting, will be highlighted.
prefix	Number of blank spaces.
indent	Number of spaces to indent.
root	Whether branch is root.

Examples

```

xml_sample <- system.file(
  package = "GermaParl2",
  "extdata", "cwb", "indexed_corpora",
  "germaparl2mini"
)
if (nchar(xml_sample) > 0L && interactive()){
  use(pkg = "GermaParl2", corpus = "GERMAPARL2MINI")

  corpus("GERMAPARL2MINI") %>%
    tree_structure()

  corpus("GERMAPARL2MINI") %>%
    subset(speaker_name == "Konrad Adenauer") %>%
    tree_structure()

  corpus("GERMAPARL2MINI") %>%
    subset(speaker_name == "Konrad Adenauer") %>%
    subset(p) %>%
    tree_structure()

  corpus("GERMAPARL2MINI") %>%
    subset(ne_type) %>%
    tree_structure()
}

```

trim

Trim an object.

Description

Method to trim and adjust objects by applying thresholds, minimum frequencies etc. It can be applied to context, features, context, partition and partition_bundle objects.

Usage

```

trim(.Object, ...)

## S4 method for signature 'TermDocumentMatrix'
trim(
  .Object,
  terms_to_drop,
  docs_to_keep,
  min_count,
  min_doc_length,
  verbose = TRUE,
  ...
)

```

```
## S4 method for signature 'DocumentTermMatrix'
trim(
  .Object,
  terms_to_drop,
  docs_to_keep,
  min_count,
  min_doc_length,
  verbose = TRUE,
  ...
)

punctuation
```

Arguments

<code>.Object</code>	The object to be trimmed
<code>...</code>	further arguments
<code>terms_to_drop</code>	A character vector with terms to exclude from matrix (terms used as stop-words).
<code>docs_to_keep</code>	A character vector with documents to keep.
<code>min_count</code>	A numeric value with a minimum value of total term frequency across documents to exclude rare terms from matrix.
<code>min_doc_length</code>	A numeric value with minimum total of the summed-up occurrence of tokens in a document. Exclude documents below this value and filter out short documents. Note that the <code>min_doc_length</code> filter is applied before filtering for <code>min_count</code> and <code>terms_to_keep</code> , and that these filters will reduce document lengths.
<code>verbose</code>	A logical value, whether to output progress messages.

Format

An object of class character of length 13.

Author(s)

Andreas Blaette

Examples

```
use("RcppCWB", corpus = "REUTERS")
dtm <- corpus("REUTERS") %>%
  split(s_attribute = "id") %>%
  as.DocumentTermMatrix(p_attribute = "word", verbose = FALSE)
trim(dtm, min_doc_length = 100)
```

t_test	<i>Perform t-test.</i>
--------	------------------------

Description

Compute t-scores to find collocations.

Usage

```
t_test(.Object)

## S4 method for signature 'context'
t_test(.Object)
```

Arguments

.Object A context or features object

Details

The calculation of the t-test is based on the formula

$$t = \frac{\bar{x} - \mu}{\sqrt{\frac{s^2}{N}}}$$

where μ is the mean of the distribution, \bar{x} the sample mean, s^2 the sample variance, and N the sample size.

Following Manning and Schuetze (1999), to test whether two tokens (a and b) are a collocation, the sample mean μ is the number of observed co-occurrences of a and b divided by corpus size N :

$$\mu = \frac{o_{ab}}{N}$$

For the mean of the distribution \bar{x} , maximum likelihood estimates are used. Given that we know the number of observations of token a, o_a , the number of observations of b, o_b and the size of the corpus N , the probabilities for the tokens a and b, and for the co-occurrence of a and b are as follows, if independence is assumed:

$$P(a) = \frac{o_a}{N}$$

$$P(b) = \frac{o_b}{N}$$

$$P(ab) = P(a)P(b)$$

See the examples for a sample calculation of the t-test, and Evert (2005: 83) for a critical discussion of the "highly questionable" assumptions when using the t-test for detecting co-occurrences.

References

Manning, Christopher D.; Schuetze, Hinrich (1999): *Foundations of Statistical Natural Language Processing*. MIT Press: Cambridge, Mass., pp. 163-166.

Church, Kenneth W. et al. (1991): Using Statistics in Lexical Analysis. In: Uri Zernik (ed.), *Lexical Acquisition*. Hillsdale, NJ:Lawrence Erlbaum, pp. 115-164 [doi:10.4324/97813157853878](https://doi.org/10.4324/97813157853878)

Evert, Stefan (2005): *The Statistics of Word Cooccurrences. Word Pairs and Collocations*. URN urn:nbn:de:bsz:93-opus-23714. <https://elib.uni-stuttgart.de/bitstream/11682/2573/1/Evert2005phd.pdf>

See Also

Other statistical methods: [chisquare\(\)](#), [ll\(\)](#), [pmi\(\)](#)

Examples

```
use("polmineR")
y <- cooccurrences("REUTERS", query = "oil", left = 1L, right = 0L, method = "t_test")
# The critical value (for a = 0.005) is 2.579, so "crude" is a collocation
# of "oil" according to t-test.

# A sample calculation
count_oil <- count("REUTERS", query = "oil")
count_crude <- count("REUTERS", query = "crude")
count_crude_oil <- count("REUTERS", query = '"crude" "oil"', cqp = TRUE)

p_crude <- count_crude$count / size("REUTERS")
p_oil <- count_oil$count / size("REUTERS")
p_crude_oil <- p_crude * p_oil

x <- count_crude_oil$count / size("REUTERS")

t_value <- (x - p_crude_oil) / sqrt(x / size("REUTERS"))
# should be identical with previous result:
as.data.frame(subset(y, word == "crude"))$t_test
```

use

Add corpora in R data packages to session registry.

Description

Use CWB indexed corpora in R data packages by adding registry file to session registry.

Usage

```
use(pkg, corpus, lib.loc = .libPaths(), tmp = FALSE, verbose = TRUE)
```

Arguments

pkg	A package including at least one CWB indexed corpus.
corpus	A corpus (or corpora) to be loaded selectively.
lib.loc	A character vector with path names of R libraries.
tmp	A logical value, whether to use a temporary data directory.
verbose	Logical, whether to output status messages.

Details

pkg is expected to be an installed data package that includes CWB indexed corpora. The use()-function will add the registry files describing the corpus (or the corpora) to the session registry directory and adjust the path pointing to the data in the package.

The registry files within the package are assumed to be in the subdirectory `./extdata/cwb/registry` of the installed package. The data directories for corpora are assumed to be in a subdirectory named after the corpus (lower case) in the package subdirectory `./extdata/cwb/indexed_corpora/`. When adding a corpus to the registry, templates for formatting fulltext output are reloaded.

If the path to the data directory in a package includes a non-ASCII character, binary data files of the corpora in package are copied to a subdirectory of the per-session temporary data directory.

Value

A logical value: TRUE if corpus has been loaded successfully, or FALSE, if any kind of error occurred.

See Also

To get the temporary registry directory, see [registry](#).

Examples

```
use("polmineR")
corpus()
```

view

Inspect object using View().

Description

Inspect object using View().

Usage

```
view(.Object, ...)
```

Arguments

.Object an object
 ... further parameters

weigh *Apply Weight to Matrix*

Description

Apply Weight to Matrix

Usage

```
weigh(.Object, ...)
```

```
## S4 method for signature 'TermDocumentMatrix'
```

```
weigh(.Object, method = "tfidf")
```

```
## S4 method for signature 'DocumentTermMatrix'
```

```
weigh(.Object, method = "tfidf")
```

```
## S4 method for signature 'count'
```

```
weigh(.Object, with)
```

```
## S4 method for signature 'count_bundle'
```

```
weigh(.Object, with, progress = TRUE)
```

Arguments

.Object A matrix, or a count-object.
 ... further parameters
 method The kind of weight to apply.
 with A data.table used to weigh p-attributes. A column 'weight' with term weights is required, and columns with the p-attributes of .Object for matching.
 progress Logical, whether to show a progress bar.

Examples

```
## Not run:
library(data.table)
if (require("zoo") && require("devtools")){

# Source in function 'get_sentiws' from a GitHub gist
gist_url <- path(
  "gist.githubusercontent.com",
  "PolMine",
```

```

    "70eeb095328070c18bd00ee087272adf",
    "raw",
    "c2eee2f48b11e6d893c19089b444f25b452d2adb",
    "sentiws.R"
  )

devtools::source_url(sprintf("https://%s", gist_url))
SentiWS <- get_sentiws()

# Do the statistical word context analysis
use("GermaParl")
options("polmineR.left" = 10L)
options("polmineR.right" = 10L)
df <- context("GERMAPARL", query = "Islam", p_attribute = c("word", "pos")) %>%
  partition_bundle(node = FALSE) %>%
  set_names(s_attributes(., s_attribute = "date")) %>%
  weigh(with = SentiWS) %>%
  summary()

# Aggregate by year
df[["year"]] <- as.Date(df[["name"]]) %>% format("%Y-01-01")
df_year <- aggregate(df[,c("size", "positive_n", "negative_n")], list(df[["year"]]), sum)
colnames(df_year)[1] <- "year"

# Use shares instead of absolute counts
df_year$negative_share <- df_year$negative_n / df_year$size
df_year$positive_share <- df_year$positive_n / df_year$size

# Turn it into zoo object, and plot it
Z <- zoo(
  x = df_year[, c("positive_share", "negative_share")],
  order.by = as.Date(df_year[, "year"])
)
plot(
  Z, ylab = "polarity", xlab = "year",
  main = "Word context of 'Islam': Share of positive/negative vocabulary",
  cex = 0.8,
  cex.main = 0.8
)

# Note that we can use the kwic-method to check for the validity of our findings
words_positive <- SentiWS[weight > 0][["word"]]
words_negative <- SentiWS[weight < 0][["word"]]
kwic("GERMAPARL", query = "Islam", positivelist = c(words_positive, words_negative)) %>%
  highlight(lightgreen = words_positive, orange = words_negative) %>%
  tooltips(setNames(SentiWS[["word"]], SentiWS[["weight"]]))
}

## End(Not run)

```

Index

- * **classes to manage corpora**
 - corpus-class, 45
 - phrases-class, 118
 - ranges-class, 127
 - regions, 130
 - subcorpus, 136
- * **datasets**
 - trim, 153
- * **package**
 - polmineR-package, 4
- * **statistical methods**
 - chisquare, 22
 - ll, 99
 - pmi, 121
 - t_test, 155
- * **textstatistics**
 - chisquare, 22
- +, bundle, bundle-method (bundle-class), 18
- +, bundle, textstat-method (bundle-class), 18
- +, partition_bundle, ANY-method (partition_bundle-class), 114
- +, partition_bundle, partition-method (partition_bundle-class), 114
- +, partition_bundle, partition_bundle-method (partition_bundle-class), 114
- +, partition_bundle-method (partition_bundle-class), 114
- +, textstat, textstat-method (textstat-class), 146
- [, bundle, ANY, ANY, ANY-method (bundle-class), 18
- [, context, ANY, ANY, ANY-method (context-class), 28
- [, context-method (context-class), 28
- [, context_bundle, ANY, ANY, ANY-method (context_bundle-class), 31
- [, context_bundle-method (context_bundle-class), 31
- [, kwic, ANY, ANY, ANY-method (kwic-class), 95
- [, kwic-method (kwic-class), 95
- [, partition, ANY, ANY, ANY-method (partition_class), 116
- [, partition-method (partition_class), 116
- [, partition_bundle, ANY, ANY, ANY-method (partition_bundle-class), 114
- [, partition_bundle-method (partition_bundle-class), 114
- [, textstat, ANY, ANY, ANY-method (textstat-class), 146
- [[, bundle-method (bundle-class), 18
- [[, context-method (context-class), 28
- [[, context_bundle-method (context_bundle-class), 31
- [[, partition_bundle-method (partition_bundle-class), 114
- [[, textstat-method (textstat-class), 146
- [[<-, bundle-method (bundle-class), 18
- \$, bundle-method (bundle-class), 18
- \$, corpus-method (corpus-methods), 47
- \$<-, bundle-method (bundle-class), 18
- aggregate, slice-method (slice), 135
- annotations, 6
- annotations, kwic-method (annotations), 6
- annotations, textstat-method (annotations), 6
- annotations<- (annotations), 6
- annotations<-, kwic, list-method (annotations), 6
- annotations<-, textstat, list-method (annotations), 6
- as (as.VCorpus), 16
- as.bundle (textstat-class), 146
- as.bundle, list-method (bundle-class), 18

- as.bundle, textstat-method
(bundle-class), 18
- as.character, kwic-method (kwic-class),
95
- as.character, phrases-method
(phrases-class), 118
- as.corpusEnc (encodings), 68
- as.cqp (cqp), 57
- as.data.frame, cooccurrences_bundle-method
(cooccurrences-class), 44
- as.data.frame, kwic-method (kwic-class),
95
- as.data.frame, textstat-method
(textstat-class), 146
- as.data.table.bundle (bundle-class), 18
- as.data.table.ranges (ranges-class), 127
- as.data.table.regions (regions), 130
- as.data.table.textstat
(textstat-class), 146
- as.DataTables, context-method
(context-class), 28
- as.DataTables, textstat-method
(textstat-class), 146
- as.DocumentTermMatrix
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, bundle-method
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, character-method
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, context-method
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, corpus-method
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, kwic-method
(kwic-class), 95
- as.DocumentTermMatrix, partition_bundle-method
(as.TermDocumentMatrix), 13
- as.DocumentTermMatrix, subcorpus_bundle-method
(as.TermDocumentMatrix), 13
- as.list, bundle-method (bundle-class), 18
- as.list.bundle (bundle-class), 18
- as.markdown, 8
- as.markdown, partition-method
(as.markdown), 8
- as.markdown, plpr_partition-method
(as.markdown), 8
- as.markdown, plpr_subcorpus-method
(as.markdown), 8
- as.markdown, subcorpus-method
(as.markdown), 8
- as.matrix, bundle-method (bundle-class),
18
- as.matrix, context_bundle-method
(context), 24
- as.matrix, partition_bundle-method
(partition_bundle-class), 114
- as.nativeEnc (encodings), 68
- as.partition_bundle (partition_class),
116
- as.partition_bundle, list-method
(partition_bundle-class), 114
- as.partition_bundle, partition-method
(partition_class), 116
- as.partitionBundle (renamed), 133
- as.phrases (phrases-class), 118
- as.phrases, matrix-method
(phrases-class), 118
- as.phrases, ngrams-method
(phrases-class), 118
- as.regions (regions), 130
- as.regions, context-method
(context-class), 28
- as.regions, partition-method
(partition_class), 116
- as.simple_triplet_matrix, Cooccurrences-method
(Cooccurrences-class), 41
- as.sparseMatrix, 10
- as.sparseMatrix, bundle-method
(as.sparseMatrix), 10
- as.sparseMatrix, Cooccurrences-method
(Cooccurrences-class), 41
- as.sparseMatrix, DocumentTermMatrix-method
(as.sparseMatrix), 10
- as.sparseMatrix, simple_triplet_matrix-method
(as.sparseMatrix), 10
- as.sparseMatrix, TermDocumentMatrix-method
(as.sparseMatrix), 10
- as.speeches, 11
- as.speeches, character-method
(as.speeches), 11
- as.speeches, corpus-method
(as.speeches), 11
- as.speeches, partition-method
(as.speeches), 11
- as.speeches, subcorpus-method
(as.speeches), 11

- as.TermDocumentMatrix, [13](#), [46](#)
- as.TermDocumentMatrix, bundle-method (as.TermDocumentMatrix), [13](#)
- as.TermDocumentMatrix, character-method (as.TermDocumentMatrix), [13](#)
- as.TermDocumentMatrix, context-method (as.TermDocumentMatrix), [13](#)
- as.TermDocumentMatrix, kwic-method (kwic-class), [95](#)
- as.TermDocumentMatrix, partition_bundle-method (as.TermDocumentMatrix), [13](#)
- as.TermDocumentMatrix, subcorpus_bundle-method (as.TermDocumentMatrix), [13](#)
- as.utf8 (encodings), [68](#)
- as.VCorpus, [16](#), [61](#)
- as_igraph (Cooccurrences-class), [41](#)
- as_igraph, Cooccurrences-method (Cooccurrences-class), [41](#)

- barplot, partition_bundle-method (partition_bundle-class), [114](#)
- blapply, [17](#)
- blapply, bundle-method (blapply), [17](#)
- blapply, list-method (blapply), [17](#)
- blapply, vector-method (blapply), [17](#)
- browse (polmineR-defunct), [123](#)
- bundle, [113](#)
- bundle (bundle-class), [18](#)
- bundle-class, [18](#)

- capitalize, [21](#)
- check_cqp_query (cqp), [57](#)
- chisquare, [22](#), [101](#), [122](#), [156](#)
- chisquare, context-method (chisquare), [22](#)
- chisquare, cooccurrences-method (chisquare), [22](#)
- chisquare, features-method (chisquare), [22](#)
- colnames, textstat-method (textstat-class), [146](#)
- concatenate_phrases (phrases-class), [118](#)
- context, [24](#)
- context, character-method (context), [24](#)
- context, cooccurrences-method (context), [24](#)
- context, corpus-method (context), [24](#)
- context, matrix-method (context), [24](#)
- context, partition-method (context), [24](#)
- context, partition_bundle-method (context), [24](#)
- context, slice-method (context), [24](#)
- context, subcorpus-method (context), [24](#)
- context-class, [28](#)
- context_bundle-class, [31](#)
- Cooccurrences, [43](#)
- Cooccurrences (Cooccurrences, corpus-method), [36](#)
- cooccurrences, [31](#), [38](#), [46](#)
- Cooccurrences, character-method (Cooccurrences, corpus-method), [36](#)
- cooccurrences, character-method (cooccurrences), [31](#)
- cooccurrences, context-method (cooccurrences), [31](#)
- cooccurrences, Cooccurrences-method (cooccurrences), [31](#)
- Cooccurrences, corpus-method, [36](#)
- cooccurrences, corpus-method (cooccurrences), [31](#)
- Cooccurrences, partition-method (Cooccurrences, corpus-method), [36](#)
- cooccurrences, partition-method (cooccurrences), [31](#)
- cooccurrences, partition_bundle-method (cooccurrences), [31](#)
- cooccurrences, remote_corpus-method (cooccurrences), [31](#)
- cooccurrences, remote_subcorpus-method (cooccurrences), [31](#)
- Cooccurrences, slice-method (Cooccurrences, corpus-method), [36](#)
- cooccurrences, slice-method (cooccurrences), [31](#)
- Cooccurrences, subcorpus-method (Cooccurrences, corpus-method), [36](#)
- cooccurrences, subcorpus-method (cooccurrences), [31](#)
- Cooccurrences-class, [41](#)
- cooccurrences-class, [44](#)
- cooccurrences_bundle (cooccurrences-class), [44](#)

- cooccurrences_bundle-class
 - (cooccurrences-class), 44
- cooccurrences_reshaped-class
 - (cooccurrences-class), 44
- corpus, 119
- corpus (corpus-class), 45
- corpus, bundle-method (renamed), 133
- corpus, character-method (corpus-class), 45
- corpus, kwic-method (renamed), 133
- corpus, missing-method (corpus-class), 45
- corpus, textstat-method (renamed), 133
- corpus-class, 45
- corpus-methods, 47
- count, 46, 49
- count, character-method (count), 49
- count, context-method (context-class), 28
- count, corpus-method (count), 49
- count, kwic-method (kwic-class), 95
- count, partition-method (count), 49
- count, partition_bundle-method (count), 49
- count, remote_corpus-method (count), 49
- count, remote_subcorpus-method (count), 49
- count, subcorpus-method (count), 49
- count, subcorpus_bundle-method (count), 49
- count, vector-method (count), 49
- count-class (count_class), 53
- count-method (count), 49
- count_bundle-class (count_class), 53
- count_class, 53
- cp (textstat-class), 146
- cpos, 55
- cpos, character-method (cpos), 55
- cpos, corpus-method (cpos), 55
- cpos, hits-method (cpos), 55
- cpos, matrix-method (cpos), 55
- cpos, NULL-method (cpos), 55
- cpos, partition-method (cpos), 55
- cpos, slice-method (cpos), 55
- cpos, subcorpus-method (cpos), 55
- cqp, 57

- data_dir (registry_move), 131
- decode (decode-method), 59
- decode, character-method
 - (decode-method), 59
- decode, Cooccurrences-method
 - (Cooccurrences-class), 41
- decode, corpus-method (decode-method), 59
- decode, data.table-method
 - (decode-method), 59
- decode, integer-method (decode-method), 59
- decode, partition-method
 - (decode-method), 59
- decode, slice-method (decode-method), 59
- decode, subcorpus-method
 - (decode-method), 59
- decode-method, 59
- dim, textstat-method (textstat-class), 146
- dispersion, 46, 52, 63, 135
- dispersion, character-method
 - (dispersion), 63
- dispersion, corpus-method (dispersion), 63
- dispersion, hits-method (dispersion), 63
- dispersion, partition-method
 - (dispersion), 63
- dispersion, remote_corpus-method
 - (dispersion), 63
- dispersion, remote_subcorpus-method
 - (dispersion), 63
- dispersion, slice-method (dispersion), 63
- dispersion, subcorpus-method
 - (dispersion), 63
- dotplot, 66
- dotplot, features-method (dotplot), 66
- dotplot, features_ngrams-method
 - (dotplot), 66
- dotplot, partition-method (dotplot), 66
- dotplot, textstat-method (dotplot), 66

- edit, textstat-method (annotations), 6
- encoding, 67
- encoding, bundle-method (encoding), 67
- encoding, call-method (encoding), 67
- encoding, character-method (encoding), 67
- encoding, corpus-method (encoding), 67
- encoding, missing-method (encoding), 67
- encoding, quosure-method (encoding), 67
- encoding, subcorpus-method (encoding), 67
- encoding, textstat-method (encoding), 67
- encoding<- (encoding), 67
- encoding<- , call-method (encoding), 67

- encoding<-, quosure-method (encoding), 67
- encodings, 68
- enrich, 69
- enrich, context-method (context-class), 28
- enrich, Cooccurrences-method (Cooccurrences-class), 41
- enrich, kwic-method (kwic-class), 95
- enrich, partition-method (partition_class), 116
- enrich, partition_bundle-method (partition_bundle-class), 114
- enrich, subcorpus_bundle-method (partition_bundle-class), 114
- enrich-method (enrich), 69
- export (partition_class), 116
- export, partition-method (partition_class), 116

- features, 70
- features, Cooccurrences-method (features), 70
- features, count-method (features), 70
- features, count_bundle-method (features), 70
- features, ngrams-method (features), 70
- features, partition-method (features), 70
- features, partition_bundle-method (features), 70
- features-class, 72
- features_bundle-class (features-class), 72
- features_cooccurrences-class (features-class), 72
- features_ngrams-class (features-class), 72
- flatten (partition_bundle-class), 114
- format, cooccurrences-method (cooccurrences-class), 44
- format, features-method (features-class), 72
- format, kwic-method (kwic-class), 95
- format, textstat-method (textstat-class), 146

- get_corpus (corpus-class), 45
- get_corpus, bundle-method (bundle-class), 18
- get_corpus, corpus-method (corpus-methods), 47
- get_corpus, kwic-method (kwic-class), 95
- get_corpus, subcorpus-method (subcorpus), 136
- get_corpus, textstat-method (textstat-class), 146
- get_info (polmineR-generics), 123
- get_info, corpus-method (corpus-methods), 47
- get_template, 73
- get_template, character-method (get_template), 73
- get_template, corpus-method (get_template), 73
- get_template, subcorpus-method (get_template), 73
- get_token_stream, 74
- get_token_stream, character-method (get_token_stream), 74
- get_token_stream, corpus-method (get_token_stream), 74
- get_token_stream, matrix-method (get_token_stream), 74
- get_token_stream, numeric-method (get_token_stream), 74
- get_token_stream, partition-method (get_token_stream), 74
- get_token_stream, partition_bundle-method (get_token_stream), 74
- get_token_stream, regions-method (get_token_stream), 74
- get_token_stream, slice-method (get_token_stream), 74
- get_token_stream, subcorpus-method (get_token_stream), 74
- get_type, 79
- get_type, character-method (get_type), 79
- get_type, corpus-method (get_type), 79
- get_type, partition_bundle-method (get_type), 79
- get_type, subcorpus-method (get_type), 79
- get_type, subcorpus_bundle-method (get_type), 79
- getEncoding (renamed), 133
- getTerms (renamed), 133
- getTokenStream (renamed), 133

- head, context-method (context-class), 28

- head, textstat-method (textstat-class), 146
- highlight, 94
- highlight (highlight-method), 80
- highlight, character-method (highlight-method), 80
- highlight, html-method (highlight-method), 80
- highlight, kwic-method (highlight-method), 80
- highlight-method, 80
- hist, count-method (count_class), 53
- hits, 52, 81, 135
- hits, character-method (hits), 81
- hits, context-method (hits), 81
- hits, corpus-method (hits), 81
- hits, partition-method (hits), 81
- hits, partition_bundle-method (hits), 81
- hits, remote_corpus-method (hits), 81
- hits, remote_subcorpus-method (hits), 81
- hits, subcorpus-method (hits), 81
- hits-class (hits_class), 85
- hits_class, 85
- href (href-function), 86
- href-function, 86
- html, 87
- html, character-method (html), 87
- html, kwic-method (html), 87
- html, partition-method (html), 87
- html, partition_bundle-method (html), 87
- html, remote_subcorpus-method (html), 87
- html, subcorpus-method (html), 87
- is.cqp (cqp), 57
- is.partition (partition_class), 116
- is_nested, 89
- knit_print, kwic-method (kwic-class), 95
- knit_print, textstat-method (textstat-class), 146
- kwic, 46, 90, 98, 129
- kwic, character-method (kwic), 90
- kwic, context-method (kwic), 90
- kwic, Cooccurrences-method (Cooccurrences-class), 41
- kwic, corpus-method (kwic), 90
- kwic, partition-method (kwic), 90
- kwic, partition_bundle-method (kwic), 90
- kwic, remote_corpus-method (kwic), 90
- kwic, remote_partition-method (kwic), 90
- kwic, remote_subcorpus-method (kwic), 90
- kwic, slice-method (kwic), 90
- kwic, subcorpus-method (kwic), 90
- kwic, subcorpus_bundle-method (kwic), 90
- kwic-class, 95
- kwic_bundle-class (features-class), 72
- length, bundle-method (bundle-class), 18
- length, context-method (context-class), 28
- length, count-method (count_class), 53
- length, kwic-method (kwic-class), 95
- ll, 23, 35, 99, 122, 156
- ll, context-method (ll), 99
- ll, Cooccurrences-method (ll), 99
- ll, cooccurrences-method (ll), 99
- ll, features-method (ll), 99
- mail (polmineR-defunct), 123
- means, 102
- means, DocumentTermMatrix-method (means), 102
- merge, kwic_bundle-method (kwic-class), 95
- merge, partition_bundle-method (partition_bundle-class), 114
- merge, subcorpus-method (subcorpus_bundle-class), 138
- merge, subcorpus_bundle-method (subcorpus_bundle-class), 138
- name (textstat-class), 146
- name, character-method (textstat-class), 146
- name, corpus-method (corpus-methods), 47
- name, textstat-method (textstat-class), 146
- name<- (textstat-class), 146
- name<- , bundle-method (bundle-class), 18
- name<- , subcorpus-method (subcorpus), 136
- name<- , textstat-method (textstat-class), 146
- names, bundle-method (bundle-class), 18
- names, partition_bundle-method (partition_bundle-class), 114
- names, textstat-method (textstat-class), 146

- names<- , bundle, vector-method (bundle-class), 18
- ncol, textstat-method (textstat-class), 146
- ngrams, 103
- ngrams, character-method (ngrams), 103
- ngrams, corpus-method (ngrams), 103
- ngrams, data.table-method (ngrams), 103
- ngrams, list-method (ngrams), 103
- ngrams, partition-method (ngrams), 103
- ngrams, partition_bundle-method (ngrams), 103
- ngrams, subcorpus-method (ngrams), 103
- ngrams-class (ngrams_class), 106
- ngrams_class, 106
- noise, 106
- noise, character-method (noise), 106
- noise, DocumentTermMatrix-method (noise), 106
- noise, TermDocumentMatrix-method (noise), 106
- noise, textstat-method (noise), 106
- nrow, textstat-method (textstat-class), 146

- ocpu_exec, 107
- opencpu (ocpu_exec), 107

- p_attributes, 124
- p_attributes, character-method (p_attributes), 124
- p_attributes, context-method (context-class), 28
- p_attributes, corpus-method (p_attributes), 124
- p_attributes, partition-method (partition_class), 116
- p_attributes, partition_bundle-method (p_attributes), 124
- p_attributes, remote_corpus-method (p_attributes), 124
- p_attributes, remote_partition-method (p_attributes), 124
- p_attributes, slice-method (p_attributes), 124
- p_attributes, subcorpus-method (partition_class), 116
- p_attributes, textstat-method (textstat-class), 146

- partition, 108, 113
- partition, character-method (partition), 108
- partition, context-method (partition), 108
- partition, corpus-method (partition), 108
- partition, environment-method (partition), 108
- partition, partition-method (partition), 108
- partition, remote_corpus-method (partition), 108
- partition, remote_partition-method (partition), 108
- partition-class (partition_class), 116
- partition_bundle, 111
- partition_bundle, character-method (partition_bundle), 111
- partition_bundle, context-method (partition_bundle), 111
- partition_bundle, corpus-method (partition_bundle), 111
- partition_bundle, environment-method (partition_bundle-class), 114
- partition_bundle, partition-method (partition_bundle), 111
- partition_bundle, partition_bundle-method (partition_bundle), 111
- partition_bundle-class, 114
- partition_class, 69, 111, 116
- partition_to_string, 118
- partitionBundle (renamed), 133
- pAttributes (renamed), 133
- phrases (phrases-class), 118
- phrases-class, 118
- plpr_partition-class (partition_class), 116
- plpr_subcorpus-class (subcorpus), 136
- pmi, 23, 101, 121, 156
- pmi, context-method (pmi), 121
- pmi, Cooccurrences-method (pmi), 121
- pmi, ngrams-method (pmi), 121
- polmineR (polmineR-package), 4
- polmineR-defunct, 123
- polmineR-generics, 123
- polmineR-package, 4
- press_partition-class (partition_class), 116

- press_subcorpus-class (subcorpus), 136
- punctuation (trim), 153
- ranges, 125
- ranges, character-method (ranges), 125
- ranges, corpus-method (ranges), 125
- ranges, partition-method (ranges), 125
- ranges, subcorpus-method (ranges), 125
- ranges-class, 127
- read, 94, 127
- read, data.table-method (read), 127
- read, hits-method (read), 127
- read, kwic-method (read), 127
- read, partition-method (read), 127
- read, partition_bundle-method (read), 127
- read, regions-method (read), 127
- read, subcorpus-method (read), 127
- regions, 46, 119, 127, 130, 137
- regions, corpus-method (regions), 130
- regions, subcorpus-method (regions), 130
- regions-class (regions), 130
- registry, 157
- registry (registry_move), 131
- registry_move, 131
- remote_corpus (corpus-class), 45
- remote_corpus-class (corpus-class), 45
- remote_partition-class
 - (partition_class), 116
- remote_subcorpus-class (subcorpus), 136
- renamed, 133
- restore (textstat-class), 146
- round, textstat-method (textstat-class), 146
- rownames, textstat-method
 - (textstat-class), 146
- s_attribute_decode, 61
- s_attributes, 46, 61, 143
- s_attributes, call-method
 - (s_attributes), 143
- s_attributes, character-method
 - (s_attributes), 143
- s_attributes, context-method
 - (s_attributes), 143
- s_attributes, corpus-method
 - (s_attributes), 143
- s_attributes, data.table-method
 - (s_attributes), 143
- s_attributes, name-method
 - (s_attributes), 143
- s_attributes, partition-method
 - (s_attributes), 143
- s_attributes, partition_bundle-method
 - (s_attributes), 143
- s_attributes, quosure-method
 - (s_attributes), 143
- s_attributes, remote_corpus-method
 - (s_attributes), 143
- s_attributes, remote_partition-method
 - (s_attributes), 143
- s_attributes, slice-method
 - (s_attributes), 143
- s_attributes, subcorpus-method
 - (s_attributes), 143
- sample, bundle-method (bundle-class), 18
- sample, context-method (context-class), 28
- sample, hits-method (hits_class), 85
- sample, kwic-method (kwic-class), 95
- sAttributes (renamed), 133
- show, context-method (context-class), 28
- show, context_bundle-method
 - (context_bundle-class), 31
- show, cooccurrences-method
 - (cooccurrences-class), 44
- show, corpus-method (corpus-methods), 47
- show, features-method (features-class), 72
- show, html-method (html), 87
- show, kwic-method (kwic-class), 95
- show, partition-method
 - (partition_class), 116
- show, partition_bundle-method
 - (partition_bundle-class), 114
- show, subcorpus_bundle-method
 - (subcorpus_bundle-class), 138
- show, textstat-method (textstat-class), 146
- show_info (polmineR-generics), 123
- show_info, corpus-method
 - (corpus-methods), 47
- size, 46, 133, 137
- size, character-method (size), 133
- size, corpus-method (size), 133
- size, DocumentTermMatrix-method (size), 133

- size, features-method (size), 133
- size, partition-method (size), 133
- size, partition_bundle-method (size), 133
- size, remote_corpus-method (size), 133
- size, remote_partition-method (size), 133
- size, slice-method (size), 133
- size, subcorpus-method (subcorpus), 136
- size, TermDocumentMatrix-method (size), 133
- slice, 135
- slice-class (slice), 135
- sort, textstat-method (textstat-class), 146
- split (partition_class), 116
- split, corpus-method (subcorpus_bundle-class), 138
- split, partition-method (partition_class), 116
- split, subcorpus-method (subcorpus_bundle-class), 138
- split, subcorpus_bundle-method (subcorpus_bundle-class), 138
- subcorpus, 46, 119, 127, 131, 136
- subcorpus-class (subcorpus), 136
- subcorpus_bundle-class, 138
- subset, 137
- subset (subset-method), 140
- subset, bundle-method (bundle-class), 18
- subset, character-method (subset-method), 140
- subset, Cooccurrences-method (Cooccurrences-class), 41
- subset, corpus-method (subset-method), 140
- subset, kwic-method (kwic-class), 95
- subset, remote_corpus-method (subset-method), 140
- subset, subcorpus-method (subset-method), 140
- subset, subcorpus_bundle-method (subset-method), 140
- subset, textstat-method (textstat-class), 146
- subset-method, 140
- summary, context-method (context-class), 28
- summary, context_bundle-method (context_bundle-class), 31
- summary, count-method (count_class), 53
- summary, features-method (features-class), 72
- summary, features_bundle-method (features-class), 72
- summary, partition_bundle-method (partition_bundle-class), 114
- summary, subcorpus-method (subcorpus), 136
- t_test, 23, 101, 122, 155
- t_test, context-method (t_test), 155
- tail, textstat-method (textstat-class), 146
- terms, 145
- terms, character-method (terms), 145
- terms, corpus-method (terms), 145
- terms, partition-method (terms), 145
- terms, slice-method (terms), 145
- terms, subcorpus-method (terms), 145
- textstat-class, 146
- tooltips (tooltips-method), 151
- tooltips, character-method (tooltips-method), 151
- tooltips, html-method (tooltips-method), 151
- tooltips, kwic-method (tooltips-method), 151
- tooltips-method, 151
- tree_structure, 152
- tree_structure, corpus-method (tree_structure), 152
- tree_structure, subcorpus-method (tree_structure), 152
- tree_structure, xml_document-method (tree_structure), 152
- tree_structure, xml_node-method (tree_structure), 152
- trim, 153
- trim, context-method (context-class), 28
- trim, DocumentTermMatrix-method (trim), 153
- trim, TermDocumentMatrix-method (trim), 153
- trim-method (trim), 153
- unique, bundle-method (bundle-class), 18
- use, 156

view, [157](#)
view,cooccurrences-method
 (cooccurrences-class), [44](#)
view,cooccurrences_reshaped-method
 (cooccurrences-class), [44](#)
view,features-method (features-class),
 [72](#)
view,kwic-method (kwic-class), [95](#)
view,textstat-method (textstat-class),
 [146](#)
viewer, [7](#)

weigh, [158](#)
weigh,count-method (weigh), [158](#)
weigh,count_bundle-method (weigh), [158](#)
weigh,DocumentTermMatrix-method
 (weigh), [158](#)
weigh,TermDocumentMatrix-method
 (weigh), [158](#)

zoom (corpus-class), [45](#)